

## Scissor Hoists for Dump Trailers

• Brand new, Maxim scissor hoists rated for dump trailers with 8-20 ton capacities and 8-14' bodies (Not recommended for truck bodies). Designed for durability and safety. Used to move heavy loads of material off a dump trailer's bed with ease. Scissor hoists are much more robust and provide more lifting power than standard cylinder dumps. Also cost less than telescopic hoists, while providing similar lifting performance and reliability. A double-acting hydraulic power unit with free flow in extend and controlled flow in return is recommended for hoist only.

| Hoist Kits                                     |       | *Includes 12 Volt Hydraulic Power Unit |                          |        |          |                 |
|--|-------|--|--------------------------|--------|----------|-----------------|
| Item   | Model | Capacity                               | Trailer                  |        |          |                 |
|  |       | Tons                                   | Size                     | Body   | Shpg     | Price           |
| 300386   | 516   | 8-20                                   | 44" x 30.5" x 10.18"     | 8-12'  | 425 lbs. | <b>\$799.95</b> |
| 300388   | 520   | 10-20                                  | 49.13" x 33.03" x 11.57" | 10-14' | 425 lbs. | <b>\$899.95</b> |
| Hoist Only                                     |       |  |                          |        |          |                 |
| *Does not include 12 Volt Hydraulic Power Unit |       |  |                          |        |          |                 |
| Item   | Model | Capacity                               | Trailer                  |        |          |                 |
|  |       | Tons                                   | Size                     | Body   | Shpg     | Price           |
| 300387   | 516   | 8-20                                   | 44" x 30.5" x 10.18"     | 8-12'  | 380 lbs. | <b>\$599.95</b> |
| 300389   | 520   | 10-20                                  | 49.13" x 33.03" x 11.57" | 10-14' | 380 lbs. | <b>\$699.95</b> |

## Left & Right Hand Hydrostatic Transaxle Pair

**ITEM 604198 \$699.95**

• New, Tuff Torq left/right hand hydrostatic transaxle pair. Features 5" dia. belt-drive input pulley with 7" dia. fan, polymer fluid tank, heavy steel axles for added strength and control, aluminum case for professional-grade durability and dependable performance and an internal braking system. Designed to be used on residential zero-turn mowers

### SPECIFICATIONS

- Brand Tuff Torq
- Part Number 787Q2124020 & 787Q2124030
- Model Number TZ-450B-X
- Input Rotation CW
- Vehicle Speed Max. 10.5 mph
- Tire Size 23" max.
- Vehicle Weight max. w/ Attachments & Operator 1275 lbs. (578 kg)
- Reduction Ratio 18:1
- Pump/Motor Displacement 10/10 cc/rev
- Brake Capacity min. 180 lb-ft (180 Nm)
- Brake Arm Torque 11.7 lb-ft (15.8 Nm)
- Axle Torque 321 lb-ft (435 Nm)
- Fan Size dia. 7" (177.8 mm)
- Pulley Size dia. 5" (127 mm)
- Axel Length 4 1/8" (Housing to Face of Hub)
- Output Four bolt (1/2"-20 TPI) wheel hub on 4" B.C.
- Mount Six 0.38" dia. thru holes
- Size 15 1/2" x 15 1/4" x 9"
- Shpg 82 lbs. (Ships in two boxes)

**ITEM 604194 Left Hand \$399.95**

**ITEM 604195 Right Hand \$399.95**

## 9.5 HP Kohler Engine ▲

**ITEM 300365 \$299.95**

• New. KOHLER Command Pro Series horizontal engine. Features a heavy-duty air cleaner, forged-steel crankshaft, electronic ignition and cast-iron cylinder liner.

### SPECIFICATIONS

- Model CH395-3149
- Engine Family Command Pro Series
- Power 9.5 HP
- Torque 13.9 ft-lbs.
- Bore/Stroke 78mm/58mm
- Disp. 277 cc
- Speed 3000 RPM
- Start Recoil
- Fuel Tank 7.39 qt
- Shaft 1" dia. x 3.49" long
- Base Mount Four hole on 3 3/4" x 7 3/4" centers
- Accessory Mount: Inner 4 bolt on 5" B.C. Outer 4 bolt on 6.5" B.C.
- Size 15.9" x 16.8" x 16.7"
- Shpg. 80 lbs.



## 3 GPM Plunger Pumps

**ITEM 200821 \$119.95**

• New, plunger pump. Designed for a wide variety of moderate pressure washing applications. They are constructed with die-cast bodies and feature a brass head. Internal components include special thick solid ceramic plungers for long life and durability. Precision cast cooling fins are anodized for maximum heat dissipation. For use with gas engines with 5/8" hollow shaft and flange mount.

### SPECIFICATIONS

- Manufacturer Anovi Reverberi
- Model Number XTA 3G22 E
- Flow 3 gpm
- Pressure 2175 psi
- Rpm 1750
- Required HP 4.5 HP
- Rotation Reversible
- Shaft 5/8" hollow w/keyway
- Size 7 7/8" x 7 3/8" x 4.5"
- Flange Mount Four 0.405" slotted holes on 2 1/4" x 2 1/4" centers
- Body Mount Two M8-1.25 tapped holes on 1 1/8" centers and Four M8-1.25 tapped holes on 3 1/8" x 1 1/8" centers
- Inlet Ports 1/2" NPT
- Outlet Ports 3/8" NPT
- Shpg 17 lbs.

**ITEM 200820 \$119.95**

**SPECIFICATIONS SAME AS ABOVE EXCEPT**

- Model Number XTA 3G16 E
- Pressure 1595 psi

## 6.5 HP Horizontal Shaft Engine

**ITEM 300376 \$179.95**

## 6.5 HP Horizontal Shaft Engine



• New, BRIGGS & STRATTON XR Series horizontal shaft recoil start engine. Features a premium Dual Clean air filtration system and maintenance-free Magnetron electronic ignition. For utility and general applications like log splitters, pressure washers, compressors, and tillers. 49 state compliant, not for sale in California.

### SPECIFICATIONS

- Brand Briggs & Stratton
- Model Number 130G320063F1
- Engine Family XR
- Power 6.5 HP
- Bore/Stroke 2.756(70mm)/2.137" (54mm)
- Displacement 12.69 cu in (208cc)
- Speed 3600 RPM
- Start Recoil
- Fuel Tank Yes
- Shaft 3/4" dia. x 2 1/4" long w/ 3/16" keyway
- Base Mount Four hole on 3 1/8" x 6 3/8" centers
- Accessory Mount 4 bolt on 3 1/8" B.C.
- Size 14 1/2" x 12 1/2" x 15" (208cc)
- Shpg 45 lbs.



## Flow Control Valves

**\$86.65 Each**



• Brand new, Dynamic full-range pressure compensating variable flow control. Features a cast iron body, heat treated compensator spool and a stainless steel rotary spool. Designed so that the orifice area varies as the lever is rotated. The outlet flow is smooth and constant regardless of the pressure on the control flow or excess flow ports.

### SPECIFICATIONS

- Pressure 3000 PSI max.
- \* Relief Valve Adjustable 75 to 3000 PSI, preset to 2100 PSI
- Mount Two 17/64" holes thru body on 3.87" centers
- Size 5.78" x 4.56" x 2.87"
- Shpg 11 lbs.

| ITEM    | Model          | Ports    | GPM  |
|---------|----------------|----------|------|
| 907009* | DFC-R-51-12-S  | SAE 12   | 0-32 |
| 907016  | DFC-N-51-12-S  | SAE 12   | 0-32 |
| 907015  | DFC-N-51-10-S  | SAE 10   | 0-16 |
| 907008* | DFC-R-51-10-S  | SAE 10   | 0-16 |
| 907014  | DFC-N-51-08-S  | SAE 8    | 0-16 |
| 907007* | DFC-R-51-08-S  | SAE 8    | 0-16 |
| 907013  | DFC-N-51-06-S  | SAE 6    | 0-8  |
| 907006* | DFC-R-51-06-S  | SAE 6    | 0-8  |
| 907012  | DFC-N-51-3/4-N | 3/4" NPT | 0-30 |
| 907005* | DFC-R-51-3/4-N | 3/4" NPT | 0-30 |
| 907004* | DFC-R-51-1/2-N | 1/2" NPT | 0-16 |
| 907011  | DFC-N-51-1/2-N | 1/2" NPT | 0-16 |
| 907010  | DFC-N-51-3/4-N | 3/4" NPT | 0-8  |
| 907003* | DFC-R-51-3/4-N | 3/4" NPT | 0-8  |

## 13 HP Horizontal Shaft Engine



**ITEM 300374 \$199.95**

• New, POWERPRO horizontal shaft engine features overhead valves, cast iron sleeve liner, low-oil sensor, and electronic ignition. EPA certified. CARB compliant for 2020-2021.

### SPECIFICATIONS

- Model 2541-0048
- Power 13 HP
- Torque 19.6 ft-lbs
- Bore/Stroke 3.46" x 2.51" (54mm)
- Disp. 23.73 cu. inch
- Speed 3600 RPM
- Start Recoil
- Shaft 1" dia. x 3 5/8" keyed, tapped 3/8"-24
- Mount 3 3/4" x 7 1/16"
- Accessory Mount 5" bolt circle and 6.5" bolt circle
- Fuel Tank 1.7 gallons
- Size 14 1/2" x 18" x 17"
- Shpg. 81 lbs.