

## Hydrolico Vane Pumps

- Brand new, Hydrolico hydraulic vane pumps. Cast iron construction. Ports inline with one another.
- Input rotation CW • Mount SAE A 2 bolt
- SPECIFICATIONS** For V10 Series
- Inlet port 1" NPT • Outlet port 1/2" NPT • Shaft 3/4" dia. x 1.65" w/ 3/16" keyway



## Pneumatic Dust Collectors



### ITEM 100426

**\$249.95**

- New, Chicago Pneumatic CDP 10 dust collector. Heavy steel construction. Unit does not require power, only a reliable source of compressed air. For indoor and outdoor use. Intended for use with one hand-held rock drill or breaker with proper attachments. The ejector tube is located in a well protected position inside the filter and the housing-unit. Unit has three folding legs that need to be deployed on a flat surface before use. The rock cuttings and dust particles that are sucked into the dust collector are collected into a sack. The sack is secured around the cyclone part of the filter unit by the sack holder.

### SPECIFICATIONS

- Height of Housing Unit 30" (760mm)
- Brand Chicago Pneumatic
- Model Number CDP 10
- Air Consumption at 87 psi (6 bar) 23.3 to 25.4 cfm (11 to 12 l/s)
- Suction Hose 1 1/2" (38mm)
- Filter Surface Area 21 1/2 sq. ft. (2 m<sup>2</sup>)
- Collection Sack, Flat Dimensions 22" x 27.5" (560mm x 700mm)
- Diameter of Housing Unit 14 1/8" (365mm)
- Height above ground 51- 1/2" (1310mm)
- Shpg in Two Boxes
- First Box: 29 lbs. Dimensional (20 lbs. Actual)
- Second Box: 117 lbs. Dimensional (87 lbs. Actual)
- Total weight: 146 lbs. Dimensional (107 lbs. Actual)

### ITEM 100433

**\$249.95**

- Brand Atlas Copco. With multi-tool attachment

## SPECIFICATIONS For V20 Series

- Inlet port 1 1/4" NPT • Outlet port 3/4" NPT • Shaft 3/4" dia. x 2.655" w/ 3/16" keyway

ITEM	Model	Displ.	Max. RPM	PSI	GPM max.	Size	Shpg.	Price
906595	V20-1P5P-1C11	1.0	3400	2500	13.5	7.59" x 5.12" x 4.79"	19 lbs.	<b>\$286.55</b>
906596	V20-1P6P-1C11	1.19	3400	2500	16.1	7.59" x 5.12" x 4.79"	19 lbs.	<b>\$286.55</b>
906597	V20-1P7P-1C11	1.39	3000	2500	16.7	7.84" x 5.12" x 4.79"	20 lbs.	<b>\$286.55</b>
906598	V20-1P8P-1C11	1.62	2800	2500	17.7	7.84" x 5.12" x 4.79"	20 lbs.	<b>\$286.55</b>
906599	V20-1P9P-1C11	1.81	2800	2500	19.8	7.84" x 5.12" x 4.79"	20 lbs.	<b>\$286.55</b>
906600	V20-1P10P-1C11	2.0	2500	2500	20.6	8.04" x 5.12" x 4.79"	21 lbs.	<b>\$286.55</b>
906601	V20-1P11P-1C11	2.22	2500	2500	22.9	8.04" x 5.12" x 4.79"	21 lbs.	<b>\$286.55</b>
906602	V20-1P12P-1C11	2.38	2400	2200	23.4	8.18" x 5.12" x 4.79"	21 lbs.	<b>\$286.55</b>
906587	V20-1P13P-1C11	2.59	2400	2200	25.9	8.18" x 5.12" x 4.79"	21 lbs.	<b>\$286.55</b>



## Cross Control Valves

- Brand new CROSS directional control valve for operating double acting cylinders. Features include built-in adjustable pressure relief valve, open center, side inlet/outlet and top work ports. Integral load holding check valves. Can be converted to power beyond.

### SPECIFICATIONS

- Max. 25 GPM
- Max. 3000 PSI
- Adjustable relief valve 1500-3000 PSI factory set at 2000 PSI
- Spring centering

#### NPT Ports

- IN/OUT 3/4" NPT,
- Work Ports 1 1/2" NPT

#### SAE Ports

- IN/OUT SAE 12
- Work Ports SAE 10



Available with your choice of NPT or SAE ports

### One Spool Valves 30 GPM

NPT Ports ITEM Price	SAE Ports ITEM Price	Style	Size	Shpg.
906138 <b>\$243.95</b>	906139 <b>\$243.95</b>	DA spring centered	13.25" x 7.3" x 4.88"	16 lbs.

### Two Spool Valves 30 GPM

NPT Ports ITEM Price	SAE Ports ITEM Price	Style	Size	Shpg.
906140 <b>\$371.10</b>	906141 <b>\$374.75</b>	DA spring centered	13.25" x 7.3" x 7.13"	24 lbs.
906145 <b>\$423.00</b>	906146 <b>\$435.40</b>	DA spring centered w/float	13.25" x 7.3" x 7.13"	25 lbs.

### Three Spool Valves 30 GPM

NPT Ports ITEM Price	SAE Ports ITEM Price	Style	Size	Shpg.
906143 <b>\$491.35</b>	906144 <b>\$496.15</b>	DA spring centered	13.25" x 7.3" x 7.13"	37 lbs.
906149 <b>\$548.55</b>	906150 <b>\$582.95</b>	DA spring centered w/float	13.25" x 7.3" x 7.13"	37 lbs.



## 7.9 GPM Gear Pump

### ITEM 200883

**\$29.95**



### ITEM 200883

**\$29.95**

- New, Shurflo heavy duty cast iron pedestal rotary external gear pump. These pumps are specifically designed to be used with oil-based fluids, not to be used with water-based fluids. Pumps include steel spur gears with steel shafts and cast iron shaft support.

### SPECIFICATIONS

- Brand Shurflo
- Model Number GPCV3-01-09
- Max. Flow 7.9 GPM
- Max. Pressure 125 PSI
- Max. RPM 1725
- Ports 1/2" NPT
- Rotation Reversible
- Shaft 5/8" dia. x 1 7/8" long w/ 3/16" keyway
- Mount Two 0.387" holes on 2 1/2" centers
- Size 7" x 3 3/4" x 4 1/8"
- Shpg 8 lbs.