



### 13200 BTU 12 VDC Cab Heater With 2 Speed Fan



### 12500 BTU 12 VDC Cab Heater With 3 Speed Fan



#### ITEM 300220

**\$299.55**

• Brand new, MARADYNE Model H-400012 cab heater. Heater uses engine coolant to heat your cab. Mounts easily to floor of cab. 2 speed fan with speed control switch built into the housing. Four, rotatable, adjustable opening louvers. Glass-filled nylon housing, aluminum tube and fin heating core.

#### SPECIFICATIONS

- Heating Output 13200 BTU/HR
- Air Flow 200 CFM
- Blower Motor Voltage 12 VDC
- Size 7 $\frac{3}{8}$ " x 7 $\frac{1}{4}$ " x 9 $\frac{1}{2}$ "
- Blower Motor Amperage 6 amps
- Hose Fittings  $\frac{5}{8}$ " dia. x 1 $\frac{1}{4}$ " hose barb
- Mount Three  $\frac{5}{16}$ "-18 x 1" studs
- Shpg. 10 lbs.

#### ITEM 300219

**\$205.90**

• Brand new, MARADYNE cab heater. Heater uses engine coolant to heat your cab. Mounts easily to wall or floor of cab. 3 speed fan. Directional airflow doors. Steel housing, aluminum tube and fin heating core. Comes with 3 speed fan switch.

#### SPECIFICATIONS

- Heating Output 12500 BTU/HR
- Air Flow 200 CFM
- Blower Motor Voltage 12 VDC
- Size 7 $\frac{1}{16}$ " x 7 $\frac{3}{8}$ " x 7 $\frac{1}{16}$ "
- Blower Motor Amperage 2.9 amps
- Hose Fittings  $\frac{5}{8}$ " dia. x 1 $\frac{1}{2}$ " hose barb
- Mount Three  $\frac{5}{16}$ "-18 x 1" studs
- Shpg. 11 lbs.

### Flat Document Holders



• Brand new. Molded plastic construction with two latches for lid and rubber seal to keep manuals, service records or other documents clean and dry. Four holes for mounting.

Holds 8 $\frac{1}{2}$ " x 11" documents

#### ITEM 300216

**\$11.95**

#### SPECIFICATIONS

- ServiceMate SM9000-8
- Document Size 8.5" x 11" x 1"
- Label area 6.25" x 2.75"
- Size 14.5" x 11" x 2.135"
- Mounting pattern 5.875" x 7"
- Shpg. 3 lbs.

Holds 6" x 8" documents

#### ITEM 300218

**\$9.55**

#### SPECIFICATIONS

- ServiceMate SM9000-16
- Document Size 6" x 8" x 1"
- Label area 5" x 2.75"
- Size 11.2" x 8.25" x 1.95"
- Mounting pattern 4.25" x 6" (T pattern)
- Shpg. 3 lbs.

### Round Document Holder



#### ITEM 300217

**\$7.80**

• Brand new, SERVICEMATE SM9000-14, holds rolled up 8 $\frac{1}{2}$ " x 11" documents. Molded plastic construction with twist lock lid and rubber seal to keep manuals, service records or other documents clean and dry.

#### SPECIFICATIONS

- Document Size 8.5" x 11" x 1"
- Label area 5.25" x 1.75"
- Size 3.7" dia. x 12.5"
- Shpg.  $\frac{1}{4}$  lb.



### Cab Heater Installation Kit

**\$46.00**

#### SPECIFICATIONS

- One, shut-off valve  $\frac{3}{8}$ " NPTM x  $\frac{5}{8}$ " hose barb
- One,  $\frac{3}{8}$ " NPTM x  $\frac{5}{8}$ " hose barb
- Two,  $\frac{1}{2}$ " NPTM x  $\frac{3}{8}$ " NPTF bushing
- Four,  $\frac{5}{8}$ " hose clamps
- Shpg.  $\frac{1}{2}$  lb.

### 12 Volt Digital Hourmeter



#### ITEM 501019

**\$25.00**

• Brand new. Shows running time of equipment. Digital design, no moving parts. Spade terminals. Includes metal clamp mounting bracket to hold meter in place in a panel. Chrome bezel.

#### SPECIFICATIONS

- Operates on 12/24 volts DC
- Non-resettable
- Panel mount in 2" diameter hole
- Shpg.  $\frac{1}{4}$  lb.

### 12-24 VDC Back-Up Alarms

• Brand new, BUYERS back-up alarms. Plastic housing, epoxy sealed from moisture, dust and vibration. Self grounding. Back up alarm should be louder than background noise of all jobsites vehicle is used at. Meets OSHA, Bureau of Mines, GSA and all state regulations. Conforms to J994 criteria.

• Voltage 12-24 VDC. Mount two  $\frac{1}{4}$ " holes on side or base. Shpg.  $\frac{3}{4}$  lb.



ITEM	Decibels	Size	Price
500664	97 dB	4 $\frac{1}{4}$ " x 2 $\frac{3}{4}$ " x 2"	<b>\$18.75</b>
500665	102 dB	4 $\frac{5}{16}$ " x 2 $\frac{7}{8}$ " x 2"	<b>\$20.05</b>
500666	107 dB	4 $\frac{3}{16}$ " x 3 $\frac{3}{8}$ " x 2"	<b>\$20.50</b>

### Magnetic Engine Block Heaters

• Brand new, KAT'S MAGNUM HAN-DI-HEAT magnetic heaters. General application usage includes hydraulic reservoirs, thawing frozen locks, pipes, gutters and live stock feeders.

#### 200 Watt

#### ITEM 500810

**\$84.95**

• Ideal for small engine blocks. Thermostatically controlled.

#### SPECIFICATIONS

- Voltage 120 Volts AC
- Power 200 W
- Cord Length 43"
- Heated surface dimension 3 $\frac{3}{4}$ " x 2 $\frac{1}{4}$ "
- Size 6 $\frac{1}{2}$ " x 2 $\frac{1}{4}$ " x 2"
- Shpg. 1 lb.



#### 300 Watt

#### ITEM 500811

**\$141.00**

• Ideal for car and truck engine blocks.

#### SPECIFICATIONS

- Voltage 120 Volts AC
- Power 300 W
- Cord Length 42"
- Heated surface dimension 4 $\frac{1}{8}$ " x 5"
- Size 7" x 5" x 2"
- Shpg. 1 $\frac{1}{2}$  lbs.

### Backup Alarm

#### ITEM 501586

**\$19.95**

• New, Ingersoll Rand multi tone warning alarm.

#### SPECIFICATIONS

- Brand Ingersoll Rand
- Model 19295435
- Decibels Unknown
- Voltage Unknown
- Plug Three pin
- Mount Two 0.21" slotted holes on 3" centers
- Size 4" x 2 $\frac{3}{4}$ " x 1"
- Shpg. 0.55 lb.



### 12 Volt Hourmeters

• Brand new. Shows running time of equipment. 12 volt DC (will operate on 10-80 VDC). Non-resettable. Shpg.  $\frac{1}{4}$  lb.



ITEM 500103



ITEM 500384



ITEM 500385

Panel Opening And				
ITEM	Front Face	Mount	Rear Clearance Required	Price
500103	2 $\frac{3}{8}$ " O.D.	Rear Clamp	2" dia. x 1 $\frac{1}{4}$ "	<b>\$29.90</b>
500384	2 $\frac{7}{8}$ " O.D.	3 holes in flange 2 $\frac{1}{2}$ " B.C.	2" dia. x 1 $\frac{1}{4}$ "	<b>\$31.60</b>
500385	2 $\frac{1}{8}$ " x 1 $\frac{1}{4}$ "	2 holes in flange 1 $\frac{3}{4}$ " c/c	1" x 1 $\frac{1}{2}$ " x 2 $\frac{3}{8}$ "	<b>\$29.90</b>

### 12 VDC Electronic Fuel Pumps



• Brand new, FACET solid state electronic fuel pumps. For carbureted gas, diesel and blended fuel engines.

**Not intended for any aircraft use.**

#### SPECIFICATIONS

- Voltage 12 Volts DC
- Amps 1.6
- Ports  $\frac{1}{8}$ " NPT female
- Size 3" x 3 $\frac{1}{4}$ " x 2 $\frac{3}{8}$ "
- Shpg. 2 lbs.

Range Flow				
ITEM	Model	Pressure	Flow (GPH)	Price
300231	40104	1.5-4 PSI	25	<b>\$68.00</b>
300238*	40102	1.5-4 PSI	25	<b>\$73.10</b>
300239	40106	4-7 PSI	32	<b>\$68.00</b>
300240	40185	9-11.5 PSI	32	<b>\$85.10</b>

\* Same as 300231 but includes brass adapters to  $\frac{5}{16}$ " ID hose and mounting hardware.