

Water System Automatic Pressure Switches

• Brand new, LEFOO automatic pressure switch for automatic water systems. Automatically turns pump ON or OFF at set values. Adjustable differential. Sturdy plastic housing. Single port.

ITEM 400263

\$13.95

SPECIFICATIONS

- Contact ratings
1½ HP at 120 VAC
2 HP at 230 VAC
3 HP at 240 VAC 3Ph
- Factory setting
ON (cut-in) 40 PS
OFF (cut-out) 60 PSI
- Min. ON (cut-in) 20 PSI
• Max. OFF (cut-out) 80 PSI
• Differential 15-35 PSI
• Port ¼" NPT
• Size 3 ¾" x 2 ½" x 3 ¾"
• Shpg. 1 ½ lbs.



ITEM 400262

\$13.95

SPECIFICATIONS

- Contact ratings
1 ½ HP, 20 amps at 120 VAC
2 HP, 12 amps at 240 VAC
3 HP, 9.6 amps at 240 VAC
3Ph
- Factory setting
ON (cut-in) 30 PS
OFF (cut-out) 50 PSI
- Min. ON (cut-in) 30 PSI
• Max. OFF (cut-out) 100 PSI
• Differential 20-35 PSI
• Port ¼" NPT
• Size 3 ½" x 2 ¼" x 3 ½"
• Shpg. 1 ½ lbs.



Simer Water Pump

ITEM 200306

\$39.95

• New, SIMER. Flexible impeller pump. Use to pump water, brine solutions and light lubricating oils. **WARNING:** This pump should never be used to pump flammable fluids! Wired with a 4 ft. power cord with on/off switch and alligator clips. Permanent magnet motor. Includes two garden hose to ½" hosebarb adapters and instructions.

SPECIFICATIONS

- 1,140 liters/hour (301 GPH)
- 24 Volt DC
- Self-priming to 9 feet
- 20 PSI max.
- Max 118°F
- Male garden hose thread ports
- Base mount
- Overall size 7 ½" x 4 ½" x 4 ½"
- Shpg. 7 lbs.



12 VDC Submersible Pump



ITEM 200678

\$13.95

• New. Submersible, brushless impeller pump. Can be mounted in or under tank. Sold with 115 Volt AC to 12 Volt DC adapter with on/off switch (needs alteration to mate with leads from pump). Pump is not self-priming.

SPECIFICATIONS

- Voltage 12 VDC
- Amperage 0.36 Amps @ 12 Volt DC, Dry
- Flow 6 GPM @ 0' head pressure
- Max Head Pressure 6.5'
- Input 17mm (0.669") O.D. hose
- Output 12mm (0.472") O.D. hose
- Leads 6"
- Size 3 ¾" x 2 ½" x 1 ¼"
- Shpg. 1 lb.

115 VAC Coolant Recirculating Pump

ITEM 200590

\$27.95

• New, BECKETT model BJ5A coolant recirculating pedestal pump. Ideal replacement or use with evaporative coolers, displays, laboratories and other water transfer applications. Features include polystyrene column and cap, ABS base plate and a ½" OD PVC adapter. ODP motor with fan and cover.

SPECIFICATIONS

- Voltage 115 Volt AC
- Amperage 0.9 Amps
- Power 1/70 HP
- Flow Rates
340 GPH @ 1 ft. head
255 GPH @ 4 ft. head
200 GPH @ 6 ft. head
130 GPH @ 8 ft. head
40 GPH @ 10 ft. head
- Speed 3000 RPM
- Shut-off @ 10.1 ft. head
- Duty Continuous
- Power Cord 3 foot 18/3
- Inlet Base
- Discharge ½" hose barb with adapter
- Size 4 ½" diameter x 9" high
- Shpg. 5 lbs.



120 VAC Submersible Pump

ITEM 200705

\$29.95

• New, DK-5000 submersible water pump. Ideal for fountains, ponds, machine tool coolant. Plastic housing, plastic impeller. Slotted intake cover can be easily removed for cleaning. Four suction cups on base. Includes a brass adapter to ¾" ID tubing.

SPECIFICATIONS

- Voltage 120 Volt AC
- Power Consumption 105 Watts
- Flow 20 GPM open flow
- Max Head 15 ft.
- Size 7" x 4" x 5"
- Port ¾" MGHT (Standard Garden Hose Male) w/ ¾" ID hose adapter
- Power Cord 15 ft. long, 3-prong plug
- Shpg. 8 lbs.



Tuthill Manual Transfer Pump

ITEM 300167

\$19.99

• New, TUTHILL Series 20 hand lever piston pump for pumping fluid into a container. Polypropylene housing, BUNA N seals. Economical manual transfer pump ideal for use on barrels, drums and storage tanks. Anti-drip nozzle, check valve and 360° locking ring. Telescoping suction pipe fits up to 36" high container. Compatible with water, gear oils, engine oils, paraffin, fertilizers, mild acids, anti-freeze, hydraulic oils, diesel, degreasers, herbicides and pesticides. Not for use with gasoline, ethanol or methanol.

SPECIFICATIONS

- Flow 11 fl. oz. per stroke
- Viscosity SAE 90 max.
- Bung Adapter 2" NPS
- Inlet 1" NPT
- Outlet Nozzle with strainer
- Size 9 ¼" x 3 ½" x 12"
- Shpg. 5 lbs.



12 VDC Diaphragm Pump

ITEM 200702

\$19.99

• New, DELAVAN automatic demand diaphragm pump. Ideal for spot sprayers or as replacement on existing equipment. Santoprene diaphragm and Viton valves. Automatic shut off switch set to 40 PSI. Pump turns on at 25 PSI. Self priming to 4 foot suction lift. Can run dry intermittently without damage. Wire leads. Rubber vibration damper mounting feet.

SPECIFICATIONS

- Voltage 12 Volt DC
- Amperage 2.6 Amps
- Flow Rates
1 GPM @ open flow
0.85 GPM @ 10 PSI
0.71 GPM @ 20 PSI
0.61 GPM @ 30 PSI
0.42 GPM @ 40 PSI
- Shut-Off Pressure 40 PSI
- Ports ¾" Hosebarb QA port adapters
- Duty Intermittent
- Temperature 110°F max.
- Mount Four bolt on 3.19" x 2.25" pattern
- Size 7" x 3 ½" x 2 ¾"
- Shpg. 2 lbs.



Line Strainers

ITEM 200124

\$15.35

ITEM 200125

\$16.55

ITEM 200126

\$22.50



½" IPS Brass Gate Valve

ITEM 200594

\$4.99

• New, CHAMPION-ARROWHEAD lead-free brass gate valve. Full port. IPS (Iron Pipe Straight) ports.

SPECIFICATIONS

- Ports ½" IPS
- Pressure Max 200 PSI
- Size 2" x 1 ¼" x 3 ¼"
- Shpg. ½ lb.



12 VDC Centrifugal Pump

ITEM 200200

\$349.05

• Brand new HYPRO "Aqua-Tiger" bronze centrifugal pump. Use for ag chemical transfer, live well aeration, circulation, etc. Permanent magnet motor. Not self-priming.

SPECIFICATIONS

- 12 Volt DC
- 5.5 amps
- Max. flow 19 GPM
- Max. 7 PSI
- Max 140°F
- Ports ¾" NPT
- 7" x 4 ½" x 4"
- Shpg. 8 lbs.

