

Cast Iron High Speed Gearboxes

ITEM 603513

• Brand new. PEERLESS cast iron gearbox. Shafts rotate in opposite direction.

SPECIFICATIONS

- Model 1050-009A
- Ratio 1:1
- Rotation Opposite
- Input Power 10 HP max continuous
- Input Speed 3600 RPM max.
- Output Torque 360 in-lb
- Input Shaft $\frac{3}{4}$ " dia. x $1\frac{5}{8}$ " w/ $\frac{3}{16}$ " woodruff keyway
- Output Shaft $\frac{3}{4}$ " dia. x $1\frac{5}{8}$ " w/ $\frac{5}{32}$ " woodruff keyway
- Mount Two $\frac{3}{8}$ -16 bolt holes on 4" centers and 2.9" dia. pilot
- Size 7" x $5\frac{3}{4}$ " x $4\frac{3}{4}$ "
- Shpg. 13 lbs.



\$417.10

ITEM 603514

\$426.05

SPECIFICATIONS SAME AS ABOVE EXCEPT

- Model 1015-012 • Ratio 1.2:1 • Rotation Same

Aluminum High Speed Gearboxes

ITEM 603491

\$264.85

• Brand new. PEERLESS 1000-014-D gearbox. Cast aluminum gearbox and ships with oil. Shafts rotate in same direction when viewed from end.

SPECIFICATIONS FOR ALL

- Ratio 1:1
- Input Power: 10 HP continuous
- Input Speed: 3600 RPM max.
- Output Torque 360 in-lbs.
- Size $5\frac{1}{2}$ " x $4\frac{3}{4}$ " x 7"
- Input Shaft: $\frac{7}{8}$ " dia. x $1\frac{1}{2}$ " w/ $\frac{3}{16}$ " woodruff keyway
- Output Shaft: $\frac{7}{8}$ " dia. x $1\frac{1}{2}$ " w/ $\frac{5}{32}$ " woodruff keyway and $\frac{3}{8}$ -24 tapped end
- Mount: Two $1\frac{3}{32}$ " bolt holes on 4" centers, 2.92" dia. pilot
- Shpg. 8 lbs.



ITEM 603492

\$257.50

• PEERLESS 1000-015 gearbox. Shafts rotate in opposite directions when viewed from end. Shpg. 8 lbs.

3 Shaft Gearbox

ITEM 603493

\$262.90

• Brand new. PEERLESS 1000-007 gearbox. Solid output shaft extends from both sides of case. Shpg. 9 lbs.



Stewart Differential Axles



• New, STEWART MANUFACTURING. Differential assembly with disc brake. Die cast aluminum differential case and 1215 cold drawn steel axle shaft with black oxide coating applied to axle shafts. 1" Diameter.

SPECIFICATIONS FOR BOTH

- Axle Dia. 1"
- Disc Brake Dimensions
- Axle Threads 1"-14 TPI x 1" 8.875" dia. x 0.179"
- Sprocket 28 tooth 081 Pitch

ITEM 604134

\$39.95

35" Model# 50-000059

SPECIFICATIONS

- Size 35" x $8\frac{3}{4}$ " x $8\frac{3}{4}$ "
- Axle Lengths 14 $\frac{3}{4}$ ", 13 $\frac{3}{4}$ "
- Shpg. 26 lbs.

ITEM 604135

\$49.95

48" Model# 50-000121

SPECIFICATIONS

- Size 48" x $8\frac{3}{4}$ " x $8\frac{3}{4}$ "
- Axle Lengths 20", 20 $\frac{3}{4}$ "
- Shpg. 20 lbs.

Transaxles and Right Angle Gearboxes



Right Angle Gearboxes

• Brand new. Right angle gearboxes. One piece cast iron gear case and bearing caps. Roller bearings. Ships without oil, user must add $\frac{1}{2}$ quart of 80-90 W oil prior to use.



SPECIFICATIONS FOR ALL

- Ratio 1:1
- Input Shaft $\frac{3}{4}$ " dia. x $1\frac{5}{8}$ " w/ $\frac{3}{16}$ " woodruff keyway
- Output Shaft $\frac{3}{4}$ " dia. x $1\frac{5}{8}$ " w/ $\frac{5}{32}$ " woodruff keyway
- Mount Two $\frac{3}{8}$ -16 bolt holes on 4" centers and 2.9" dia. pilot
- Size 7" x $5\frac{3}{4}$ " x $4\frac{3}{4}$ "
- Shpg. 13 lbs.

ITEM	Input Shaft	Output rotation	Price
602823	1" dia. x $2\frac{1}{2}$ " w/ $\frac{1}{4}$ " keyway	Opposite of input	\$211.30
602822	1" dia. x $2\frac{1}{2}$ " w/ $\frac{1}{4}$ " keyway	Same as input	\$211.30
602824	1" dia. x $2\frac{1}{2}$ " w/ $\frac{1}{4}$ " keyway	Dual Shaft	\$251.75
604021	1" dia. x $2\frac{1}{2}$ " w/ $\frac{5}{16}$ " crosshole and $\frac{1}{4}$ " keyway	Dual Shaft	\$251.75

Peerless Differential Axle



ITEM 603503

3/4" Diameter

\$187.85

• Brand new. PEERLESS differential. Can be used with PEERLESS 700 series transmission, a gas engine, or electric motor (sold separately) for residential or commercial use. Axle is not heat treated. Used with related PEERLESS drive sprockets (sold separately).

SPECIFICATIONS

- Model 100-007B
- Axles $\frac{3}{4}$ " dia. x 16" smooth shaft
- Mount: Two $1\frac{3}{32}$ " bolt holes on 4" centers, 2.92" dia. pilot
- Shpg. 11 lbs.
- Output Torque 150 ft-lb max
- Load Rating 400 lb max
- Size $39\frac{3}{8}$ " x $3\frac{5}{8}$ " x $3\frac{3}{8}$ "

Peerless Differential Axle



ITEM 603504

1" Diameter

\$287.70

• Brand new. PEERLESS 100-224 differential. Can be used with PEERLESS 700 series transmission, a gas engine, or electric motor (sold separately) for residential or commercial use. Axle is not heat treated. Use with related PEERLESS drive sprockets (sold separately).

SPECIFICATIONS

- Brand Peerless Model 100-224
- Axles 1" dia. x $14\frac{1}{2}$ " w/ $\frac{1}{4}$ " x 6" keyway and $\frac{1}{4}$ " x 1" threaded $\frac{3}{4}$ -16 UNF x $1\frac{1}{8}$ "
- Output Torque 150 ft-lb max
- Tire Diameter 20" max
- Load Rating 600 lb max
- Size 38" x $3\frac{5}{8}$ " x $3\frac{3}{8}$ "
- Shpg. 14.5 lbs.
- Tire Diameter 20" max
- Load Rating 600 lb max
- Size 38" x $3\frac{5}{8}$ " x $3\frac{3}{8}$ "

Peerless Differential Sprockets

• Brand new. PEERLESS sprocket for differential

SPECIFICATIONS

- Bolt Holes Four $0.35\frac{1}{2}$ " dia. for $\frac{5}{16}$ -18 stud
- Bolt Hole Pattern $0.941\frac{1}{2}$ " x $2.81\frac{1}{2}$ "



ITEM	Pitch	Bore	Teeth	O.D.	Shpg.	Price
603509	35	2 $\frac{1}{8}$ "	36	4.51"	1/2	\$54.15
603506	40	2 $\frac{1}{8}$ "	45	7.45"	2 $\frac{1}{2}$	\$88.55
603505	41	2 $\frac{1}{8}$ "	40	6.81"	2	\$48.40
603507	41	2 $\frac{1}{8}$ "	48	7.93"	2	\$62.50
603508	41	2 $\frac{1}{8}$ "	60	9.84"	5	\$68.95

Hydrogear Hydrostatic Transaxle

ITEM 602786

\$249.95



ITEM 602786

\$249.95

• New, Hydro-gear ZT-2200 EZT series model ZC-AHBB-4M7B-2FPA zero-turn style hydrostatic transaxle. Includes right transaxle for building ZTR vehicles or for use as replacement on equipment. Integrated 10cc variable displacement axial pump and a 10cc fixed displacement drive motor. Features include a die cast aluminum housing, belt-drive input pulley with fan, single control lever per unit for forward/reverse and speed control, disengagement lever to allow freewheeling, four bolt hub for direct mounting of wheel and parking brake.

SPECIFICATIONS

- Input Speed 3000 RPM max.
- Overall Reduction 19.2:1
- Output Speed 0-150 RPM
- Engine Size 18-22 HP
- Output Torque Continuous 115 ft-lbs. Intermittent 150 ft-lbs.
- Max. Weight per Axle 18" Diameter Tire 340 lbs. 20" Diameter Tire 300 lbs.
- Max. Tire Dia. 20"
- Input Rotation CW
- Input 4 $\frac{1}{2}$ " dia. pulley for $\frac{1}{2}$ " belt
- Axle Length: 4 $\frac{1}{8}$ " housing to face of hub
- Output 4 bolt wheel hub on 4" B.C.
- Mount 6 hole
- Lubrication 20W-50 motor oil
- Size 14 $\frac{3}{4}$ " x 14 $\frac{1}{4}$ " x 10 $\frac{1}{4}$ "
- Shpg. 44 lbs.

Peerless Six Speed Transaxles

ITEM 603510

\$509.55



ITEM 603510

\$509.55

• Brand new. PEERLESS MST-206-545C six speed transaxle. Push brake lever to actuate brake. "Axe-Rearward" style transaxle pre-filled with oil from the factory.

SPECIFICATIONS

- Speeds: Six forward, Reverse, and Neutral
- Input Speed 2,000 RPM
- Input Rotation CW
- Output Torque 225 ft-lbs
- Load Rating 525 lbs max
- Input Shaft $\frac{5}{8}$ " dia. x $1\frac{1}{8}$ " w/ $\frac{5}{16}$ " keyway
- Axles $\frac{3}{4}$ " dia. x $4\frac{3}{4}$ " long w/ $\frac{5}{16}$ " keyway
- Overall Axle Width 29 $\frac{1}{8}$ "
- Tire Diameter 20" max
- Gear Shift Shaft $\frac{3}{8}$ " square, tapped $\frac{1}{4}$ -28
- Inner Mount Four holes on 13" x 1 $\frac{1}{4}$ " centers
- Outer Mount Four holes on 16 $\frac{1}{4}$ " x 2 $\frac{1}{2}$ " centers
- Size 29 $\frac{1}{8}$ " x 12 $\frac{1}{2}$ " x 8"
- Shpg 33 lbs.

w/Pull Brake Lever

ITEM 603511

\$522.55

w/Pull Brake Lever/Axle Forward

ITEM 603512

\$525.85