

Double Roller Chain Couplers

- Brand new. Three piece chain coupler consist of two sprockets connected together with double roller chain. Sold as individual halves and chain. Purchase two halves and one coupler chain to make a complete coupling.



Pitch & Tooth Count	Max. RPM	Max. Torque Ft.-Lbs.	Max HP at RPM	Coupling O.D.	Coupled Length
40 Pitch 16 Tooth	5000	80.5	73.6 at 4800 RPM	3.03"	3.44"
50 Pitch 16 Tooth	4000	159.6	109.4 at 3600 RPM	3.78"	3.92"
60 Pitch 18 Tooth	3000	407.5	194.5 at 2500 RPM	5"	4.86"

Keyed Half

- Furnished with standard keyway and setscrews.

Item	Pitch	Tooth	Shpg	Price
5/8" Bore				
602832	40	16	2lbs.	\$18.05
3/4" Bore				
602833	40	16	2lbs.	\$18.05
602841	50	16	3lbs.	\$22.40
7/8" Bore				
602834	40	16	2lbs.	\$18.05
602842	50	16	3lbs.	\$22.40
1" Bore				
602835	40	16	2lbs.	\$18.05
602843	50	16	3lbs.	\$22.40
602854	60	18	7lbs.	\$38.85
1 1/8" Bore				
602836	40	16	2lbs.	\$18.05
602844	50	16	3lbs.	\$22.40
602855	60	18	7lbs.	\$38.85
1 1/4" Bore				
602845	50	16	3lbs.	\$22.40
602856	60	18	7lbs.	\$38.85
1 1/2" Bore				
602846	50	16	3lbs.	\$22.40
602857	60	18	7lbs.	\$38.85

Item	Pitch	Tooth	Shpg	Price
1 1/16" Bore				
602847	50	16	3lbs.	\$22.40
1 1/2" Bore				
602848	50	16	3lbs.	\$22.40
602858	60	18	7lbs.	\$38.85
1 5/8" Bore				
602859	60	18	7lbs.	\$38.85
1 15/16" Bore				
602860	60	18	7lbs.	\$38.85
2" Bore				
602861	60	18	7lbs.	\$38.85
2 1/8" Bore				
602862	60	18	7lbs.	\$38.85
2 3/8" Bore				
602863	60	18	7lbs.	\$38.85
2 7/16" Bore				
602864	60	18	7lbs.	\$38.85

**Smooth Bore Half**

- Plain bore, no keyway or setscrews.

Machinable Bore Range	50 Pitch 16 Tooth		
	ITEM	Shpg.	Price
5/8" - 1 1/8"	602839	3 lbs.	\$19.45

**Double Roller Chain with Connecting Link**

	40 Pitch 16 Tooth	50 Pitch 16 Tooth	60 Pitch 18 Tooth
ITEM	602837	602850	602865
Shpg.	1/2 lb.	1 1/2 lbs.	3 lbs.
Price	\$5.70	\$10.15	\$18.05

**Coupling Covers**

- Brand new. Shock coupling covers recommended to obtain maximum coupling life. Aluminum covers are made as halves for easy installation.

	40 Pitch 16 Tooth	50 Pitch 16 Tooth	60 Pitch 18 Tooth
ITEM	602838	602851	602866
Shpg.	1 lb.	1 1/2 lbs.	3 lbs.
Price	\$29.60	\$40.10	\$53.10

**Splined PTO
Adapters**

- Brand new, G & G Mfg. Co. Adapts keyed shaft to 1 3/8" 6 tooth spline. **Shpg 4 lbs.**

ITEM	Female Bore	Size	Price
600729	1"	2" dia. x 5 3/4"	\$37.60
600730	1 1/4"	2" dia. x 5 7/8"	\$37.60
601852	1 1/2"	2 1/4" dia. x 5 7/8"	\$42.85

**Tractor PTO
Adapter**

- ITEM 600165 \$53.35**
- New. Use to connect hydraulic or water pumps direct to tractor PTO.

SPECIFICATIONS

- Splined end 1 3/8" 6 tooth spline, 2 1/2" deep
- Keyed end 7/8" dia. x 2 1/2" deep, 3/16" keyway
- Overall size 1 3/4" dia. x 5"
- **Shpg. 3 lbs.**

**Snap Hitch
Pump Adapters**

- Brand new G & G. Snap hitch adapters. Slides onto standard 1 3/8" splined PTO shaft and spring-loaded retention pin holds adapter onto PTO shaft retention groove. Painted steel construction. Size 4 1/8" x 2 1/2" x 2 1/8". **Shpg. 4 lbs.**

ITEM # 6T	ITEM # 21T	Round Bore	Keyway	Price
601433	601440	5/8"	3/16"	\$68.95
601434	601441	3/4"	3/16"	\$59.65
601435	—	7/8"	3/16" & 1/4"	\$68.95
601436	601443	1 5/16"	1/4"	\$68.95
601437	601444	1"	1/4"	\$68.95

U-Joint Assembly

- ITEM 601561 \$4.99**

- New, universal joint assembly originally made for use in automotive steering applications. Ideal for low torque, low speed projects. Gray rubber boot. Rubber boot end accepts a round shaft 0.645" in diameter x 1 5/16" long with two flats, 0.58" across the flats. Other end accepts a 7/8" diameter shaft with two flats (0.667" across). 14" overall length, tip-to-tip. Tube outside diameter 7/8". **Shpg. 3 lb.**

**12 VDC Electric
Clutch/Brake****ITEM 603981****\$78.99**

- New. OGURA model GT1-CH03L(D) 12 volt DC clutch/brake. Ideal replacement for mowers. Triangular back plate. Note: Crankshaft does not extend fully thru clutch.

SPECIFICATIONS

- Voltage 12 DC
- Pulley 5 1/4" dia. 1 groove
- Belt Width 5/8"
- Mount 2 slots
- Back Plate 6" x 6 1/4"
- Hub 25mm bore
- Size 6 1/2" x 3" x 5 3/4"
- **Shpg. 10 lbs.**