

General Purpose Motors

• Brand new WORLDWIDE ELECTRIC general purpose motors. Ideal for use in blowers, pumps, conveyors, and many other diverse applications.

SPECIFICATIONS

- 208-230/460 Volt
- Reversible Rotation

- Enclosure TEFC
- 56 Frame
- 3-Phase
- IP43 Protection

- 5/8" Diameter keyed shaft
- Service Factor 1.15
- Continuous Duty

501513



1 HP 1760 RPM 3PH Motor ITEM 501459 \$499.95

• Brand new, LEESON model# 121179.00 3-Phase general purpose motor. Rolled steel frame.

SPECIFICATIONS

- Power 1 HP
- Voltage 230/460 Volt AC
- Phase 3
- Frequency 60 Hz
- Amperage 3.2/1.6 Amps
- Speed 1760 RPM
- Rotation Reversible
- Service Factor 1.15
- Bearings Ball
- Thermal Overload Protection None
- Enclosure TEFC
- Duty Continuous
- Frame 143TC
- Base Mount Six 0.88" x 0.34" elliptical slots on 5.50" x 3" and 5" centers
- Face Mount Four 3/8"-16 threaded holes in motor face on 5/8" B.C., 4 1/2" pilot
- Shaft 7/8" dia. x 2.13" overall length w/ 3/16" wide x 1 1/8" long keyway
- Size 10.16" x 8.64" x 7.32"
- Shpg. 35 lbs.



Rigid Base					
ITEM	Model	HP	Amps	Shpg	Price
501513	NAT12-18-56	1/2	1.9/0.95	24 lbs.	\$198.00
501520	NAT34-18-56	3/4	2.6/1.3	27 lbs.	\$211.90
501529	NATE1-18-56	1	3.22/1.61	41 lbs.	\$262.50
501524	NATE1.5-18-56	1 1/2	4.52/2.26	48 lbs.	\$309.90
501534	NATE2-18-56	2	5.92/2.96	53 lbs.	\$369.25



501517



501519



501539

C-Face Removable Base 1800 RPM					
ITEM	Model	HP	Amps	Shpg	Price
501517	NAT13-18-56CB	1/3	1.4/0.72	22 lbs.	\$191.55
501514	NAT12-18-56CB	1/2	1.9/0.95	24 lbs.	\$203.40
501521	NAT34-18-56CB	3/4	2.6/1.3	27 lbs.	\$220.60
501530	NATE1-18-56CB	1	3.22/1.61	41 lbs.	\$289.55
501525	NATE1.5-18-56CB	1 1/2	4.52/2.26	48 lbs.	\$367.00
501535	NATE2-18-56CB	2	5.92/2.96	54 lbs.	\$409.05

C-Face Removable Base 3600 RPM					
ITEM	Model	HP	Amps	Shpg.	Price
501519	NAT13-36-56CB	1/3	1.3/0.65	24 lbs.	\$175.95
501516	NAT12-36-56CB	1/2	1.7/0.85	23 lbs.	\$183.65
501523	NAT34-36-56CB	3/4	2.4/1.2	27 lbs.	\$191.25
501532	NATE1-36-56CB	1	3.0/1.5	29 lbs.	\$267.25
501527	NATE1.5-36-56CB	1 1/2	3.96/1.98	36 lbs.	\$302.60
501537	NATE2-36-56CB	2	5.22/2.61	39 lbs.	\$334.40
501539	NATE3-36-56CB	3	7.38/3.69	45 lbs.	\$386.85



501518



501536



501533

C-Face Round Body 1800 RPM					
ITEM	Model	HP	Amps	Shpg	Price
501518	NAT13-18-56CRD	1/3	1.4/0.72	22 lbs.	\$191.55
501515	NAT12-18-56CRD	1/2	1.9/0.95	23 lbs.	\$203.40
501522	NAT34-18-56CRD	3/4	2.6/1.3	26 lbs.	\$220.60
501531	NATE1-18-56CRD	1	3.22/1.61	40 lbs.	\$289.55
501526	NATE1.5-18-56CRD	1 1/2	4.52/2.26	47 lbs.	\$367.00
501536	NATE2-18-56CRD	2	5.92/2.96	52 lbs.	\$409.05

C-Face Round Body 3600 RPM					
ITEM	Model	HP	Amps	Shpg.	Price
501533	NATE1-36-56CRD	1	3.0/1.5	27 lbs.	\$267.25
501528	NATE1.5-36-56CRD	1 1/2	3.96/1.98	33 lbs.	\$302.60
501538	NATE2-36-56CRD	2	5.22/2.61	38 lbs.	\$334.40
501540	NATE3-36-56CRD	3	7.38/3.69	44 lbs.	\$386.85

3 HP 3600 RPM 3PH Motor ITEM 501456 \$179.95

• New, WEG 00336ES3ESA80SL saw arbor motor. Compact motor with cast iron frame that ensures high outputs with smaller frame. It was especially designed for application on circular saws, miter saws, metal cutoff saws, routers, disc sanders, and wood milling machines.

SPECIFICATIONS

- Power 3 HP
- Voltage 208-230/460 VAC
- Phase 3 Ph
- Frequency 60 Hz
- Amperage 9.49-8.58/4.29 Amps
- Speed 3500 RPM
- Rotation CW
- Service Factor 1.00
- Bearings Ball
- Enclosure TEFC
- Thermal Overload Protection None
- Duty S6
- Frame 80S
- Base Mount Four 0.58" holes on 10 1/2" x 7 1/2" centers
- Shaft M30 x 3.5 (left)
- Arbor Dimensions 120mm dia. x 32.5mm
- Size 18 1/2" x 10 1/2" x 6 1/2"
- Shpg. 132 lbs.



3 HP 3490 RPM Motor ITEM 501608 \$249.95

• New, WEG capacitor-start, capacitor-run motor. Stainless steel shaft. Thermal overload protection.

SPECIFICATIONS

- Brand WEG
- Model Number 24366-SHU
- Power 3 HP
- Voltage 208-230 Volt AC
- Phase 1
- Frequency 60 Hz
- Amperage 14.00-12.70
- Speed 3490 RPM
- Rotation CCW
- Service Factor 1.15
- Bearings Ball
- Thermal Overload Protection Automatic
- Enclosure TEFC
- Duty Continuous
- Frame 56HJ
- Base Mount Six 1 1/8" x 5/16" elliptical slots on 4 7/8" x 2" x 5" centers
- Face Mount Four 3/8"-16 threaded holes in motor face on 5/8" B.C., 4 1/2" pilot
- Shaft 5/8" dia. x 2 1/2" overall length w/ 7/16"-20 x 5/8" threaded end
- Size 16" x 10 1/4" x 8 1/4"
- Shpg. 51 lbs.

