

1/0.33 HP 1450 RPM Motor ITEM 500320 \$149.95



Old unused inventory, General Electric 5KC184AL929 base mount motor.

SPECIFICATIONS

- Power 1 & 1/2 HP
- Voltage 230 AC
- Phase 1
- Frequency 50 Hz
- Amperage 7/4.5 Amps
- Speed 1450/970 RPM
- Rotation Reversible
- Service Factor 1
- Bearings Ball

- Enclosure TEFC
- Duty Continuous
- Frame 184TY
- Base Mount Six 0.39" dia. x 1 1/4" slotted holes on 1", 5 1/2" x 7 1/2" centers
- Shaft 1-1/8" dia. x 2 1/2" overall length w/ 1/4" x 2" long keyway
- Size 16 1/2" x 12" x 9 1/2"
- Shpg. 84 lbs.

1/2 HP 1725 RPM Motor ITEM 501607 \$119.95



New, Century carbonator pump motor. Automatic overload protection.

SPECIFICATIONS

- Model Number S48A64C28
- Power 1/2 HP
- Voltage 115/230 Volt AC
- Phase 1
- Frequency 60/50 Hz
- Amperage 6.8/3.4 Amps
- Speed 1725/1425 RPM
- Rotation Reversible
- Service Factor 1.0
- Bearings Ball

- Thermal Overload Protection Automatic
- Enclosure ODP
- Duty Continuous
- Frame 48
- Base Mount Four 1" x 5/16" elliptical slots on 4 1/4" x 2 3/4" centers
- Shaft 0.197" wide Tang drive
- Size 9" x 5 1/2" x 6"
- Shpg. 20 lbs.

1/2 HP 3450 RPM Motor ITEM 501379 \$79.95



• New, pool pump motor. Ideal replacement motor for pool pumps. Square flange 4 bolt pump mount on 7 1/8" bolt circle. Stainless steel shaft 5/8" diameter with 1/2"-20 UNF-2A RH threaded end. Thermally protected.

SPECIFICATIONS

- Power 1/2 HP
- Voltage 208-230/460 AC
- Amps 3/1.5
- RPM 3450
- Rotation CCW
- Phase 3
- Service Factor 1.9

- Enclosure TEFC
- Duty continuous
- Frame 56Z
- Shaft 5/8" diameter with 1/2"-20 UNF-2A threaded end
- Size 10 1/2" x 6 1/2" x 8 1/2"
- Shpg 18 lbs.

3/4 HP 3450 RPM Motor ITEM 501285 \$59.95



• New, BLUFFTON MOTOR WORKS model B1244 pool pump motor. Smooth portion of shaft measures 1 1/16" from the bearing overall length 2 1/16". Automatic thermal overload protection.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 AC
- Amperage 12.8/6.4 Amps
- Speed 3450 RPM
- Rotation CCW
- Phase 1
- Service Factor 1.27
- Bearings Ball

- Enclosure ODP
- Duty Continuous
- Frame 56Y
- Mount Square flange 4 bolt on 7 1/8" dia. B.C.
- Shaft 5/8" dia. x 2 1/16" w/ 1/2"-20 RH threaded end
- Size 10 1/2" x 6 5/8" x 6 5/8"
- Shpg. 24 lbs.

3/4 HP 3480 RPM Motor ITEM 501606 \$149.95



New, WEG model# 1409-SHU general purpose electric motor. Capacitor start. Steel housing. Automatic overload protection.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/208-230 Volt AC
- Phase 1
- Frequency 60 Hz
- Amperage 10.8/5.40-4.90 Amps
- Speed 3480 RPM
- Rotation CCW
- Service Factor 1.15
- Bearings Ball
- Thermal Overload Protection Automatic

- Enclosure TEFC
- Duty Continuous
- Frame E56J
- Base Mount Four 1 1/4" x 5/16" elliptical slots on 4 7/8" x 3" centers
- Face Mount Four 3/8"-16 threaded holes in motor face on 5 7/8" B.C., 4 1/2" pilot
- Shaft 5/8" dia. x 1 7/8" overall length w/ 7/16"-20 x 5/8" threaded end
- Size 12 1/2" x 9 1/2" x 8 1/4"
- Shpg. 31 lbs.

3/4 HP 3600 RPM Motor ITEM 501329 \$39.95



• New, AO Smith model# J218-1006.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 VAC
- Phase 1
- Frequency 60 Hz
- Amperage 12.5/3 Amps
- Speed 3600 RPM
- Rotation CCW
- Bearings Ball
- Enclosure ODP

- Thermal Overload Protection Automatic
- Duty Continuous
- Face Mount Four 3/8" threaded holes in motor face on 7 1/8" B.C.
- Shaft 12mm dia. tapered x 3/4" long with M10-1.0 threaded end
- Size 12" x 8" x 8"
- Shpg. 23 lbs.

3/4 HP 3600 RPM Motor ITEM 501331 \$49.99



• New, AO SMITH model# J218-590B.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 VAC
- Phase 1
- Frequency 60 Hz
- Amperage 11.5/5.75 Amps
- Speed 3600 RPM
- Rotation CCW
- Service Factor 1.25
- Bearings Ball

- Thermal Overload Protection Automatic
- Enclosure ODP
- Duty Continuous
- Face Mount Four 3/8" threaded holes in motor face on 7 1/8" B.C.
- Shaft 5/8" dia. x 1 1/2" long with 1/2"-20 threaded end
- Size 10 1/2" x 6 1/2" x 6 1/2"
- Shpg. 22 lbs.

3/4 HP 1725 RPM Motor ITEM 501498 \$139.95



• New, CENTURY electric motor. Manual thermal overload protection

SPECIFICATIONS

- Model 7-196325-21
- Power 3/4 HP
- Voltage 115/208-230 AC
- Phase 1
- Frequency 60/50 Hz
- Amperage 10.6/5.2-5.3 Amps
- Speed 1725/1425 RPM
- Rotation Reversible
- Service Factor 1.25
- Bearings Ball
- Enclosure ODP

- Thermal Overload Protection Manual
- Duty Continuous
- Frame K56C
- Base Mount Four slots on 4" to 5 3/4" x 3" centers
- Face Mount Four 3/8"-16 threaded holes on 5 7/8" B.C. w/ 4 1/2" pilot
- Shaft 5/8" dia. x 1 7/8" overall length w/ 3/16" wide x 1 1/2" long keyway
- Size 11 1/2" x 6 1/2" x 9"
- Shpg. 31 lbs.

3/4 HP 1725 RPM Motor ITEM 501575 \$69.95



New, Century motor. Thermal overload protection with manual reset.

SPECIFICATIONS

- Model Number S56AA23C8
- Power 3/4 HP
- Voltage 115/230 AC
- Phase 1
- Frequency 60 Hz
- Amperage 10.4/5.2 Amps
- Speed 1725/1425 RPM
- Rotation Reversible
- Service Factor 1.00
- Bearings Ball
- Enclosure ODP

- Thermal Overload Protection Manual
- Duty Continuous
- Frame 56
- Base Mount Eight 1 1/4" x 5/16" elliptical slots on 1 7/8", 3", 4 7/8" x 5" centers
- Face Mount Four 3/8"-16 threaded holes in motor face on 5 7/8" B.C., 4 1/2" pilot
- Shaft 5/8" dia. x 2 3/8" overall length w/ flat
- Size 12 1/8" x 6 1/2" x 6 3/4"
- Shpg. 30 lbs.

1 HP 1725 RPM Motor ITEM 501499 \$149.95



• New, CENTURY capacitor-start motor. Thermal overload protection with manual reset. Rigid Base and C-face mount.

SPECIFICATIONS

- Model C56AA79C28-03
- Power 1.0 HP
- Voltage 208-230/115 AC
- Phase 1
- Frequency 60/50 Hz
- Amperage 6.5-6.3/12.6 Amps
- Speed 1725/1425 RPM
- Rotation Reversible

- Service Factor 1.25
- Thermal Overload Protection Manual
- Enclosure ODP
- Duty Continuous
- Frame L56C
- Shaft 5/8" dia. x 2 3/4" w/ flat
- Size 10 1/4" x 7 1/2" x 8 3/4"
- Shpg. 37 lbs.

1 HP 1800 RPM Motor ITEM 501472 \$159.95



• New, CENTURY model #C530 electric motor. Rigid base mount. 5/8" dia. shaft.

SPECIFICATIONS

- Power 1 HP
- Voltage 208-230/115 AC
- Phase 1
- Frequency 60 Hz
- Amperage 7.2-6.5/13.6 Amps
- Speed 1725 RPM
- Rotation Reversible

- Service Factor 1.25
- Bearings Ball
- Thermal Overload None
- Enclosure ODP
- Duty Continuous
- Frame L56C
- Size 10 1/4" x 6 1/2" x 8 5/8"
- Shpg. 35 lbs.

2 HP 1725 RPM Motor ITEM 501581 \$249.95



• New, BALDOR RELIANCE model# 36F283-379 capacitor-start, capacitor-run motor. Thermal overload protection with manual reset. ON/OFF switch mounted on the electrical box.

SPECIFICATIONS

- Power 2 HP
- Voltage 115/230 Volts AC
- Phase 1
- Frequency 60 Hz
- Amperage 24/12 Amps
- Speed 1725 RPM
- Rotation CW
- Service Factor 1.15
- Bearings Ball

- Thermal Overload Protection Manual
- Enclosure Open
- Duty Continuous
- Frame 184
- Base Mount:
- Shaft 7/8" dia. x 2 1/4" w/ 3/16" keyway
- Size 14" x 10 1/2" x 11"
- Shpg. 72 lbs.