


1.8 RPM 115 VAC Inline Gearmotor**ITEM 500719****\$18.95**

• New, inline gearmotors. Ideal replacement corn pellet stove, auger motor. Originally built for Bixby stoves. Aluminum gear housing. Four 8-32 UNC tapped bolt hole face mount on 2 3/8" x 2 3/8" centers.

SPECIFICATIONS

- SPG Co. Model ISG-3220BXA(P/N 2051788)
- Speed 1.8 RPM
- Voltage 115 AC
- Torque 110 in - lbs.
- Rotation CW
- Duty intermittent (5 min)
- Enclosure open
- Mount face
- Shaft 1/2" dia. x 1 3/4"
- 1/2-13 UNC RH threaded
- Size 3 3/8" x 2 3/4" x 4 3/4"
- Shpg. 5 lbs.

**115 VAC Inline Gearmotors****\$748.95 each**

• Brand new LEESON inline split capacitor gearmotors. Features steel gears and needle bearing supported output shaft. No thermal overload. Capacitor furnished.

SPECIFICATIONS

- Voltage 115 AC
- Torque 100 in - lbs.
- Rotation reversible
- Duty continuous



500825

500826
500827

- Enclosure TENV
- Mount four 10-32 holes on face, 2.645" x 2.645"
- Shaft 1/2" dia. x 1" w/1/8" keyway

ITEM	Model	RPM	Amps	HP	Gear Ratio	Size	Shpg.
500825	M1125050	1.9	0.4	1/50	900:1	7.25" x 3.63" x 3.63"	9 lbs.
500826	M1125127	9	0.9	1/15	180:1	8.86" x 3.75" x 3.97"	11 lbs.
500827	M1125128	19	0.9	1/15	180:1	8.86" x 3.75" x 3.97"	12 lbs.

18 RPM, 115 VAC Shaded Pole Gearmotor**ITEM 501416****\$9.95**

• New, OH SUNG model ORG-4003Y1-2 compact shaded pole gearmotor. Thermally protected, originally built for refrigerator ice maker.

SPECIFICATIONS FOR BOTH

- Speed 18 RPM
- Voltage 115 AC
- Amperage 2.5 Amps
- Power 97 Watts @ idle
- Rotation CW
- Size 2 7/8" x 3 1/2" x 4"
- Duty Intermittent (1 minute max on time)
- Face Mount 3 tapped bosses
- Shaft: 3/8" dia. x 2 1/8" long, threaded end 5/16"-18 LH
- Overall length 2 5/8"
- Shpg. 4 lbs.

**ITEM 501418****\$9.95**

• New, SPG model ISF-3240SSJ. Amperage 2.8 Amps

310 RPM 220 VAC Gearmotor**ITEM 500573****\$199.95**

• New, BISON, model 015-790-0011. In-line permanent magnet gearmotor. Requires 270-324 MFD start capacitor and 189605-13 solid state switch not included.

SPECIFICATIONS


- Brand Bison
- Speed 131 RPM
- Voltage 208-230 AC
- Amperage 5
- Power 5 1/2 HP
- Torque 280 in.lbs.
- Gear Ratio 10.8:1
- Rotation Reversible
- Duty Continuous
- Enclosure TE
- Size 12 1/2" x 6 1/4" x 7 1/4"
- Gearbox Face Mount 4 holes 0.410" x 0.375" depth 2 3/4" x 4 3/4" centers
- Motor Mount 4 tapped holes 1/4"-20 TPI, two on each side of motor on 4" centers
- Shaft 1" dia. x 3 1/16" w/ tang 0.887" x 0.371" x 0.493" on end of shaft and 0.108" wide groove 2.443" from end of shaft to center of groove
- Shpg. 40 lbs.

**3.5 RPM 115 VAC Inline Gearmotor****ITEM 500999****\$11.95**

• New, SPG Co. model ISG-31315FKA (P/N 40384rG). Inline gearmotor. Originally built for timer controls on water softeners. Aluminum gear housing. Four 10-32 UNF tapped bolt hole face mount on 1 1/2" x 1 1/2" centers.

SPECIFICATIONS


- Speed 3.5 RPM
- Voltage 115 AC
- Amperage 1/2 Amp
- Rotation CW
- Duty Intermittent (30 seconds on/30 seconds off)
- Enclosure Open
- Mount Face
- Shafts Front-5/16" dia. x 0.7", Rear-1/4" dia. x 3/4" both have cross holes
- Size 2 1/4" x 3" x 5"
- Shpg. 3 lbs.

**15 RPM, 115 VAC Shaded Pole Gearmotor****ITEM 500600****\$9.95**

• New, MERKLE-KORFF Model 3715UP-250. Thermally protected, shaded pole motor. Metal gear housing.

SPECIFICATIONS

- Speed 15 RPM
- Voltage 115 AC
- Amperage 2.7 Amps
- Power 97 Watts at idle
- Rotation CW
- Duty intermittent
- Face mt 3 untapped bosses
- Shaft: Threaded end 5/16"-18 LH
- Base end 3/8" dia. x 3/8" long
- Overall lgth. 1 5/16"
- Size 3 3/8" x 2 1/2" x 4"
- Shpg. 3 lbs.

**20 RPM 115 Vac Gearmotor****ITEM 500548****\$8.95**

• Unused old inventory. BRISTOL MOTOR COMPANY model# 425 2B, 115 Volt AC gearmotor with two animation arms that have some superficial rust.

SPECIFICATIONS

- Speed 20 RPM
- Voltage 115 AC
- Cycle 60
- Watt. 4
- Mounting Tabs 2 tabs 0.495" x 0.421" x 0.121"
- Arm length 1.47"
- Arm diameter 0.092"
- Shpg. 0.7 lb.

**62 RPM 115 VAC Inline Gearmotor****ITEM 500717****\$8.99**

• New, BREVEL 782 inline gearmotor. T.P.I. Model 8T-115-7AM209A10. Aluminum gear housing. Shaded pole motor. Mounting holes tapped 8-32.

SPECIFICATIONS


- Speed 62 RPM
- Voltage 115 AC
- Amperage 4 Amps
- Rotation CW
- Duty Intermittent
- Enclosure Open
- Mnt. 4 holes on back face
- Shaft 1/2" dia. x 1 1/2" hollow threaded 7/16"-20 LH
- Size 2 1/2" x 2" x 5 3/4"
- Shpg. 3 lbs.

**65 RPM 120 VAC****ITEM 501338****\$8.95**

• New, MOLON inline shaded pole gearmotor. Diecast gear housing. Four thru hole face mount on 2 3/8" x 2 3/8" centers.

SPECIFICATIONS

- Speed 65 RPM
- Voltage 115 AC
- Amperage 2 Amps
- Rotation CW
- Duty Intermittent(1 min)
- Enclosure Open
- Mount Face
- Shaft 3/8" diam. x 1" w/flat
- Size 5" x 2 3/4" x 4 3/4"
- Shpg. 5 lbs.

**75 RPM 115 Volt AC Gearmotor****ITEM 500631****\$6.99**

• New, ECM model 34 3406 000 shaded pole gearmotor. Tapped mounting holes #8-32. Shaft extends from opposite side of mounting holes.

SPECIFICATIONS


- Speed 75 RPM
- Voltage 115 AC
- Amperage 1.8 Amps
- Rotation CW
- Duty Intermittent
- Enclosure Open
- Mount Four bolt on 1 5/8" x 1 1/8"
- Shaft 1/4" diam. x 1 7/32" w/ 3/32" diam. pin hole
- Size 2 3/4" x 2 3/4" x 5 1/2"
- Shpg. 4 lbs.

**100 RPM 115 AC****ITEM 500171****\$4.95**

• New MERKLE-KORFF.

SPECIFICATIONS

- RPM 100
- Voltage 115
- Amps 1.25
- Torque 4 in. lbs.
- Rotation CCW
- Duty Intermittent
- Shaft 5/16" diam. x 1/2" w/crosshole
- Mount front
- Size 2 3/4" x 2 1/2" x 5 1/4"
- Shpg. 3 lbs.

**743 RPM 115 VAC Inline Gearmotor****ITEM 501479****\$29.99**

• Used, BODINE ELECTRIC 48C8B-VDDY2, inline gearmotor. Requires run and start capacitors (not included). Requires relay (not included) for start capacitor.

SPECIFICATIONS

- Speed 743 RPM
- Voltage 115 AC
- Amperage 9.9 Amps
- Power 440 watts
- Torque 44 in - lbs.
- Gear ratio 2.42:1
- Rotation CW
- Duty continuous
- Enclosure open
- Mount face 3 5/8" x 3 5/8"
- Shaft 16mm x 3 1/2" w/keyway
- Size 5 1/2" x 10 1/2" x 5 1/2"
- Shpg. 36 lbs.

