



120 RPM 22 Volt DC Inline Gearmotor



ITEM 500808

\$9.99

• New, IGARASHI permanent magnet inline gearmotor. Spur geartrain.

SPECIFICATIONS

- Speed 120 RPM-no load
- Voltage 22 DC
- Amperage 90 mA no-load
- Performance 70 RPM w/50 oz.in. torque, 500 mA
- Gear Ratio 50
- Rotation Reversible
- Duty Continuous
- Mount 3 holes on face, M3 thread.
- Shaft 5mm dia. x 7mm w/flat
- Size 1.3" dia. x 2.5"
- Shpg. 1 lb.

175 RPM 12 Volt DC Gearmotor



ITEM 501413

\$8.95

• New, right angle drive gearmotor originally made for use in electric automotive seats. No clutch or limit switches. Permanent magnet type motor. Output to right when viewed from motor end with output shaft above motor centerline.

SPECIFICATIONS

- Voltage 12 VDC
- Amps 1.5 no load
- RPM 175
- Output Orientation RH
- Rotation reversible
- Enclosure Fully enclosed
- Duty Intermittent
- Mount 1/4" clevis, 3/8" between ears
- Shaft Thread 7/16"-8 ACME thread w/M6x1 LH at end
- Shaft Length 3 1/2"
- Overall size 6" x 2 1/2" x 5 1/2"
- Shpg. 3 lbs.

13 RPM 24 VDC Right Angle Gearmotor



ITEM 501114

\$12.99

• New, right angle permanent magnet gearmotor. High torque in a compact size for many applications.

SPECIFICATIONS

- Speed 13 RPM no load
- Voltage 24 DC
- Amperage 40 mA no load
- Torque 4 in.-lbs.
- Rotation Reversible
- Duty Continuous
- Mount M3 tapped 4 bolt on 18mm x 33mm centers
- Shaft 6mm dia. x 9/16" long w/flat tapped M3
- Size 3 1/8" x 1 1/4" x 1 1/8"
- Shpg. 1/2 lb.

188 RPM 24 VDC Gearmotor



ITEM 501060

\$19.95

• New, AMETEK PITTMAN model# GM9234E992-R1 parallel-shaft gear motor. Intended for use with nylon travelling nut to move along shaft. No limit switches. (Nylon travelling nut not included.)

SPECIFICATIONS

- Travel 7"
- Full Stroke Time 4 seconds
- Shaft Speed 188 RPM
- Voltage 24 VDC
- Amperage 0.15 Amps @ No Load
- Gear Ration 5.9:1
- Rotation Reversible
- Duty Intermittent
- Enclosure TENV
- Face Mount Two 10-32 tapped holes on 1 1/2" centers
- Rear Mount Four 6-32 tapped holes on 1 1/16" square centers
- Shaft 3/8"-8 round thread lead screw
- Size 3 1/16" x 2" dia.
- Shpg. 3 lbs.

142 RPM 24 Volt DC Inline Gearmotor



ITEM 501356

\$8.95

• New, HENKWEILL, very compact permanent magnet precision inline gearmotor. Will operate on 6-24 VDC. Planetary gear reduction, dual ball bearings.

SPECIFICATIONS

- Speed 142 RPM no load, 113 RPM rated load
- Voltage 24 DC rated
- Gear Ratio 84:1
- Torque 1.3 in.lb. rated, 4.9 in.lb. stall
- Amps 0.1 no load, 0.2 rated load
- Rotation Reversible
- Duty Continuous
- Mount 4 M2 tapped holes, 18mm B.C.
- Shaft 6mm dia. x 14mm w/crosshole
- Size 11mm dia. x 50mm
- Shpg. 1/2 lb.

90 RPM 12 Volt DC Inline Gearmotor



ITEM 501357

\$8.95

• New, KINDLY MOTOR model KC55-37G50-3162 compact permanent magnet inline gearmotor. Operates on 12-24 VDC.

SPECIFICATIONS

- Speed 90 RPM (no load)
- Voltage 12 DC
- Amps 160 mA (no load)
- Torque 8 in.-lbs.
- Gear Ratio 50:1
- Rotation Reversible
- Duty Continuous
- Mount 6 holes on face tapped M3
- Shaft 5.5mm x 15" w/flat
- Size 35mm dia. x 83mm
- Shpg. 1 lb.

30 RPM, 24 VDC Gearmotor

ITEM 500220

\$24.95

• New MULTI-PRODUCTS CO. INC. #2738. Offset gearbox.

SPECIFICATIONS

- RPM 30
- Duty continuous
- Voltage 24 DC
- Shaft 11 mm dia. x 12 mm w/dual flats
- Amps 0.68 no load
- HP 1/4s
- Mnt. 4 bolt 2 1/2" x 2" pattern
- Torque 47 in. lbs.
- Size 4 1/2" x 3" x 4 3/4"
- Rotation reversible
- Shpg. 5 lbs.

45 RPM, 24 VDC Inline Gearmotor



ITEM 500568

\$9.95

• New, MOLON Model CHM-2435-1. High torque output. 4 7/8" wheel with o-ring on edge to friction drive equipment. Use for drive wheel on robots. Operates at 1/2 speed on 12 VDC. Permanent magnet motor.

SPECIFICATIONS

- Speed 45 RPM
- Voltage 24 DC
- Amperage 0.28
- Torque 7.5 in.-lbs.
- Rotation Reversible
- Duty Continuous
- Mount 4 tapped holes 2 3/8" x 2 1/2"
- Shaft 5/16" dia.
- Size 2 3/4" x 2 1/4" x 3"
- Shpg. 1 1/2 lbs.

180 RPM, 24 VDC

ITEM 500809

\$8.95

• New, inline gearmotor. Die cast zinc gear housing. Will operate on 12 volts at reduced output speed.

SPECIFICATIONS

- Speed 180 RPM
- Voltage 24 DC
- Amperage 0.6 Amps
- Torque 2.5 in.-lbs.
- Rotation Reversible
- Duty Continuous
- Shaft 1/4" dia. x 5/8" w/dual flats and crosshole
- Shaft crosshole 1/8"
- Mount 4 bolt 1.25" x 1.56" centers
- Size 2 3/4" x 2 1/2" x 2 3/4"
- Shpg. 1 lb.

12 VDC, 5.9" Stroke Linear Actuator



ITEM 500184

\$9.95

• New MOLON take-offs. Inline parallel shaft gear motor. Rated 24 volt DC, will run on 12 volt DC at lower speed and torque

SPECIFICATIONS

- RPM 45
- Voltage 24 DC
- Draws 175 mA @ no load
- Torque 38 in. lbs. full load
- 7.5 in. lbs. cont.
- Rotation reversible
- Duty continuous
- Shaft 5/16" x 3/4" long w/flat
- Mount face 2 3/8" x 2 1/2" drilled/tapped
- Size 2 3/4" x 3" x 2 3/16"
- Shpg. 2 lbs.

120 RPM, 22 VDC Inline Gearmotor



ITEM 500807

\$9.99

• New, IGARASHI permanent magnet inline gearmotor. Spur geartrain. Includes rubber boot over brushholders.

SPECIFICATIONS

- Speed 120 RPM-no load
- Voltage 22 DC
- Amperage 90 mA no-load
- Performance 70 RPM w/50 oz.in. torque, 500 mA
- Gear ratio 50
- Rotation reversible
- Duty continuous
- Mount 3 holes on face, M3 thread
- Shaft 5mm dia. x 7mm w/flat
- Size 1.3" dia. x 2.5"
- Shpg. 1 lb.

15 RPM, 24 VDC

ITEM 500235

\$4.95

• New CKD Model J209-056. DC synchronous motor attached to removable mtg. bracket.

SPECIFICATIONS

- RPM 15
- Voltage 24 DC
- Amps 0.2 no load
- Rotation CW
- Duty intermittent
- Shaft 3/16" diam. x 1 1/2" long w/flat
- Mount 2 bolt on 3 13/32" BC
- Size 4" x 1 1/4" x 2"
- Shpg. 1 lb.

152 RPM, 36 VDC Gearmotor



ITEM 500780

\$7.99

• New, MAXON A-max, very compact permanent magnet precision gearmotor. Will operate on 12-36 VDC.

SPECIFICATIONS

- Speed 152 RPM
- Voltage 36 DC
- Gear ratio 64.4:1
- Power consumption 5 watts
- Rotation reversible
- Duty continuous
- Mount three M2x1.5 holes, 17mm B.C.
- Shaft 2.7mm dia. x 4mm w/flat
- Size 1 5/16" dia. x 2"
- Shpg. 1/2 lb.

30 RPM, 50 VDC Gearmotor



ITEM 500605

\$89.95

• Used PARVALUX permanent magnet right angle gearmotor. Heavy duty construction.

SPECIFICATIONS

- Speed 30 RPM
- Voltage 50 DC
- Amperage 1.3 Amps
- Torque 62 in. - lbs.
- Gear ratio 96:1
- Rotation reversible
- Duty continuous
- Mount base
- Shaft 15 mm x 2" w/keyway
- Size 9" x 5" x 5 1/2"
- Shpg. 16 lbs.