

Rol-Air Two Stage Air Compressors


• Brand new ROL-AIR. Two-stage compressors with aluminum crankcase for light weight and good heat dissipation. Cast iron cylinders for long life and greater wear resistance. Crankshaft supported on roller bearings with replaceable bearings for connecting rods. Reed valves. Deep fins for cooling on output lines and intercooler. Includes oil sight gauge and automotive style air filter.

SPECIFICATIONS FOR ALL TWO STAGE

- 175 PSI Max.
- CCW Rotation



400136



400127



400239

ITEM	Model	Cylinders	HP	RPM	CFM Open	CFM at 175 PSI	Port NPT	Pulley	Mount	Size	Shpg.	Price
400127	K24	Two	3	1000	14.58	10.37	1/2"	15.16" dia.	6.41" x 8.09"	15.18" x 12.25" x 16.37"	64 lbs.	\$654.00
			5	1250 *	18.25	13.14	Two A belts					
400239	K28	Two	3	800	16.66	13.02	3/4"	15.16" dia.	6.41" x 8.09"	16.37" x 12.25" x 16.62"	75 lbs.	\$676.50
			5	1250 *	20.35	15.87	Two A belts					
400128	K30	Two	5	800	20.52	16.01	3/4"	15.16" dia.	7.48" x 8.97"	16.37" x 14.18" x 22.25"	95 lbs.	\$894.00
			7.5	1200 *	30.78	23.63	Two A belts					
400136	K60	Four	10	800	41.04	33.65	1"	21.65" dia.	9.6" x 11.73"	28.94" x 17.5" x 23.62"	255 lbs.	\$2181.00
			15	1100 *	54.58	44.75	Two B belts					

* Maximum

Rol-Air Single Stage Air Compressors

• Brand new ROL-AIR. Single stage compressors, ideal replacement on portable compressors. Aluminum head and crankcase give good heat dissipation while cast iron cylinder sleeves provide long life.

SPECIFICATIONS FOR ALL SINGLE STAGE

- 150 PSI Max. (140 PSI on ITEM 400145)
- CCW Rotation



400145



400135



400146


ITEM	Model	Cylinders	HP	RPM	CFM Open	CFM at 150 PSI	Port NPT	Pulley	Mount	Size	Shpg.	Price
400145	K3	One	0.5	700	2.16	1.3	1/2"	10.24" dia.	3.74" x 4.53"	10.25" x 9.87" x 12.5"	17 lbs.	\$285.00
			0.75	1000 *	3.09	1.85	One A belt					
400135	K17	Two	1	600	7.32	4.98	1/2"	11.5" dia.	5.19" x 7.08"	11.5" x 10.25" x 13.75"	40 lbs.	\$454.50
			1.5	800	9.07	6.16	One A belt					
			2	1000	11.33	7.7						
400146	K35	Two	5	800 *	30.16	22.62	3/4"	15.16" dia.	7.48" x 8.97"	15.18" x 14.18" x 18.5"	86 lbs.	\$870.00
			Two A belts									

* Maximum

Heavy Duty Two Stage Air Compressors

• Brand new. Heavy duty two stage, cast iron compressors designed for heavy duty applications where high air volume and pressure are required along with extra long life. All cast iron including inner and after coolers to reduce air temperature. Low speed gives quieter operation, less vibration. Complete with oil sight glass, unloader valve and safety pop off valve.

23 CFM,
Two Cylinder



ITEM 400100
\$958.25

SPECIFICATIONS

- Displ. 23 CFM
- 175 PSI max.
- 17 CFM at 175 PSI
- 805 RPM max.
- Bore/stroke 4 1/8" x 3 1/2" 1st stage 2 1/8" x 3 1/2" 2nd stage

- Mtg. pattern 8" x 9"
- Two cylinder
- 5 HP
- 17" pulley 2 groove B belt
- Cooling fan/pulley
- Size 17" x 19" x 21"
- Shpg. 250 lbs.

Truck freight only.

46 CFM,
Four Cylinder



ITEM 400101
\$1336.45

SPECIFICATIONS

- Displ. 46 CFM
- 175 PSI max.
- 35 CFM at 175 PSI
- 805 RPM max.
- Bore/stroke 4 1/8" x 3 1/2" 1st stage 2 1/8" x 3 1/2" 2nd stage

- Mtg. pattern 9 1/4" x 9 1/2"
- Four cylinder
- 10 HP
- 19" pulley 2 groove B belt
- Cooling fan/pulley
- Size 20" x 29" x 28"
- Shpg. 250 lbs.

Truck freight only.

12.9 CFM, Single Stage Compressor



ITEM 400276
\$262.50

• Brand new, FINI Model MK103. Single cylinder, single stage belt drive compressor. Aluminum head and crankcase. Integral cold start valve allows no load starting. Oil sight gauge.

SPECIFICATIONS

- One stage, one cylinder
- Pressure 145 PSI max.
- Flow at 1370 RPM (3 HP) 12.9 CFM open flow 8 CFM at 145 PSI 9.9 CFM open flow 7.2 CFM at 145 PSI



- Rotation CCW
- Flywheel 10" dia. single 1/2" groove
- Port 1/2" NPT
- Oil capacity 1/2 qt.
- Mount 6 1/4" x 4 3/4"
- Size 10" x 10" x 11"
- Shpg. 27 lbs.