

2.50-4 Wheel Assembly**ITEM 700654****\$5.95**

- New, rubber tire with tube on steel wheel. Offset hub.

**SPECIFICATIONS**

- Size 2.50-4
- O.D. 8 1/2"
- Bore 5/8" dia.
- Thru Bore Length 1 7/16"
- Tread Width 2 3/16"
- Tube Type
- Load Range 297 lbs. Pressure 30 PSI max.
- Ply Rating 2
- Shpg. 4 lbs.

**4.10/3.50x4
2 Ply Tire****ITEM 700449****\$1.99**

- New, DICO pneumatic tire.

SPECIFICATIONS

- Size 4.00/3.50-4
- Outside Diameter 10"
- Tread Width 2 1/2"
- Tread Sawtooth
- Load Rating 250 lbs.
- Pressure 30 PSI max.
- Ply Rating 2
- Shpg. 2 1/2 lbs.

**13 x 5.00-6
Turf Tire****ITEM 700450****\$4.95**

- NEW, DURO Turf tire. Tires are shipped flat and may require extra effort to mount on a rim.

SPECIFICATIONS

- Size 13x5.0-6
- Tire Tubeless
- Outside Diameter 13" dia.
- Cross Section 5" Wide
- Ply Rating 2
- Tread Knobby
- Tread Width 4"
- Pressure 20 PSI max.
- Shpg. 5 lbs.

1/2"-20 Cone Wheel Lug Nut**ITEM 700602****.95¢**

- Brand new. 1/2"-20 NF cone lug nut. Replacement lug nut to fit popular trailer hub studs.

SPECIFICATIONS

- Thread 1/2"-20 NF
- Length 0.585"
- Hex Size 0.805" (measured across flats)
- Shpg. 0.05 lb.

Trailer Bearing Kits

- Brand new, DURA-ROLL replacement trailer bearing kit. Use with boat, camping, utility and snowmobile trailers. 1 kit per wheel required. Bearings must be packed with grease before installation. Kit contents available at www.surpluscenter.com. Fully tested and exceeds VESC regulations. Installation instructions included.

ITEM	Typical Axle		Rating (lbs.)	Shpg.	Price
	Inner	Outer			
700167	1"	1"	2000	1 lb.	\$14.85
700168	3/4"	3/4"	2000	1 lb.	\$11.90
700169	1 1/4"	1 1/4"	2000	1 1/2 lbs.	\$14.35
700170	1 3/8"	1 1/16"	3500	1 lb.	\$15.00
700171	1 1/16"	1 1/16"	2000	1 lb.	\$14.50

Press In Bearings & Bushings

- Brand new, bearings and bushings for low speed wheels. Available in Oilite bushings, standard ball bearings and precision sealed ball bearings. All are designed to fit into common 1 3/8" ID wheel hubs. Shpg 1/4 lb.

ITEM	Style	Axle Bore	Price
700536	Oilite Bushing	1"	\$1.00
700537	Oilite Bushing	3/4"	\$1.50
700538	Oilite Bushing	5/8"	\$2.25
700539	Ball Bearing	1/2"	\$2.25
700540	Ball Bearing	3/4"	\$2.25
700541	Ball Bearing	5/8"	\$1.95
700542*	Precision BB	3/4"	\$5.75
700543	Precision BB	5/8"	\$4.95
700544	Precision BB	5/8"	\$3.25

* with flange

**18 x 6.50-8
Wheel Assembly****ITEM 700560****\$32.99**

- New, WANDA pneumatic tire mounted on steel rim. NOT for Highway Service.

SPECIFICATIONS

- Size 18 x 6.50-8
- Outside Diameter 18"
- Cross Section 6 1/2" Wide
- Tread Knobby
- Tread Width 5 1/2"
- Bore 1"
- Bore Thru-Length 3"
- Hub Type Centered
- Tire Tubeless
- Load Rating 330 lbs. @ 10 PSI
- Ply Rating 2
- Shpg. 16 lbs.

Hi-Speed Wheel Hubs

- Brand new. Use with a 1" diameter spindle to mount high speed wheels on small trailers. Includes grease cap, tapered roller bearings and seal. Shpg. 7 lbs.

ITEM	Bolts	Bolt Circle	Type	Price
700101	4	4"	Lug Bolt	\$43.95
700102	5	4 1/2"	Lug Bolt	\$46.70
700413	4	4"	Stud	\$45.05
700414	5	4 1/2"	Stud	\$48.00

1" Trailer Spindle

- Brand new steel trailer spindle with castle nut. 1" diam. x 8 1/2" long. Shpg. 4 lbs.

Grease Cap**ITEM 700662****\$1.59**

- New. Steel grease cap.

SPECIFICATIONS

- Height 1.165"
- Inside Diameter 1.895"
- Outside Diameter 1.987"
- Shpg 0.15 lb.

24 x 12.00-12 Directional**Lug Tread****OTR Tire****and Steel****Wheel Assembly****\$119.95 ea.**

- New, OTR directional lug tread tire mounted on steel rim.

(Not For Highway Use).

ITEM 700599

Right Hand

ITEM 700600

Left Hand

SPECIFICATIONS

- Size 24 x 12.00-12
- Outside Diameter 24.37"
- Tread Directional Lug
- Tread Width 12"
- Mount: 5 hole on 4 1/2" B.C.
- 2 3/4" dia. pilot
- Backspace 4.5"
- Tire Tubeless
- Load Rating 1710 lbs. @10mph
- Pressure 20 PSI max.
- Ply Rating 4
- Actual Weight 39.15 lbs.
- Dimensional Shpg. 57 lbs.

250/50R15**Radial Tire Pair****ITEM 700759****\$49.95**

- New, Vision Envy 250/50R15 6-ply radial DOT rated tire pair. Applications include golf carts, mowers, ATVs, and other low-speed vehicles.

SPECIFICATIONS

- Tread Width 9.75"
- Tire Tubeless
- Load Rating 910 lbs @ 30 PSI
- Pressure 30 PSI
- Ply Rating 6
- Max. Speed 40 mph
- Shpg. 91 lbs.
- Tread Envy non-conventional

4.80/4.00-8**Wheelbarrow Wheel****ITEM 700549****\$65.60**

- New, LOADSTAR wheelbarrow tire on steel wheel with ball bearings. NHS

SPECIFICATIONS

- Size 4.80/4.00-8
- Outside Diameter 16"
- Tread Sawtooth
- Tread Width 3 1/4"
- Cross section 4"
- Bore 5/8"
- Bore Thru-Length 6"
- Hub Type Centered
- Bearing Ball
- Tire Tubeless
- Load Rating 590 lbs.
- Pressure 30 PSI max.
- Ply Rating 4
- Shpg. 12 lbs.

8" x 5.5" Steel**Wheel Rim w/Bearings****ITEM 700415****\$5.99**

- New take-offs, black steel rim with dual ball bearings for 8" tires.

SPECIFICATIONS

- Wheel Rim Size 8" x 5.5"
- O.D. 8 7/8"
- Width 6 5/16"
- Bearings Ball
- Bore 3/4"
- Hub thru length 3 1/16"
- Hub type Offset
- Shpg. 8 lbs.