

Flush Face Quick Coupler

ITEM 907079

\$24.95

• New, Flush face quick coupler. Includes body and tip. Flush face design is easily cleaned, minimizes oil spillage during disconnection and air inclusion during connection. One-handed, push-to-connect convenience. Commonly used on many models of skid-steer loaders and construction and agricultural equipment. Plated steel construction. Interchangeable with Parker FEM, Faster FF, Holmberg Series A and other brands of quick couplings that conform to International Standard ISO 16028 dimensional requirements.

SPECIFICATIONS

- ISO Standard 16028
- ISO Body Size 1/2"
- Ports SAE 12
- Tip Diameter 0.96"
- Pressure, Working 3000 PSI Max
- Burst, Pressure 12000 PSI
- Flow 11.9 GPM Max
- Temperature Range -25° C to 125° C
- Oil Spillage (at disconnect) 0.07 cc
- Coupler O.D. 1.72"
- Coupled Length 6 3/4"
- Shpg. 3 lbs.

22 GPM Two Stage Hydraulic Pump

ITEM 906420

\$149.95

• New, BAILEY two stage HI/LO pressure hydraulic gear pump. Ideal for applications such as log splitters, presses and other equipment where rapid movement of the cylinder at low pressure is required prior to automatically switching to the high pressure mode to meet load requirements.

SPECIFICATIONS

- Model Number CBDN-16/7SA2
- Displacement: 0.429 cu. in. / rev. HI press. stage 0.989 cu. in. / rev. LO press. stage
- Pump Type Gear
- Rotation CW
- Pressure 3000 PSI max.
- Speed 3600 RPM max.
- Flow: 6.1 GPM HI press. stage 22 GPM LO press. stage
- Unloading Pressure 652 PSI
- Mount 2-Bolt SAE A
- Shaft 5/8" dia. x 2' long w/ 3/16" keyway
- Inlet Port SAE 16
- Outlet Port SAE 12
- Size 8 1/4" x 6" x 4 1/2"
- Shpg. 16 lbs.

24 HP Kohler Engine

ITEM 300391

\$699.95

• New, Kohler KT735-3094 7000 series four-cycle, twin-cylinder, air-cooled, vertical shaft, gasoline, OHV, with cast iron cylinder sleeves. Applications include residential riding and zero turn mowers. Fits TimeCutter, TimeCutter Max and Quest S. Does not include fuel tank or muffler. Adjustable mechanical governor.

SPECIFICATIONS

- Brand Kohler
- Model KT735-3094
- Engine Family 7000 series
- Power 24 HP
- Torque 40.5 lb-ft @ 2400 RPM
- Bore/Stroke 3.3" (83mm)/2.6" (67mm)
- Disp. 44.2 cu in (725 cc)
- Oil Capacity 2.0 US qt. (1.9 L)
- Speed Governor set to 3300 RPM max.
- Start Electric
- Fuel Tank None
- Shaft 1" (25.4mm) dia. x 3.16" (80.26 mm) w/ 0.25" Keyway tapped 7/16"-20 TPI
- Mount Four 0.34" dia. unthreaded holes on 10" dia. B.C.
- Size 18.6" x 17.5" x 13.9"
- Shpg 125 lbs.

Truck freight only.

SURPLUS CENTER

1015 West "O" Street
Lincoln, NE 68528

8-20 Ton Scissor Hoist Kit for Dump Trailers Maxim 516

ITEM 300386

\$799.95

Additional specifications on each hoist can be found on page 2.



10-20 Ton Scissor Hoist Kit for Dump Trailers Maxim 520

ITEM 300388

\$899.95

1 Spool 30 GPM Log Splitter Valve

ITEM 906130

\$239.45

• Brand new CROSS CD11FCA0 series directional control valve for operating double acting cylinders. Features include monoblock construction, built-in pressure relief valve, open center, side inlet/outlet and top work ports. Handle assembly can be mounted to have the handle be push or pull to extend the cylinder.

SPECIFICATIONS

- Brand Cross Mfg.
- Model# SCD2E
- Cross Item# 108360
- Open Center
- Spools One
- Flow 30 GPM max.
- Pressure 2500 PSI rated
- Size 12.62" x 7.41" x 4.62
- Relief Valve 2000 PSI, fixed
- Detent Release Pressure 1000 PSI
- In/Out Ports 3/4" NPT
- Work Ports 1/2" NPT
- Mount Three, 3/8" dia. holes
- Shpg. 12 lbs.

2.5" x 14" x 1.25"

ITEM 905477

\$59.95

New, BAILEY welded, double acting cylinder. Includes SAE to JIC adapters, 90° JIC 6 M on rod end and JIC 6 M straight on base end.

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2 1/2" x 14"
- Pressure 3000 PSI max.
- Rod Dia. 1/4"
- Ports SAE 6
- Retracted Length 24 1/4"
- Clevis Ends
- Pin Holes 1"
- Shpg. 27 lbs.

7.05 cu in Hydraulic Motor

ITEM 906471

\$799.95

• New. Rexroth axial piston variable motor. The automatic high pressure related control adjusts the displacement automatically depending on the working pressure.

SPECIFICATIONS

- Brand Rexroth
- Model AGM-115HA1000004C/71AR-V0D4T11U0-0
- Family A6VM
- Series 71
- Displacement 7.05 cu. in. / rev.
- Motor Type Axial Piston
- Rotation CW
- Pressure: 6527 PSI cont.
- Size 16" x 8" x 12 1/2"
- Torque: 7328 in-lbs. max.
- Speed: 3550 RPM cont. 6150 RPM int.
- Flow: 108 GPM max.
- Mount Four bolt SAE D
- Shaft 1 1/4" dia. 13T, 2 1/2" long
- Ports 1", 4 bolt flange, code 62
- Case Drain SAE 16
- Shpg. 158 lbs.

Truck freight only.

1" Steel Flange Bearing

ITEM 604137

\$8.95

• New, Sealed self aligning ball bearing with two bolt stamped steel two piece housing. Model SB205-16/R2. Bearing is centered in housing. Inner race has 2 set screws for locking to shaft.

SPECIFICATIONS

- Bearing Model# SB205-16/R2
- Housing Model# PFL205
- Bore 1"
- Mount 2 Bolt, 3" c/c
- Bore thru length 1.06"
- Bolt size 5/16" sq.
- Size 3.74" x 2.74" x 1.17"
- Shpg. 0.55 lbs.