

8 GPM Wolverine by Prince MB Series Compact Double Acting Directional Control Valves

• Brand new WOLVERINE by PRINCE MB Series directional control valve for operating double acting cylinders. Ideal for small tractor and other low flow applications requiring a compact control valve. Features include monoblock construction, load check, built-in adjustable pressure relief valve, spring centering spool action, open center with enclosed plug to convert to power beyond or closed center, side or top inlet/outlet ports and vertical or horizontal handle mounting.

SPECIFICATIONS

- Flow 8 GPM max.
- Pressure 3500 PSI max.
- Relief valve 2000 PSI, adj. 2000-3500 PSI
- Reqd. filtration ISO 4406 19/17/14

- Mount 3 hole base
- In/Out ports SAE 8
- Work ports SAE 8
- Open center convertible to power beyond or closed ctr.



Motoring Spool Valves can be found on page 31

# Spools	ITEM	Style	Size	Shpg.	Price
One	902240	DA spring centered	7 $\frac{5}{8}$ " x 4" x 2 $\frac{1}{4}$ "	9 lbs.	\$169.50
One	903111	DA spring centered w/float	9 $\frac{1}{8}$ " x 4" x 2 $\frac{1}{4}$ "	9 lbs.	\$284.20
Two	902241	DA spring centered	7 $\frac{5}{8}$ " x 5 $\frac{7}{16}$ " x 2 $\frac{1}{4}$ "	12 lbs.	\$282.15
Two	902242*	DA spring centered w/float	9 $\frac{1}{8}$ " x 5 $\frac{7}{16}$ " x 2 $\frac{1}{4}$ "	12 lbs.	\$336.00
Three	902243	DA spring centered	7 $\frac{5}{8}$ " x 6 $\frac{13}{16}$ " x 2 $\frac{1}{4}$ "	15 lbs.	\$440.10
Four	902244	DA spring centered	7 $\frac{5}{8}$ " x 8 $\frac{7}{16}$ " x 2 $\frac{1}{4}$ "	18 lbs.	\$392.85
Five	902245	DA spring centered	7 $\frac{5}{8}$ " x 9 $\frac{13}{16}$ " x 2 $\frac{1}{4}$ "	21 lbs.	\$700.00
Six	902246	DA spring centered	7 $\frac{5}{8}$ " x 11 $\frac{7}{16}$ " x 2 $\frac{1}{4}$ "	24 lbs.	\$767.50

* First spool detented float



Joystick Handle Kit

ITEM 902392 \$298.50

• Brand new, straight joystick handle for use with Wolverine MB Series valves. Allows one lever to control two different adjacent work sections. Spools can be operated independently or simultaneously. If two joysticks are installed on one stack valve, it is recommended that there be two standard work sections between them to prevent handle interference.

SPECIFICATIONS

- Straight handle joystick control
- Shpg. 2 lbs.

MB Series Accessory Power Beyond/Closed Center Conversion Plug

ITEM 902248

\$15.00

- For use with Wolverine MB Series valves. Power beyond plug is necessary to convert valves to closed center. Shpg. 1/10 lb.



Compact Double Acting Directional Control Valve

• New CHIEF directional control valve for operating double acting cylinders. Ideal for small tractors and other compact applications. Features include monoblock construction, built-in adjustable pressure relief valve, load check, spring centering spool action, open center, side inlet/outlet ports, top work ports and vertical or horizontal handle mounting.

SPECIFICATIONS

- Open Center
- Double Acting
- Spring Centering
- Flow 10 GPM max.
- Pressure 3600 PSI max.
- Relief Valve Set at 2250 PSI, adj. 1500-3600 PSI
- In/Out Ports SAE 10
- Work Ports SAE 8
- Mount 2 hole base

1 Spool

ITEM 904535

\$69.95

Size 8 $\frac{1}{4}$ " x 3 $\frac{5}{8}$ " x 2 $\frac{7}{16}$ " Shpg. 8 lbs.

2 Spool

ITEM 904536

\$119.95

Size 8 $\frac{1}{4}$ " x 5 $\frac{5}{8}$ " x 2 $\frac{7}{16}$ " Shpg. 12 lbs.



6 Spool Control Valve

ITEM 904372 \$299.95

• New, WALVOIL SD6 sectional directional control valve. Features cast iron construction, load check, adjustable flow control, open center, and vertical or horizontal handle mounting.

SPECIFICATIONS

- Open Center
- Spools Six
- Flow 12 GPM max.
- Pressure 4600 PSI max.
- Relief Valve none
- In/Out Ports SAE 8
- Work Ports SAE 8
- Size 12 $\frac{1}{2}$ " x 11" x 6 $\frac{1}{2}$ "
- Shpg. 55 lbs.



1 Spool Control Valve

ITEM 906137 \$181.05

• Brand new CROSS SCV1 CONVERTA series directional control valve for operating double-acting or single-acting cylinders. Included with a 3-way port plug and 3-way conversion plug to convert from basic 4-way (double-acting) to a 3-way (single-acting) cylinder. Painted black.

SPECIFICATIONS

- Brand Cross Mfg.
- Model# SCV1
- Cross Item# 103980
- Open Center
- Spools One
- Flow 25 GPM max.
- Pressure 2000 PSI max.
- Relief Valve 2000 PSI @ 10 GPM
- In/Out Ports 3/4" NPT
- Work Ports 1/2" NPT
- Mount Three, 3/8" dia. holes
- Size 12.62" x 7.41" x 4.62"
- Shpg. 11 lbs.



Compact 6 Spool Double Acting Directional Control Valve

ITEM 905604 \$399.95

• New WOLVERINE by PRINCE model W-V-C03, MB series directional control valve for operating double acting cylinders. Ideal for small tractor and other low flow applications requiring a compact control valve. Features include monoblock construction, load check, built-in adjustable pressure relief valve, spring centering spool action, open center with enclosed plug to convert to power beyond or closed center, side or top inlet/outlet ports and vertical or horizontal handle mounting. Painted black.



SPECIFICATIONS

- Open Center Convertible to power beyond or closed center
- Spools Six
- Flow 8 GPM max.
- Pressure 3500 PSI max.
- Work Ports SAE 8
- Relief Valve 2500 PSI, adj. 2000-3500 PSI
- Reqd. Filtration ISO 4406 19/17/14
- Mount 3 hole base
- Size 7 $\frac{5}{8}$ " x 11 $\frac{7}{16}$ " x 2 $\frac{1}{4}$ "
- Shpg. 26 lbs.