

**Hydraulic Solenoid Valves** ▲

- Brand new EATON VICKERS DG4V-3 Series. Dual solenoid directional valves for operating hydraulic cylinders, motors and other actuators. Spring centering spool action. Manual over-ride on solenoids. Valves ship with four cap-screws for mounting. Requires D03 subplate sold separately on this page. Use with two Hirschmann connectors (not incl.) for wiring.

**SPECIFICATIONS**

- GPM 10 1/2
- PSI 3000
- Ports D03 subplate mtg.
- Shpg. 6 lbs.

**Voltage****ITEM****Price****Valve Type****Spool Details****12 VDC****901041****\$232.60**

## Open center

## Work ports blocked in neutral

## Amperage 3.5

**901043****\$195.30**

## Closed center

## All ports blocked in neutral

## Size 8 3/4" x 1 1/8" x 2 1/8"

**901042****\$201.30**

## Open center

## All ports open to tank in neutral

**120 VAC****901796****\$283.45**

## Open center

## Work ports blocked in neutral

## Amperage 0.35

**901798****\$294.80**

## Closed center

## All ports blocked in neutral

## Size 7 3/4" x 1 1/8" x 2 1/8"

**901797****\$292.45**

## Open center

## All ports open to tank in neutral

**Solenoid Coil Wire Connector****ITEM 500318****\$7.95**

- Brand new HIRSCHMAN style connector for installation of wires to solenoid coil. Two connectors required for each solenoid valve. Shpg. 1/10 lb.

**D03 Subplates** ▲


- Brand new D03 aluminum subplates for solenoid operated valves.
- Parallel circuit for closed center valves.
- Series circuit for open center valves.



Parallel

Series

Valves	Parallel		Series		Ports	Shpg.
	ITEM	Price	ITEM	Price		
1	<b>900622</b>	<b>\$43.50</b>	<b>900622</b>	<b>\$43.50</b>	IN SAE 6, OUT SAE 6, Work SAE 6	<b>2 lbs.</b>
2	<b>900623</b>	<b>\$90.00</b>	<b>901062</b>	<b>\$115.75</b>	IN SAE 10, OUT SAE 12, Work SAE 8	<b>6 lbs.</b>
3	<b>900624</b>	<b>\$138.00</b>	<b>901002</b>	<b>\$153.25</b>	IN SAE 10, OUT SAE 12, Work SAE 8	<b>7 lbs.</b>
4	<b>903090</b>	<b>\$183.00</b>	<b>903091</b>	<b>\$196.75</b>	IN SAE 10, OUT SAE 12, Work SAE 8	<b>9 lbs.</b>

**Directional Control Valves** ▲

- Brand new HYDRAFORCE dual solenoid directional control valves.

**SPECIFICATIONS**

- Pressure 3500 PSI
- Spools one
- In/Out ports SAE 6
- Work ports SAE 6
- Mount 2 hole side 2" c/c
- Size 2 1/2" x 1 3/4" x 7 3/4"
- Shpg. 5 lbs.

Voltage	ITEM	Price	Valve Type	Spool Details		
					Ports	Shpg.
<b>12 VDC</b>	<b>907067</b>	<b>\$178.80</b>	Open center	Work ports blocked in neutral		<b>2 lbs.</b>
	<b>907068</b>	<b>\$170.85</b>	Closed center	All ports blocked in neutral		
	<b>907063</b>	<b>\$172.00</b>	Open center	All ports open to tank in neutral		
<b>115 VAC</b>	<b>907069</b>	<b>\$236.20</b>	Open center	Work ports blocked in neutral		<b>8 lbs.</b>
	<b>907071</b>	<b>\$228.25</b>	Closed center	All ports blocked in neutral		
	<b>907070</b>	<b>\$229.40</b>	Open center	All ports open to tank in neutral		

**1" NPT Hydraulic Relief Valve****ITEM 902283****\$133.00**

- Brand new, BUYERS PRODUCTS model HRV10025 inline (3 port) relief valve. Ball and spring direct acting style. Cast iron body. Three mounting holes for 3/8" bolts.

**SPECIFICATIONS**

- Flow Rating 50 GPM max
- Relief Range 1501-3000 PSI
- Factory Setting 2000 PSI
- Ports 1" NPT
- Gauge Port 1/4" NPT
- Size 9 3/8" x 3 1/2" x 3 1/4"
- Shpg. 10 lbs.

**SAE 12 30 GPM Motor Relief Bypass Valve** ▲**ITEM 904002****\$261.90**

- Brand new, FLUIDTECH four port inline crossover relief and bypass check valve. Provides overload and shut off protection for motor wind down when used with hydraulic control valves that have blocked work ports in neutral. For non reversible applications only. Ideal for use with skid steer loader or tractor valve outlets for operating remote hydraulic motor for overload and shut off protection. Two mounting holes for 3/8" bolts.

**SPECIFICATIONS**

- Flow Rating 30 GPM max
- Pressure Rating 3000 PSI max
- Relief Range 450-3000 PSI
- Ports SAE 12
- Size 2 1/2" x 3 7/8" x 8 1/8"
- Shpg. 7 lbs.

**Electric Flow Control**

- Brand new BRAND HYDRAULICS. Variable flow control valve with 12 volt DC controller for remote operation. Gives convenient hydraulic motor speed control from tractor cabs.

**SPECIFICATIONS**

- Control Voltage 12 Volt DC
- Flow Range 0-15 GPM
- Pressure 3000 PSI max.
- Size 9 1/2" x 5" x 1 1/8"
- Shpg. 12 lbs.

**ITEM 900884****\$852.85**

- Flow range 0 - 15 GPM.

**ITEM 902443****\$852.85**

- Flow range 0 - 30 GPM.

**12 VDC & 115 VAC****Solenoid****Operated****Poppet****Valves** ▲

- Brand new HYDRAFORCE. Solenoid operated 2 way poppet type valves. Use for starting, stopping, or dumping of hydraulic circuits to 3000 PSI (not a directional control valve). Available in N.O. or N.C. configurations with 12 volt DC or 115 volt AC coils. Continuous rated solenoids with hardened seats for long life and low leakage. Rated 12-15 GPM, ports SAE 8. Shpg. 2 lbs.

Voltage	ITEM	Valve Type	Price
<b>12 VDC</b>	<b>907058</b>	Normally Open	<b>\$102.25</b>
Amps 1.67	<b>907057</b>	Normally Closed	<b>\$91.30</b>
<b>115 VAC</b>	<b>907075</b>	Normally Open	<b>\$130.95</b>
Amps 0.18	<b>907074</b>	Normally Closed	<b>\$120.00</b>

**Flow Control w/ Shutoff Valve**

- Brand new, BUYERS dual flow control valve with shutoff for snow spreader equipment, fertilizer applicators and other motor speed control applications. Two pressure compensated flow controls for speed control of auger and spinner motors, relief valve and ON/OFF lever valve.

**SPECIFICATIONS**

- Flow Inlet 40 GPM max.
- Port Spinner 1/2" NPT
- Pressure 2000 PSI max.
- Size 7 3/4" x 5 1/4" x 4"
- Relief Valve 1500 PSI
- Shpg. 9 lbs.

**ITEM 904060****\$309.35**

- Flow Rate Spinner 0-7 GPM
- Flow Rate Auger 0-15 GPM

**ITEM 904061****\$289.50**

- Flow Rate Spinner 0-10 GPM
- Flow Rate Auger 0-30 GPM