

20 GPM Single Selector Valves



\$198.00 each

• Brand new PRINCE. Two position two-way selector valves. Directs pump flow to select between two circuits. Also use to select between two different single acting hydraulic cylinders from one valve.

SPECIFICATIONS

- GPM 20
- Size 5 1/8" x 3 1/4" x 2 1/4"
- Shpg 6 lbs.

ITEM	Model	Ports
901036	SS-1A1D	3/8" NPT
901035	SS-2A1D	1/2" NPT

40 GPM Single Selector Valves



CROSS



• Brand new, CROSS high flow, single selector valves. Use to switch pump flow from one circuit to a different circuit.

SPECIFICATIONS

- Flow 40 GPM max.
- Size 6 1/8" x 4 1/8" x 2 5/8"
- Mount Two holes on 3" ctrs.
- Shpg. 8 lbs.

ITEM	Model	Ports	PSI	Price
902281	VS4BKL7	1" NPT	2500	\$127.00
902282	VS4BKL9	SAE 16	3000	\$126.80
906152	VS4BKL6	3/4" NPT	2500	\$117.95
906153	VS4BKL8	SAE 12	2500	\$122.40

CROSS

20 GPM Single Selector Valves



• Brand new, CROSS high flow, single selector valves. Use to switch pump flow from one circuit to a different circuit.

SPECIFICATIONS

- Flow 20 GPM max.
- Size 5.33" x 3.25" x 2.25"
- Shpg. 4 lbs.

ITEM	Model	Ports	PSI	Price
906154	VS2BKL2	1/2" NPT	2500	\$87.00
906155	VS2BKL4	SAE 8	2500	\$87.00

30 GPM Single Selector Valves



ITEM 902280
\$231.00

• Brand new, PRINCE Model RD-975 single selector valves. Use to switch pump flow from one circuit to a different circuit.

SPECIFICATIONS

- Flow 30 GPM max.
- Pressure 3000 PSI max.
- Port 3/4" NPT
- Mnt 2 holes on 3 7/8" ctrs.
- Size 4 5/8" x 4 1/8" x 1 3/4"
- Shpg. 9 lbs.

12 VDC Solenoid Operated Double Selector Valves



900873



902155

- Brand new. Dual 12 volt DC solenoid operated double selector/multiplier valve. Use to expand the number of tractor remotes or operate two different circuits consisting of cylinders or motors from a single directional valve. Rated 3000 PSI. Terminal connections are 1/4" spade. Choose between individual or primary circuit types with two different rated flow rates.

MADE IN USA

Individual Circuit Selector

• Each circuit has its own coil that is energized to allow a directional control valve to operate the circuit selected. When used with "variable flow" or "closed center" systems valve can be used as a selector, or power both solenoids to direct fluid to both circuits at the same time. A SPDT-CO switch or two momentary pushbutton switches are required to operate selector valve.

ITEM	Flow	Ports	Amps	Size	Shpg.	Price
900873	15	SAE 8	1.67	4 1/2" x 2 1/2" x 6 1/2"	7 lbs.	\$292.05
902155	20	SAE 12	2.6	5 1/4" x 3" x 8 7/8"	15 lbs.	\$384.25

Primary Circuit Selector

• Primary type allows a directional control valve to operate one circuit with no power to selector valve. To select the other circuit, both solenoids are powered. This operation allows selection to be done by a SPST pushbutton or toggle switch. Ideal for operating a "thumb" on a loader bucket.

ITEM	Flow	Ports	Amps	Size	Shpg.	Price
902154	6	SAE 8	1.67	4 1/2" x 2 1/2" x 6 1/2"	7 lbs.	\$292.05

Double Selector Valves

MADE IN USA



\$279.45 each

• Brand new PRINCE. Allows one control valve to operate two different double acting cylinders or reversible motors. Also use to select between two different circuits from one hydraulic source. 2500 PSI. Shpg. 13 lbs.

ITEM	GPM	Ports
900599	20	1/2" NPT
901038	30	3/4" NPT
901039	40	1" NPT

Double Selector Valve

CROSS



ITEM 903987

\$231.40

• New CROSS allows one control valve to operate two different double acting cylinders or reversible motors. Also use to select between two different circuits from one hydraulic source. Detent on spool holds spool securely in either position.

SPECIFICATIONS

- Model SD4BADA3
- Flow 40 GPM
- Pressure 2500 PSI
- Positions two detented
- Ports SAE 10 (7/8"-14 ORB)
- Size 8" x 4 1/4" x 3 1/4"
- Shpg 11 lbs.

12 VDC Double Selector Valve

DYNAMIC
FLUID COMPONENTS, INC.



• Brand new, DYNAMIC Model DSV 12 volt DC solenoid operated double selector valve. Allows one directional valve to operate two independent cylinders. Energizing coil shifts from cylinder 1 to cylinder 2. Ideal for adding a "thumb" to buckets on loaders. Furnished with O-ring so they can be stacked together for even more function choices. Includes Hirschmann wiring connector.

SPECIFICATIONS

- Pressure 3600 PSI max
- Coil Voltage 12 Volt DC
- Current 2.5 amps
- Connector Hirschmann
- Size 7" x 2 1/2" x 2 3/4"
- Shpg. 10 lbs.

ITEM 903743

13.2 GPM SAE 8 Ports

ITEM 904759

24 GPM SAE 10 Ports

\$160.00

\$190.00

12 VDC Solenoid Selector Valve

HYDRAFORCE
POWER FORWARD™



ITEM 907093

\$244.85

• Brand new HYDRAFORCE. Three port 12 volt DC solenoid operated selector valve. Use to switch pump flow from one circuit to a different circuit.

SPECIFICATIONS

- Flow 15 GPM
- Pressure 3500 PSI
- Voltage 12 volt DC
- Amperage 2.8 amps
- Ports SAE 12
- Terminal Connection Wire leads
- Size 4" x 2 1/4" x 8"
- Shpg. 8 lbs.

**Ordering Information
on page 4**