




MTE Rotary Flow Dividers



- Brand new, MTE 200 series. Hydraulic gear type rotary flow dividers. Accurately divide flow from one source into two or more equal proportionate flows. Relief valves do not limit system pressure, they only limit differential pressure from outlets to inlet.

SPECIFICATIONS

- Adj. relief valve set at 750 PSI
- Adj. range 500 to 1000 PSI
- PSI max.: Inlet 3000, Outlet 3500
- Factory set PSI differential between sections 750 PSI

2 Section 50:50 Dividers


ITEM	Displ.	Input GPM		Output GPM Per Section		Ports		Size	Shpg.	Price
		Min.	Max.	Min.	Max.	Inlet	Outlet			
903131	0.11	1.8	4.2	0.9	2.1	SAE 8	SAE 8	6.49" x 3.94" x 4.66"	11 lbs.	\$249.90
903133	0.251	4.3	9.7	2.2	4.8	SAE 10	SAE 10	7.08" x 3.94" x 4.66"	12 lbs.	\$258.30
903135	0.323	5.9	12.5	2.8	6.3	SAE 10	SAE 10	7.38" x 3.94" x 4.66"	13 lbs.	\$263.45
903137	0.479	8.3	18.6	4.1	9.3	SAE 10	SAE 10	8.03" x 3.94" x 4.66"	15 lbs.	\$281.30

4 Section 25:25:25:25

ITEM	Displ.	Input GPM		Output GPM Per Section		Ports		Size	Shpg.	Price
		Min.	Max.	Min.	Max.	Inlet	Outlet			
903132	0.11	3.8	8.6	0.95	2.1	SAE 8	SAE 8	9.77" x 3.94" x 4.66"	19 lbs.	\$494.65
903134	0.251	8.6	19.5	2.2	4.9	SAE 10	SAE 8	10.94" x 3.94" x 4.66"	21 lbs.	\$515.80
903136	0.323	11.2	25.7	2.8	6.3	SAE 10	SAE 8	11.55" x 3.94" x 4.66"	22 lbs.	\$521.10
903138	0.479	16.6	37.3	4.1	9.3	SAE 10	SAE 8	12.84" x 3.94" x 4.66"	26 lbs.	\$529.95

Inline Check Valves

- Brand new, DYNAMIC HSP series hard seat, inline check valves. Available with NPT or SAE ports with 5 PSI or 65 PSI cracking pressures. Plated steel.



DYNAMIC
FLUID COMPONENTS, INC.

	ITEM	PSI Rated (Max)	GPM	Ports	Width (Across Flats)	Length	Shpg.	Price
				(Across Flats)				
NPT	5 PSI Cracking							
	902317	5000	6	1/4" NPT	0.87"	2.44"	1/2 lb.	\$18.65
	902318	5000	10	3/8" NPT	0.95"	2.87"	1/2 lb.	\$19.40
	902319	5000	18	1/2" NPT	1.14"	3.50"	1 lb.	\$23.65
	902320	3000	30	3/4" NPT	1.50"	4.25"	2 lbs.	\$34.80
	902321	3000	36	1" NPT	1.69"	5.12"	3 lbs.	\$48.95
	902322	3000	50	1 1/4" NPT	2.40"	5.56"	7 lbs.	\$85.35
	902323	3000	60	1 1/2" NPT	2.56"	5.56"	8 lbs.	\$87.35
	65 PSI Cracking							
	902331	5000	6	1/4" NPT	0.87"	2.44"	1/2 lb.	\$18.65
	902332	5000	10	3/8" NPT	0.95"	2.87"	1/2 lb.	\$19.40
	902333	5000	18	1/2" NPT	1.14"	3.50"	1 lb.	\$23.65

	ITEM	PSI Rated (Max)	GPM	Ports	Width (Across Flats)	Length	Shpg.	Price
				(Across Flats)				
SAE	5 PSI Cracking							
	902324	5000	6	SAE 4	0.87"	2.56"	1/2 lb.	\$17.60
	902325	5000	10	SAE 6	0.94"	2.91"	1/2 lb.	\$20.05
	902326	5000	18	SAE 8	1.18"	3.74"	1 lb.	\$25.60
	902327	3000	30	SAE 12	1.50"	4.29"	2 lbs.	\$38.10
	902328	3000	36	SAE 16	1.81"	5.00"	3 lbs.	\$53.50
	902329	3000	50	SAE 20	2.41"	5.20"	7 lbs.	\$86.70
	902330	3000	60	SAE 24	2.56"	5.20"	8 lbs.	\$89.30
	65 PSI Cracking							
	902338	5000	6	SAE 4	0.87"	2.56"	1/2 lb.	\$17.60
	902339	5000	10	SAE 6	0.94"	2.91"	1/2 lb.	\$20.05
	902340	5000	18	SAE 8	1.18"	3.74"	1 lb.	\$25.60

Pilot Operated Check Valves



- Brand new, pilot operated check valves. In one direction oil passes freely through the valve to the cylinder. In the other direction flow is blocked in the cylinder by the valve until pressure is applied at the pilot port allowing flow from the cylinder back through the valve.

Prince



SPECIFICATIONS

- Max. 3000 PSI
- Max. 20 GPM inlet
- Pilot ratio 4:1
- Decompression ratio 16:1
- Size 5 1/16" x 1 1/2" x 2 1/2"
- Shpg. 3 lbs.

ITEM 903221 \$250.50

- Model RD-1608. Ports SAE 8, pilot port SAE 4.

ITEM 903220 \$301.75

- Model RD-1650. Ports 1/2" NPT, pilot port 1/4" NPT.

BRAND
HYDRAULICS



ITEM 903222 \$80.15

SPECIFICATIONS

- Model PC37C
- Inlet Port 3/8" NPT female
- Outlet Port 3/8" NPT male
- Pilot Port 1/4" NPT
- Max. Pressure 3000 PSI
- Max. Flow 8 GPM
- Pilot Ratio 4:1
- Size 3 7/16" x 5/8" x 1 1/16"
- Shpg. 1 1/2 lbs.

ITEM 903219 \$83.70

SPECIFICATIONS

- Model PC50C
- Inlet Port 1/2" NPT female
- Outlet Port 1/2" NPT male
- Pilot Port 1/4" NPT
- Max. Pressure 3000 PSI
- Max. Flow 16 GPM
- Pilot Ratio 4:1
- Size 3 15/16" x 3/4" x 1 29/32"
- Shpg. 1 1/2 lbs.