

3.94" x 18.875" x 1.97"**ITEM 904819**
SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore/Stroke 3.94" x 18.875"
- 3000 PSI max
- Rod dia. 1.97"
- Ports JIS 12"
- Retracted Length 36.25"
- Tang Ends
- Swivel Eye Widths 2.25"
- Rod End: Width 2.39"
- Base End: Width 2.37"
- Pin holes 1.97"
- Shpg. 98 lbs.

Truck freight only.

\$179.95**4" x 14" x 1.5"****ITEM 905598**
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 4" x 14"
- Pressure 3000 PSI
- Rod Dia. 1.5"
- Ports SAE 8
- Retracted Length 24.25"
- Clevis Ends
- Pin Holes 1"
- Shpg. 50 lbs.

\$149.95**4" x 16" x 2"****ITEM 905730**
SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 4" x 16"
- Pressure 3000 PSI max.
- Rod Dia. 2"
- Ports SAE 12
- Retracted Length 28.5"
- Cross-Tube Ends
- Width 5"
- Pin Holes 2.5"
- Actual Weight. 115 lbs.
- Shpg. 155 lbs.

\$199.95

Truck freight only.

4" x 16" x 2"**ITEM 905731**
SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 4" x 16"
- Pressure 3500 PSI max.
- Rod Dia. 2"
- Ports SAE 12
- Retracted Length 28.5"
- Gland Face to Rod Pin Center 4"
- Cross-Tube Ends
- Rod End: Width 5"
- Base End: Width 5"
- Pin Holes 2.5"
- Actual Weight 100 lbs
- Shpg. 140 lbs.

\$199.95

Truck freight only.

4" x 18" x 2"**ITEM 903762**

- Both ports in rod end.

SPECIFICATIONS

- Unused, old inventory
- Double Acting
- Bore x Stroke 4" x 18"
- Pressure 3000 PSI
- Rod Dia. 2", hollow
- Rod thickness 7/16"
- Ports 1/4" NPT
- Retracted Length 29 5/8"
- Thru-hole ends rod 2 7/8" w., base 2" w.
- Pin Holes rod 1 1/8", base 1 1/4"
- Shpg. 67 lbs.

\$194.95**4" x 18.625" x 2"****ITEM 906341**
SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 4" x 18.625"
- Pressure 2500 PSI max.
- Rod Dia. 2"
- Ports SAE 10
- Retracted Length 33.5"
- Rod End: Clevis
- Pin Hole 2"
- Base End: Tang
- Width 1.889"
- Pin Hole 3.185"
- Shpg. 99 lbs.

\$174.95**4" x 23.625" x 2"****ITEM 902681**
SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 4" x 23 5/8"
- Pressure 3000 PSI max.
- Rod Dia. 2"
- Extend Port JIC 12 and JIC 4
- Retract Port Two SAE 12 ports
- Rod End: Tang w/ Swivel Eye
- Max Thickness 1 1/16"
- Pin Center to Tang End 29 1/4"
- Pin Hole 2"
- Trunnion: Female
- Pin Outside Width 9 1/2"
- Pin Inside Width 8 3/8"
- Pin Center to Base End 41 1/2"
- Pin Diameter 2"
- Retracted Length 43 1/2"
- Shpg. 135 lbs.
- Truck freight only.

\$159.95**4" x 24" x 1.75"****ITEM 906357**
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 4" x 24"
- Pressure 2500 PSI max.
- Rod Dia. 1.75"
- Ports SAE 8
- Retracted Length 34.5"
- Clevis Ends
- Pin Holes 1"
- Shpg. 67 lbs.

\$349.95**4" x 24" x 2"****ITEM 906947**
SPECIFICATIONS

- Double Acting
- Bore x Stroke 4" x 24"
- Pressure 3000 PSI max.
- Rod Dia. 2"
- Ports SAE 10
- Retracted Length 33"
- Cross-Tube Ends:
- Rod End: Width 3.25"
- Base End: Width 4.5"
- Pin Holes 1.25"
- Shpg. 70 lbs.

\$299.95**4" x 24" x 2"****ITEM 906787**
SPECIFICATIONS

- Double Acting
- Bore x Stroke 4" x 24"
- Pressure 2500 PSI max.
- Rod Dia. 2"
- Ports SAE 8
- Retracted Length 34.25"
- Clevis Ends
- Rod End: Outside Width 2.72"
- Inside Width 1.14"
- Base End: Outside Width 2.72"
- Inside Width 1.14"
- Pin Holes 1"
- Shpg. 83 lbs.

\$199.95**4" x 24" x 2"****ITEM 903993**
SPECIFICATIONS

- Brand New
- Double acting
- Bore x Stroke 4" x 24"
- PSI Max. 3,000
- Rod End Thru-Hole
- Pin hole 5/8"
- Base End Clevis
- Inner width 1 1/8"
- Outer width 2 5/8"
- Pin hole 1"
- Rod Dia. 2"
- Ports SAE 8
- Retracted length 32"
- Shpg. 68 lbs.

\$414.00**4" x 24" x 2"****ITEM 906711**
SPECIFICATIONS

- Double Acting
- Bore x Stroke 4" x 24"
- Pressure 3000 PSI max.
- Rod Dia. 2"
- Ports SAE 8
- Retracted Length 34.25"
- Clevis Ends
- Pin Holes 1"
- Shpg. 71 lbs.

\$279.95**3.94" x 33" x 3.94"****ITEM 904933**
SPECIFICATIONS

- Unused old inventory
- Single Acting
- Bore x Stroke 3.94"(100mm) x 33"(840mm)
- Pressure 2500 PSI max.
- Rod Dia. 3.94"(100mm)
- Rod Thickness 0.236"
- Ports JIC 16
- Retracted Length 16.25"
- Rod End ThruHole Width 1.75"
- Pin Hole 7/16"
- Base End: Mounting Stud Dimensions 1" dia. x 1/2" long
- Shpg. 111 lbs.

\$149.95

Truck freight only.

4" x 7.25" x 1.25"**ITEM 901757**
SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 4" x 7.25"
- Pressure 3000 PSI max.
- Rod Dia. 1.25"
- Ports SAE 10
- Retracted Length 21.75"
- Swivel Eye Ends
- Rod End: Width 1.405"
- Swivel Eye Width 1.532"
- Base End: Width 1.41"
- Swivel Eye Width 1.53"
- Pin Holes 1.75"
- Shpg. 52 lbs.

\$149.95**4" x 8" x 1.125"****ITEM 906808**
SPECIFICATIONS

- Double Acting
- Bore x Stroke 4" x 8"
- Pressure 2500 PSI max.
- Rod Dia. 1.125"
- Ports 1/2" NPT
- Retracted Length 18.25"
- Clevis Ends
- Pin Holes 1"
- Shpg. 43 lbs.

\$99.95**4" x 10" x 2"****ITEM 906442**
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 4" x 10"
- Pressure 3000 PSI max.
- Rod Dia. 2"
- Ports 1/2" NPT
- Retracted Length 18.5"
- Rod End: Thru-Hole
- Width 1.5"
- Pin Center to Base End 1"
- Base End: Tang
- Width 1.25"
- Pin Holes 1"
- Shpg. 44 lbs.

\$149.95**Bore** - Inside diameter of cylinder**Stroke** - How far a cylinder extends out**R-length** - Distance in inches between pin centers when cylinder is retracted**Rod Diameter** - Diameter of cylinder rod**Single Acting** - Cylinder is powered one way**Double Acting** - Cylinder is powered both ways (two way)**Crosstube End** - Round tube welded perpendicular to cylinder**Single Eye End** - For mounting between two mounting ears.**Clevis End** - Two mounting ears