



DYNAMIC
FLUID COMPONENTS, INC.**PTO Drive Motors**

- Brand new, hydraulic motor with agricultural standard 6 tooth splined shaft. Gerolator power element. Tapered roller bearings on output shaft for high axial and radial load capacity. Shaft has retention groove centered 1½" from shaft end.
- Interchangeable with the following motor lines: Char-Lynn 2000, Danfoss OMS/OMSS, White RE/DH, Parker-Ross MB/TF.

SPECIFICATIONS FOR ALL

- Rotation reversible
- Case drain SAE 4
- Ports SAE 10
- Shaft 1½" x 4" 6T spline
- Mount 2 bolt SAE A
- Size 7⅝" x 5⅞" x 4⅞"

ITEM	Displ. cu. in.	PSI Cont. Int.	Torque in. lbs. Cont. Int.	RPM Cont. Int.	GPM Cont. Int.	GPM at 540RPM at Cont. PSI	HP Cont. Int.	Shpg.	Price
902066	4.95	2576 3091	1682 2124	800 990	17.1 21	12.8	21.3 26.9	26 lbs.	\$390.15
901871	6.15	2576 3091	2124 2655	748 900	19.7 23.6	15.9	25.2 31.5	27 lbs.	\$394.35
901872	7.63	2576 3091	2744 3275	600 720	19.7 23.6	21.2	26.1 31.1	28 lbs.	\$398.55
901873	9.59	2208 3091	2780 3805	470 560	19.7 23.6	23.8	20.9 28.4	29 lbs.	\$402.75

DYNAMIC
FLUID COMPONENTS, INC.

- Brand new, DYNAMIC BMT series hydraulic motor with agricultural standard six tooth splined shaft. Heavy duty with high flow capacity. ROLORTORC power element. Tapered roller bearings on output shaft for high axial and radial load capacity. Shaft has retention groove centered 1½" from shaft end. Interchangeable with DANFOSS OMT motors.

SPECIFICATIONS FOR BOTH

- Rotation reversible
- Case drain SAE 4
- Ports SAE 12
- Shaft 1¾" x 5" 6T spline
- Mount 4 bolt SAE C

ITEM	Model	Displ. cu. in.	PSI Cont. Int.	Torque in. lbs. Cont. Int.	RPM Cont. Int.	GPM Cont. Int.	Size	Shpg.	Price
905382	BMT-160-K6-SL-S	9.83	2944 3533	4168 5071	614 770	26.42 33.02	7½" x 5⅝" x 5⅝"	47 lbs.	\$629.70
905383	BMT-200-K6-SL-S	12.29	2944 3533	5213 6354	615 743	33.02 39.63	7⅞" x 5⅝" x 5⅝"	48 lbs.	\$637.15

DYNAMIC
FLUID COMPONENTS, INC.**Heavy Duty Hydraulic Motors**

- Brand new, DYNAMIC BMK6 heavy duty hydraulic motors. Interchangeable with Char-Lynn 6000 series motors.

SPECIFICATIONS

- Rotation reversible
- Mount SAE C 4 bolt, 6⅝" bolt circle, 5" pilot dia.
- Shaft 1½" dia. x 3.01" shaft with ⅜" key, tapped ⅜"-16
- Ports SAE 16

ITEM	Displ.	PSI Cont. Int.	Torque in. lbs. Cont. Int.	RPM Cont. Int.	GPM Cont. Int.	Size	Shpg.	Price
903758	11.93	2900 4350	5000 7434	765 865	39.6 44.9	10.43" x 5.75" x 5.75"	61 lbs.	\$690.20
903757	15.01	2900 4350	6284 9558	610 830	39.6 54.1	10.67" x 5.75" x 5.75"	62 lbs.	\$703.05
903756	19.01	2900 4350	8142 11727	480 690	39.6 59.4	10.94" x 5.75" x 5.75"	64 lbs.	\$705.85
903755	23.87	2900 4350	10266 14382	382 570	39.6 59.4	11.30" x 5.75" x 5.75"	65 lbs.	\$734.35
903754	29.95	2900 3985	12789 16639	304 455	39.6 59.4	11.73" x 5.75" x 5.75"	68 lbs.	\$789.35
903753	38.01	2535 3260	13099 13726	240 360	39.6 59.4	12.32" x 5.75" x 5.75"	71 lbs.	\$805.00
903752	48.96	2030 2245	13984 16639	186 280	39.6 59.4	13.11" x 5.75" x 5.75"	75 lbs.	\$831.05
903751	59.9	2030 2030	14824 16462	152 230	39.6 59.4	13.89" x 5.75" x 5.75"	79 lbs.	\$881.60

DYNAMIC
FLUID COMPONENTS, INC.**Hydraulic Wheel Motors**

- Brand new, DYNAMIC BMER-2 series wheel mount hydraulic motors. Interchangeable with PARKER and WHITE motors.

SPECIFICATIONS

- Rotation reversible
- Mount 4 bolt wheel 5.812" bolt circle, 3¼" pilot dia.
- Shaft 1¼" tapered x 4.21" shaft w/⅝" key and threaded end
- Ports SAE 10

ITEM	Displ. cu. in.	PSI Cont. Int.	Torque in. lbs. Cont. Int.	RPM Cont. Int.	GPM Cont. Int.	Size	Shpg.	Price
903635	7.2	2970 3480	2876 3363	360 490	14.0 15.8	4.68" x 5.24" x 5.43"	29 lbs.	\$387.45
903636	9.52	2970 3480	3983 4646	375 470	15.8 19.8	4.80" x 5.24" x 5.43"	30 lbs.	\$391.60
903637	11.96	2970 3480	4691 5310	330 425	17.9 22.4	4.94" x 5.24" x 5.43"	31 lbs.	\$396.50
903638	13.91	2970 3480	5531 6284	290 365	17.9 22.4	5.04" x 5.24" x 5.43"	31 lbs.	\$413.80
903639	15.68	2970 3480	6195 6992	290 350	19.8 23.7	5.14" x 5.24" x 5.43"	32 lbs.	\$418.65
903640	18.08	2970 3480	7169 8231	250 315	19.8 25	5.30" x 5.24" x 5.43"	32 lbs.	\$422.80
903641	21.05	2970 3480	8009 9160	220 270	19.8 25.0	5.43" x 5.24" x 5.43"	33 lbs.	\$436.65
903642	22.63	2970 3480	8762 10089	200 240	19.8 23.7	5.53" x 5.24" x 5.43"	34 lbs.	\$476.85
903643	28.18	2535 2973	9602 10443	160 195	19.8 23.7	5.83" x 5.24" x 5.43"	35 lbs.	\$503.90
903644	32.94	2030 2535	8673 10974	140 170	19.8 23.7	6.14" x 5.24" x 5.43"	36 lbs.	\$512.90
903645	45.45	1520 1740	9293 10443	100 120	19.8 23.7	6.93" x 5.24" x 5.43"	40 lbs.	\$548.95