Rubber Rake Teeth A

• Brand new, rubber rake teeth by BLACK TALON. Heat treated tines with injection molded rubber. Hook style head for maximum rubber adhesion. Sold in factory box quantities. Refer to our website for specific model and mfg part numbers.



	Factor	у Вох	Sale	S				
		Yoke	Bolt	Tine	Tine			
ITEM	Application 0	pening	Hole	Lgth.	Diam.	Qty.	Shpg.	Price
1-3617-100	John Deere, many others,universal	15⁄8″	3/8"	10″	9/32"	100	55 lbs.	<i>\$322.50</i>
1-3618-100	New Holland, Allen rakes, Left Hand	155/64"	3/8"	10″	9/32"	100	59 lbs.	<i>\$373.50</i>
1-3619-100	New Holland, Allen rakes, Right Hand	155/64"	3/8"	10″	9/32"	100	59 lbs.	<i>\$373.50</i>
1-3620-100	John Deere, Vermeer	15⁄8″	3/8"	10″	9/32"	100	53 lbs.	\$402.00
1-3621-100	John Deere	15⁄8″	3/8"	10″	9/32"	100	55 lbs.	\$415.50
1-3622-50	Farmhand, New Idea,others *		3/8"	7′	9/32"	50	50 lbs.	\$439.50
1-3623-60	Vermeer, Massey Ferguson *	13⁄8″	5/16″	71/4"	1/4"	60	41 lbs.	\$413.10
1-3624-100	Ford, other windrowers	11/8″	5/16″	7½″	1/4"	100	29 lbs.	<i>\$273.95</i>
1-3625-100	Heath windrowers	11/4"	5/16″	8″	1/4"	100	29 lbs.	<i>\$471.95</i>

^{*} Double tooth

Brass Ball Valves

New. HYPRO lead-free brass ball valves











			PSI	Length x Width x Height	t	
ITEM	Model Number	Ports	Max.	with Handle	Shpg.	Price
20-1678	171N-14	1/4" NPT	600	4¼" x 3¾" x 1¾"	0.35 lb.	<i>\$5.95</i>
20-1679	171N-38	3⁄8" NPT	600	41/4" x 37/8" x 17/8"	0.3 lb.	<i>\$5.95</i>
20-1680	171N-12	1/2" NPT	600	5" x 43/8" x 21/4"	0.5 lb.	<i>\$6.95</i>
20-1682	171N-100	1" NPT	600	61/4" x 53/4" x 27/8"	3 lbs.	<i>\$12.95</i>
20-1688*	90FMB14	1/4" NPT	300	1¾″ x 1″ x 15⁄8″	0.25 lb.	<i>\$5.95</i>
20-1692*	90FMB38	3/8" NPT	300	1¾″ x 1½″ x 15%″	0.25 lb.	<i>\$6.95</i>

^{*} Plated Brass

2/6/40/200 Amp **Battery** Charger/ Starter A

ITEM 11-3713 \$179.95

 New, SCHUMACHER ELECTRIC model SC1324 12 volt battery charger. Triple mode operation, start, fast charge and slow/maintain charge. Push button con-

trols with LED indicator lights. Use with standard or AGM batteries. Includes wheel kit for portability. Thermal overload protection. mounting holes with metal insert. Shutoff valve on outlet port.

• Input 115 VAC

• Input Cord 6 ft.

. Battery Cables 6 ft.

• Size 12" x 10" x 23"

SPECIFICATIONS

- Battery Voltage 12 VDC
- Charge Rates
- Boost 200 amps
- Fast Charge 40 amps
- Slow Charge 6<>2 amps Shpg. 30 lbs.

Automatic Battery Chargers

12 Volt



· New, PEAK 12 volt battery charger. Automatic shutoff. Charge rate indicator and full charge LED. Reverse polarity indicator and thermal overload protection.

ITEM 11-3622 \$79.95

SPECIFICATIONS

- Model PKC0C100.
- · Charge Rates: Maintain 2 amps Charge 15 amps
- Start 100 amps

ITEM 11-3620

SPECIFICATIONS

- Model PKC0C6.
- · Charge Rates: Low 2 amps High 5 amps
- Battery Cables 51/2 ft.
- Size 10" x 7" x 5"
- Shpg. 19 lbs.

• Input 115 VAC

• Input Cord 6 ft.

• Input 115 VAC

- Input Cord 6 ft.
- Battery Cables 51/2 ft. • Size 83/4" x 51/2" x 41/8"
- . Shpg. 9 lbs.

Gas Springs

• Brand new, BUYERS PRODUCTS gas spring. Shock features dampened extension and undampened compression for smooth operation. The cylinder is black powder-coated for corrosion resistance. Commonly used on rear windows, tool boxes and truck boxes. Shpg 1 lb.

ITEM	Force Rating			Strok	e Price
1-6175*	35 ft-lbs.	8.5"	13.93"	5.5"	<i>\$13.75</i>
1-6176	40 ft-lbs.	8″	12"	4″	\$14.60
1-6177	60 ft-lbs.	8″	12"	4″	<i>\$14.60</i>
1-6178	80 ft-lbs.	8″	12"	4″	<i>\$12.90</i>
1-6179	97 ft-lbs.	10.8"	17.1″	6.3"	<i>\$14.60</i>
1-6180	250 ft-lbs.	11.63"	19.63"	8″	\$33.80

* Includes 10mm ball stud

ITEM 1-6182

• 10mm ball stud for gas springs. 5/16"-18 threaded stud mount.

Jumper Cables ITEM 11-3665 4



 New, heavy duty jumper cable set. Use for starting engines on cars and trucks. Compatible with top or side terminal batteries. The wire is CCA (Copper Clad Aluminum) and the connectors are made of steel, coated in copper.

SPECIFICATIONS

· Cable size 8 gauge

· Length 12 Ft. . Shpg. 3 lbs.

Heavy Duty 1 Gauge **Jumper** Cables A

ITEM 11-3408

• New, heavy duty jumper cable set in plastic carrying case. Use for starting engines on trucks, construction equipment. Compatible with top or side terminal batteries.

SPECIFICATIONS · Cable size 1 gauge

- Length 25 ft.
- . Amp rating 900 CCA
- Size 16" x 14" x 7"
- Shpg. 16 lbs.

12 VDC Electric Fuel Pump ITEM 28-2024 \$29.95



 New, CARTER FUEL SYSTEMS model P4600HP rotary vane electric fuel pump. Pump consistently delivers fuel at the precise pressure and flow rate the vehicle demands. For Carbureted and Diesel applications. Intended uses include Agricultural, Industrial, Marine, RV, and Hi-Performance Applications.

SPECIFICATIONS

- Brand Carter Fuel Systems
- Model Number P4600HP
- Voltage 12 Volt DC
- Flow 50 GPH
- Pressure 6-8 PSI
- Ports ¾" NPT
- Positive Lead 10-32 thread
- Negative Lead 10-32 thread
- Fuel Type Diesel, Gas
- Mount External from tank
- Size 4¾" x 3½" x 3"
- Shpg 4 lbs.