



• Brand new. HYPRO roller pumps give high volume and pressure for all types of agricultural spraying. Rotation can be reversed by disassembly. Super Rollers are compatible with a wide variety of chemicals. Cast iron body for general purpose spraying.

18 GPM, 8 Roller Pump

ITEM 267-CP
\$265.10



SPECIFICATIONS

- 18 GPM, 8 Roller Pump
- Model 7560-C
- 18.3 GPM
- 300 PSI
- 850 RPM
- 4.5 HP max
- Ports 3/4" NPT
- CCW rotation
- Stainless Steel Shaft 1 5/16" dia x 2"
- Ball Bearings
- Replaceable rollers, seals
- 6 3/4" x 6 1/2" x 6 1/2"
- Shpg 18 lbs.

PERFORMANCE TABLE

SPEED RPM	0 PSI		100 PSI		300 PSI	
	GPM	HP	GPM	HP	GPM	HP
550	12.0	1/4	10.6	1 1/4	8.0	3
850	18.3	1/2	16.9	1 1/2	14.2	4 1/2

20 GPM, 6 Roller Pump

ITEM 278-CP
\$202.90



SPECIFICATIONS

- 19.5 GPM
- 300 PSI
- 400 to 1200 RPM
- Ports 3/4" NPT
- CCW rotation
- Shaft 5/8" diam. x 1 1/2"
- Ball bearings
- Replaceable rollers, seals
- Size 6" x 5 3/4" x 2 1/2"
- Shpg 12 lbs.

PERFORMANCE TABLE

SPEED RPM	0 PSI		100 PSI		300 PSI	
	GPM	HP	GPM	HP	GPM	HP
540	9.1	0.21	6.5	0.81	3.3	2.10
1200	19.5	0.69	17.3	1.80	14.1	4.51

22 GPM, 7 Roller Pump

ITEM 268-CP
\$269.40



SPECIFICATIONS

- 22.4 GPM
- 200 PSI
- 850 RPM
- 1 3/4 HP max
- Ports 3/4" NPT
- CCW rotation
- Stainless Steel Shaft 1 5/16" dia x 2 1/16"
- Ball Bearings
- Replaceable rollers, seals
- 6 7/8" x 6 5/8" x 6"
- Shpg 18 lbs.

PERFORMANCE TABLE

SPEED RPM	0 PSI		100 PSI		200 PSI	
	GPM	HP	GPM	HP	GPM	HP
550	15	1/4	12.8	3/4	11.4	1 1/4
850	22.4	1/2	20.6	1 1/4	19.1	1 3/4

Roller Pump Quick Couplers



1321-0006




1321-0007

• Brand new. Use to connect Hypro roller pumps to standard tractor 1 5/8" 6 spline 540 RPM PTO shafts. Die cast construction with quick release collar.

ITEM 1321-0006 **\$50.85**
• Fits onto 5/8" pump shafts (6 roller pumps). Shpg. 4 lbs.

ITEM 1321-0007 **\$55.05**
• Fits onto 1 5/16" pump shafts (7 & 8 roller pumps). Shpg. 4 lbs.

Hydraulic Centrifugal Pump



ITEM 2-1180
\$1080.15

• Brand new HYPRO model 9303-HM1C. Cast iron centrifugal pump with direct drive hydraulic motor. Power from tractor hydraulic circuit leaving PTO free for other uses.

SPECIFICATIONS

- Maximum Pressure 120 PSI
- Maximum Pump Flow: 112 GPM
- Pump inlet 1 1/2" NPT
- Pump discharge 1 1/4" NPT
- 140° F max. fluid temp
- Hydraulic motor ports 1/2" NPT
- Hydraulic requirements-13 GPM at 2000 PSI
- 11" x 7 3/4" x 8 1/4"
- Shpg. 31 lbs.

140 GPM Centrifugal Pump



ITEM 2-1222
\$487.15

• Brand new, HYPRO 9203C cast iron centrifugal pedestal mount pump. Ideal for high volume spraying systems. Viton seals.

SPECIFICATIONS


- Model 9203C
- Max. 6000 RPM
- 1 1/2" NPT inlet port
- 1 1/4" NPT outlet port
- Rotation CCW
- Max. temp. 140° F
- 2 bolt pedestal mount on 3" centers
- Shaft 5/8" outside dia. x 2 1/8" long w/ 3/4" keyway
- Size: 7 3/8" x 7 1/4" x 8 1/4"
- Shpg. 21 lbs.

Shurflo Diaphragm Pumps

• Brand new, SHURFLO automatic demand diaphragm pumps. Ideal for spot sprayers. Santoprene diaphragm and Viton valves. Can run dry intermittently. Rubber mounting feet. Intermittent duty. Automatic on/off pressure switch. Use adapters shown below for 1/2" MSPT ported items (metal fittings and rigid pipe are not recommended). Wire leads on DC models, 6 ft. power cord on AC model.



2-1361



2-1360



2-1362
2-1363

ITEM	Model	Volts	Amps	Open Flow	GPM at PSI	Max. PSI	Ports	Switch Settings on/off	Self Priming Lift max.	Size	Shpg.	Price
2-1361	SLV10-AA41	12 DC	4	1 GPM	0.49 at 30	50	3/8" hosebarb	25/40 PSI	2 1/2 ft.	7" x 3 5/8" x 2 3/8"	3 lbs.	\$71.35
2-1360	8000-543-236	12 DC	6.4	1.8 GPM	1.4 at 40	50	3/8" NPTF	30/50 PSI	8 ft.	8 1/4" x 4" x 4 1/2"	6 lbs.	\$128.40
2-1362	2088-343-135	12 DC	7.7	3 GPM	2.05 at 40	40	1/2" MSPT	25/45 PSI	12 ft.	8 3/4" x 6" x 4 1/2"	6 lbs.	\$158.65
2-1363	2088-394-144	115 AC	0.9	3 GPM	1.6 at 40	40	1/2" MSPT	25/45 PSI	12 ft.	9" x 5 1/4" x 4 7/8"	6 lbs.	\$231.25

Shurflo Hosebarb to Pipe Fittings

• Brand new Shurflo polypropylene hosebarb to pipe fittings.

ITEM	Style	Description	Hose ID	NPT Fitting	Shpg.	Price
2-1366	A	Straight	3/8"	1/2" NPTF Swivel	1/4 lb.	\$1.10
2-1367	A	Straight	1/2"	1/2" NPTF Swivel	1/4 lb.	\$1.05
2-1364	A	Straight	5/8"	1/2" NPTF Swivel	1/4 lb.	\$2.10
2-1365	A	Straight	3/4"	1/2" NPTF Swivel	1/4 lb.	\$1.25
2-1369	B	Elbow	3/8"	1/2" NPTF Swivel	1/4 lb.	\$1.05



A



B



C

ITEM	Style	Description	Hose ID	NPT Fitting	Shpg.	Price
2-1368	B	Elbow	1/2"	1/2" NPTF Swivel	1/4 lb.	\$1.05
2-1371	B	Elbow	5/8"	1/2" NPTF Swivel	1/4 lb.	\$1.80
2-1370	B	Elbow	3/4"	1/2" NPTF Swivel	1/4 lb.	\$1.25
2-1372	C	Straight	3/8"	3/8" NPTM	1/4 lb.	\$0.50
2-1374	C	Straight	1/2"	1/2" NPTM	1/4 lb.	\$2.60