

Cast Iron High Speed Gearboxes

ITEM 13-1617-A \$207.30

• Brand new. PEERLESS cast iron gearbox. Shafts rotate in opposite direction.

SPECIFICATIONS

- Model 1050-009A
- Ratio 1:1
- Rotation Opposite
- Input Power 10 HP max continuous
- Input Speed 3600 RPM max.
- Output Torque 360 in-lb
- Input Shaft $\frac{3}{4}$ " dia. x $1\frac{1}{8}$ " w/ $\frac{3}{16}$ " woodruff keyway
- Output Shaft $\frac{3}{4}$ " dia. x $1\frac{1}{8}$ " w/ $\frac{5}{32}$ " woodruff keyway
- Mount Two $\frac{3}{8}$ "-16" bolt holes on 4" centers and 2.9" dia. pilot
- Size 7" x $5\frac{3}{4}$ " x $4\frac{3}{4}$ "
- Shpg. 13 lbs.

ITEM 13-1617-B \$211.75

• SPECIFICATIONS SAME AS ABOVE EXCEPT

- Model 1015-012 • Ratio 1.2:1 • Rotation Same

Peerless Six Speed Transaxles

ITEM 13-1620

\$509.55

• Brand new. PEERLESS MST-206-545C six speed transaxle. Push brake lever to actuate brake. "Axle-Rearward" style transaxle pre-filled with oil from the factory.

SPECIFICATIONS

- Speeds: Six forward, Reverse, and Neutral
- Input Speed 2,000 RPM
- Input Rotation CW
- Output Torque 225 ft-lbs
- Load Rating 525 lbs max
- Input Shaft $\frac{3}{8}$ " dia. x $1\frac{1}{8}$ " w/ $\frac{3}{16}$ " keyway
- Axles $\frac{3}{4}$ " dia. x $4\frac{3}{4}$ " long w/ $\frac{3}{16}$ " keyway
- Overall Axle Width 29 $\frac{1}{2}$ "
- Tire Diameter 20" max
- Gear Shift Shaft $\frac{3}{8}$ " square, tapped $\frac{1}{4}$ "-28
- Inner Mount Four holes on 13" x $1\frac{1}{2}$ " centers
- Outer Mount Four holes on 16 $\frac{1}{4}$ " x $2\frac{1}{2}$ " centers
- Size 29 $\frac{1}{8}$ " x 12 $\frac{1}{2}$ " x 8"
- Shpg 33 lbs.

w/Pull Brake Lever

ITEM 13-1621 \$285.70

w/Pull Brake Lever/Axle Forward

ITEM 13-1622 \$287.50

Hydrogear Hydrostatic Transaxle

ITEM 13-1632

\$349.95

• New HYDRO-GEAR model T2. Hydrostatic transaxle. Part #T2-BDBE-1X2B-18X1. Vertical input for belt drive. External disc brake. Bypass lever allows vehicle to be moved without power. Recommended engine size 19 HP.

SPECIFICATIONS

- Husqvarna Part 587392201
- Input speed 3600 RPM 1800 RPM min (loaded)
- Max speed 5.5 mph
- Pump/Motor Displacement 8/10 cc
- Gear Ratio 27.5:1
- Axle Torque 230 lb.ft. Continuous 445 lb.ft. Intermittent
- Max axle wt. 540 lbs.
- Input Direction CW
- Pulley 4" dia.
- Axles 1" diam. x 5" w/ keyway and snap ring groove
- Max Tire Size 23" dia.
- Recommended Oil 5W-50 Synthetic
- Two four-bolt mounts Inner mntg. centers: 13 $\frac{1}{4}$ " x 13 $\frac{3}{4}$ " Outer mntg. centers: 2 $\frac{1}{2}$ " x 16 $\frac{1}{4}$ "
- Overall Size 29 $\frac{1}{4}$ " x 15" x 10"
- Actual wt. 42 lbs.
- Shpg. 60 lbs.



Right Angle Gearboxes

• Brand new. Right angle gearboxes. One piece cast iron gear case and bearing caps. Roller bearings. Ships without oil, user must add $\frac{1}{8}$ quart of 80-90 W oil prior to use.

SPECIFICATIONS FOR ALL

- Ratio 1:1
- Input Power: 40 HP intermittent 32 HP continuous
- Input Speed 1800 RPM max.

- Size 5 $\frac{7}{8}$ " x 6 $\frac{1}{4}$ " x 4 $\frac{1}{8}$ "
- Output Shaft: 1" diam. x 2 $\frac{1}{4}$ " w/ $\frac{1}{4}$ " keyway
- Mount: Four $\frac{3}{8}$ "-16 tapped holes on 4 $\frac{1}{4}$ " square centers
- Shpg. 23 lbs.

ITEM	Input Shaft	Output rotation	Price
13-1423-K	1" diam. x 2 $\frac{1}{2}$ " w/ $\frac{1}{4}$ " keyway	Opposite of input	\$211.32
13-1423-SK	1" diam. x 2 $\frac{1}{2}$ " w/ $\frac{1}{4}$ " keyway	Same as input	\$211.32
13-1423-3K	1" diam. x 2 $\frac{1}{2}$ " w/ $\frac{1}{4}$ " keyway	Dual Shaft	\$251.75
13-1423-3KC	1" diam. x 2 $\frac{1}{2}$ " w/ $\frac{5}{16}$ " crosshole and $\frac{1}{4}$ " keyway	Dual Shaft	\$251.75

Peerless Differential Axle

ITEM 13-1618

$\frac{3}{4}$ " Diameter

• Brand new. PEERLESS differential. Can be used with PEERLESS 700 series transmission, a gas engine, or electric motor (sold separately) for residential or commercial use. Axle is not heat treated. Used with related PEERLESS drive sprockets (sold separately).

SPECIFICATIONS

- Model 100-007B
- Axles $\frac{3}{4}$ " dia. x 16" smooth shaft
- Tire Diameter 18" max
- Output Torque 150 ft-lb max
- Load Rating 400 lb max
- Size 39 $\frac{3}{8}$ " x 3 $\frac{3}{8}$ " x 3 $\frac{3}{8}$ "
- Shpg 11 lbs.

Stewart Differential Axles

• New, STEWART MANUFACTURING. Differential assembly with disc brake. Die cast aluminum differential case and 1215 cold drawn steel axle shaft with black oxide coating applied to axle shafts. 1" Diameter.

SPECIFICATIONS FOR BOTH

- Axle Dia. 1"
- Axle Threads 1"-14 TPI x 1" 8.875" dia. x 0.179"
- Sprocket 28 tooth 081 Pitch
- Disc Brake Dimensions

ITEM 13-1639 \$39.95

35" Model# 50-000059

SPECIFICATIONS

- Axle Lengths 14 $\frac{3}{4}$ ", 13 $\frac{3}{4}$ "
- Size 35" x 8 $\frac{3}{4}$ " x 8 $\frac{3}{4}$ "
- Shpg. 26 lbs.

ITEM 13-1640 \$49.95

48" Model# 50-000121

SPECIFICATIONS

- Axle Lengths 20", 20 $\frac{3}{4}$ "
- Size 48" x 8 $\frac{3}{4}$ " x 8 $\frac{3}{4}$ "
- Shpg. 20 lbs.

Peerless Differential Sprockets

• Brand new. PEERLESS sprocket for differential

SPECIFICATIONS

- Bolt Holes Four 0.35" dia.
- Bolt Hole Pattern 0.941" x 2.81"

ITEM	Pitch	Bore	Teeth	O.D.	Shpg.	Price
13-1623-35-36	35	2 $\frac{1}{8}$ "	36	4.51"	$\frac{1}{2}$	\$56.75
13-1623-40-45	40	2 $\frac{1}{8}$ "	45	7.45"	2 $\frac{1}{2}$	\$88.55
13-1623-41-40	41	2 $\frac{1}{8}$ "	40	6.81"	2	\$44.00
13-1623-41-48	41	2 $\frac{1}{8}$ "	48	7.93"	2	\$62.50
13-1623-41-60	41	2 $\frac{1}{8}$ "	60	9.84"	5	\$68.95

Aluminum High Speed Gearboxes

ITEM 13-1616-A

\$158.95

• Brand new. PEERLESS 1000-014-D gearbox. Cast aluminum gearbox and ships with oil. Shafts rotate in same direction when viewed from end.

SPECIFICATIONS FOR ALL

- Ratio 1:1
- Input Power: 10 HP continuous
- Input Speed: 3600 RPM max.
- Output Torque 360 in-lbs.
- Size 5 $\frac{1}{2}$ " x 4 $\frac{3}{4}$ " x 7"
- Input Shaft: $\frac{7}{8}$ " dia. x $1\frac{1}{2}$ " w/ $\frac{3}{16}$ " woodruff keyway
- Output Shaft: $\frac{7}{8}$ " dia. x $1\frac{1}{4}$ " w/ $\frac{5}{32}$ " woodruff keyway and $\frac{5}{16}$ "-24 tapped end
- Mount: Two 1 $\frac{3}{32}$ " bolt holes on 4" centers, 2.92" dia. pilot
- Shpg. 8 lbs.

ITEM 13-1616-B \$157.55

• PEERLESS 1000-015 gearbox. Shafts rotate in opposite directions when viewed from end. Shpg. 8 lbs.

3 Shaft Gearbox

ITEM 13-1616-C

\$157.75

• Brand new. PEERLESS 1000-007 gearbox. Solid output shaft extends from both sides of case. Shpg. 9 lbs.

Right Angle Gearbox

ITEM 13-1423-SK-G

\$149.95

• New. Right angle gearbox. One piece cast iron gear case and bearing caps. Roller bearings. Shafts rotate in same direction when viewed from end. Ships without oil, user must add $\frac{1}{8}$ quart of 80-90 W oil prior to use.

SPECIFICATIONS

- Ratio 1:1
- Input Power: 40 HP intermittent 32 HP continuous
- Size 5 $\frac{7}{8}$ " x 6 $\frac{1}{4}$ " x 4 $\frac{1}{8}$ "
- Input Shaft: 1" diam. x 2 $\frac{1}{2}$ " w/ $\frac{5}{16}$ " crosshole and $\frac{1}{4}$ " keyway
- Output Shaft: 1" diam. x 2 $\frac{1}{4}$ " w/ $\frac{5}{16}$ " crosshole and $\frac{1}{4}$ " keyway
- Input Speed 1800 RPM max.
- Mount: Four mounting holes tapped $\frac{3}{8}$ "-16 on 4 $\frac{1}{4}$ " square centers
- Shpg. 23 lbs.

ITEM 13-1423-S-G

\$149.95

• Same except Input Shaft is 1" diam. x 2 $\frac{1}{2}$ " w/ $\frac{5}{16}$ " w/crosshole and output shaft is 1" diam. x 2 $\frac{1}{4}$ " w/keyway.