

General Purpose Motors

• Brand new WORLDWIDE ELECTRIC general purpose motors. Ideal for use in blowers, pumps, conveyors, and many other diverse applications.

SPECIFICATIONS

- 208-230/460 Volt
- Reversible Rotation
- Enclosure TEFC
- 56 Frame
- 3-Phase
- IP43 Protection
- 5/8" Diameter keyed shaft
- Service Factor 1.15
- Continuous Duty



10-3416

Rigid Base					
ITEM	Model	HP	Amps	Shpg	Price
10-3416	NAT12-18-56	1/2	1.9/0.95	24 lbs.	\$198.00
10-3423	NAT34-18-56	3/4	2.6/1.3	27 lbs.	\$211.90
10-3432	NATE1-18-56	1	3.22/1.61	41 lbs.	\$262.50
10-3427	NATE1.5-18-56	1 1/2	4.52/2.26	48 lbs.	\$309.90
10-3437	NATE2-18-56	2	5.92/2.96	53 lbs.	\$369.25



10-3420



10-3422



10-3442

C-Face Removable Base 1800 RPM					
ITEM	Model	HP	Amps	Shpg	Price
10-3420	NAT13-18-56CB	1/3	1.4/0.72	22 lbs.	\$191.55
10-3417	NAT12-18-56CB	1/2	1.9/0.95	24 lbs.	\$203.40
10-3424	NAT34-18-56CB	3/4	2.6/1.3	27 lbs.	\$220.60
10-3433	NATE1-18-56CB	1	3.22/1.61	41 lbs.	\$289.55
10-3428	NATE1.5-18-56CB	1 1/2	4.52/2.26	48 lbs.	\$367.00
10-3438	NATE2-18-56CB	2	5.92/2.96	54 lbs.	\$409.05

C-Face Removable Base 3600 RPM					
ITEM	Model	HP	Amps	Shpg.	Price
10-3422	NAT13-36-56CB	1/3	1.3/0.65	24 lbs.	\$175.95
10-3419	NAT12-36-56CB	1/2	1.7/0.85	23 lbs.	\$183.65
10-3426	NAT34-36-56CB	3/4	2.4/1.2	27 lbs.	\$191.25
10-3435	NATE1-36-56CB	1	3.0/1.5	29 lbs.	\$267.25
10-3430	NATE1.5-36-56CB	1 1/2	3.96/1.98	36 lbs.	\$302.60
10-3440	NATE2-36-56CB	2	5.22/2.61	39 lbs.	\$334.40
10-3442	NATE3-36-56CB	3	7.38/3.69	45 lbs.	\$386.85



10-3421



10-3439



10-3436

C-Face Round Body 1800 RPM					
ITEM	Model	HP	Amps	Shpg	Price
10-3421	NAT13-18-56CRD	1/3	1.4/0.72	22 lbs.	\$191.55
10-3418	NAT12-18-56CRD	1/2	1.9/0.95	23 lbs.	\$203.40
10-3425	NAT34-18-56CRD	3/4	2.6/1.3	26 lbs.	\$220.60
10-3434	NATE1-18-56CRD	1	3.22/1.61	40 lbs.	\$289.55
10-3429	NATE1.5-18-56CRD	1 1/2	4.52/2.26	47 lbs.	\$367.00
10-3439	NATE2-18-56CRD	2	5.92/2.96	52 lbs.	\$409.05

C-Face Round Body 3600 RPM					
ITEM	Model	HP	Amps	Shpg.	Price
10-3436	NATE1-36-56CRD	1	3.0/1.5	27 lbs.	\$267.25
10-3431	NATE1.5-36-56CRD	1 1/2	3.96/1.98	33 lbs.	\$302.60
10-3441	NATE2-36-56CRD	2	5.22/2.61	38 lbs.	\$334.40
10-3443	NATE3-36-56CRD	3	7.38/3.69	44 lbs.	\$386.85

1 HP 1760 RPM 3PH Motor ITEM 10-3380 \$499.95



• Brand new, LEESON model# 121179.00 3-Phase general purpose motor. Rolled steel frame.

SPECIFICATIONS

- Power 1 HP
- Voltage 230/460 Volt AC
- Phase 3
- Frequency 60 Hz
- Amperage 3.2/1.6 Amps
- Speed 1760 RPM
- Rotation Reversible
- Service Factor 1.15
- Bearings Ball
- Thermal Overload Protection None
- Enclosure TEFC
- Duty Continuous
- Frame 143TC
- Base Mount Six 0.88" x 0.34" elliptical slots on 5.50" x 3" and 5" centers
- Face Mount Four 5/8"-16 threaded holes in motor face on 5/8" B.C., 4 1/2" pilot
- Shaft 7/8" dia. x 2.13" overall length w/ 3/4" wide x 1 1/8" long keyway
- Size 10.16" x 8.64" x 7.32"
- Shpg. 35 lbs.

3 HP 3600 RPM 3PH Motor ITEM 10-3377 \$179.95



• New, WEG 00336ES3ESA80SL saw arbor motor. Compact motor with cast iron frame that ensures high outputs with smaller frame. It was especially designed for application on circular saws, miter saws, metal cutoff saws, routers, disc sanders, and wood milling machines.

SPECIFICATIONS

- Power 3 HP
- Voltage 208-230/460 VAC
- Phase 3 Ph
- Frequency 60 Hz
- Amperage 9.49-8.58/4.29 Amps
- Speed 3500 RPM
- Rotation CW
- Service Factor 1.00
- Bearings Ball
- Enclosure TEFC
- Thermal Overload Protection None
- Duty S6
- Frame 80S
- Base Mount Four 0.58" holes on 10 1/2" x 7 1/2" centers
- Shaft M30 x 3.5 (left)
- Arbor Dimensions 120mm dia. x 32.5mm
- Size 18 1/2" x 10 1/2" x 6 1/2"
- Shpg. 132 lbs.

20 HP 1775 RPM 3PH Motor ITEM 10-3373 \$599.95



• New, HYUNDAI Crown Triton™ model HLS256SR2388 three phase premium efficient motor. Ideal for use in many industrial applications including marine use. Designed and field tested for use in some of the harshest industrial environments. Motor is fully compliant to IEEE-841(2009) standard for use as a chemical and process motor.

SPECIFICATIONS

- Power 20 HP
- Voltage 460 AC
- Phase 3
- Frequency 60 Hz
- Amperage 24.8 Amps
- Speed 1775 RPM
- Rotation Reversible
- Service Factor 1.15
- Inverter Rating 10:1 CT / 1000:1 VT
- Bearings 6309ZC
- Size 20 3/4" x 17" x 15"
- Bearing Seal ProTech IP66 labyrinth on DE and ODE
- Enclosure TEFC
- Degree of Protection IP56
- Duty Continuous
- Frame 256T
- Base Mount: Four bolt holes on 10" x 9 3/4" centers
- Shaft 1 5/8" dia. x 4" length w/ 3/4" keyway
- Shpg. 356 lbs.
- Truck freight only.