

**1/4 HP 3500
RPM Motor
ITEM 10-3357
\$69.95**

New TECO Westinghouse model SPO/22 general purpose electric motor. Capacitor start, capacitor run. Steel housing with cast iron end bells.

SPECIFICATIONS

- Model Number SPO/22
- Power 1/4 HP
- Voltage 115/208-230 AC
- Amperage 2.6/1.45-1.31
- Speed 3500 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball

- Enclosure ODP
- Duty Continuous
- Frame 48
- Rigid Base Mount: Four slotted holes on 4 1/2" x 2 3/4" centers
- Shaft 1/2" diam. x 1 1/2" w/ flat
- Size 9" x 7 1/2" x 7 1/4"
- Shpg. 22 lbs.

**1/2 HP 3450
RPM Motor
ITEM 10-3127
\$49.99**

• New, AO SMITH electric motor.

SPECIFICATIONS

- Model J218-582A-LS
- Power 1/2 HP
- Voltage 115/230 VAC
- Phase 1
- Frequency 60 Hz
- Amperage 11.5/5.75 Amps
- Speed 3450 RPM
- Rotation CCW
- Service Factor 1.3
- Bearings Ball

- Thermal Overload Protection Automatic
- Enclosure ODP
- Duty Continuous
- Face Mount Four 3/8" threaded holes in motor face on 7 1/8" B.C.
- Shaft 5/8" dia. x 1 1/2" long with 1/2"-20 threaded end
- Size 12" x 6 1/2" x 6 1/2"
- Shpg. 17 lbs.

**1/2 HP 3450
RPM Motor
ITEM 10-3216
\$49.95**

• New, pool pump motor. Ideal replacement motor for pool pumps. Square flange 4 bolt pump mount on 7 1/8" bolt circle. Stainless steel shaft 5/8" diameter with 1/2"-20 UNF-2A RH threaded end. Thermally protected.

SPECIFICATIONS

- Power 1/2 HP
- Voltage 208-230/460 AC
- Amps 3/1.5
- RPM 3450
- Rotation CCW
- Phase 3
- Service Factor 1.9

- Enclosure TEFC
- Duty continuous
- Frame 56Z
- Shaft 5/8" diameter with 1/2"-20 UNF-2A threaded end
- Size 10 1/2" x 6 1/2" x 8 1/2"
- Shpg 18 lbs.

**1/2 HP 1725
RPM Motor
ITEM 10-3469
\$59.95**

New, Century motor. Thermal overload protection with manual reset.

SPECIFICATIONS

- Model Number S56AA22C28
- Power 1/2 HP
- Voltage 115/230 AC
- Phase 1
- Frequency 60 Hz
- Amperage 7.6/3.8 Amps
- Speed 1725/1425 RPM
- Rotation Reversible
- Service Factor 1.00
- Bearings Ball
- Enclosure ODP

- Thermal Overload Protection Manual
- Duty Continuous
- Frame 56
- Base Mount Eight 1 1/4" x 5/16" elliptical slots on 1 7/8", 3", 4 1/8" x 5" centers
- Face Mount Four 3/8"-16 threaded holes in motor face on 5 7/8" B.C., 4 1/2" pilot
- Shaft 5/8" dia. x 2 1/4" overall length w/ flat
- Size 11 1/8" x 6 1/2" x 6 3/4"
- Shpg. 27 lbs.

**3/4 HP 3450
RPM Motor
ITEM 10-3120
\$59.95**

• New, BLUFFTON MOTOR WORKS model B1244 pool pump motor. Smooth portion of shaft measures 1 9/16" from the bearing overall length 2 1/16". Automatic thermal overload protection.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 AC
- Amperage 12.8/6.4 Amps
- Speed 3450 RPM
- Rotation CCW
- Phase 1
- Service Factor 1.27
- Bearings Ball

- Enclosure ODP
- Duty Continuous
- Frame 56Y
- Mount Square flange 4 bolt on 7 1/8" diam. B.C.
- Shaft 5/8" diam. x 2 1/16" w/ 1/2"-20 RH threaded end
- Size 10 7/8" x 6 5/8" x 6 5/8"
- Shpg. 24 lbs.

**3/4 HP 3600
RPM Motor
ITEM 10-3126
\$39.95**

• New, AO Smith model# J218-1006.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 VAC
- Phase 1
- Frequency 60 Hz
- Amperage 12.5/3 Amps
- Speed 3600 RPM
- Rotation CCW
- Bearings Ball
- Enclosure ODP

- Thermal Overload Protection Automatic
- Duty Continuous
- Face Mount Four 3/8" threaded holes in motor face on 7 1/8" B.C.
- Shaft 12mm dia. tapered x 3/4" long with M10-1.0 threaded end
- Size 12" x 8" x 8"
- Shpg. 23 lbs.

**3/4 HP 3600
RPM Motor
ITEM 10-3128
\$49.99**

• New, AO SMITH model# J218-590B.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 VAC
- Phase 1
- Frequency 60 Hz
- Amperage 11.5/5.75 Amps
- Speed 3600 RPM
- Rotation CCW
- Service Factor 1.25
- Bearings Ball

- Thermal Overload Protection Automatic
- Enclosure ODP
- Duty Continuous
- Face Mount Four 3/8" threaded holes in motor face on 7 1/8" B.C.
- Shaft 5/8" dia. x 1 1/2" long with 1/2"-20 threaded end
- Size 10 1/2" x 6 1/2" x 6 1/2"
- Shpg. 22 lbs.

**3/4 HP 1725
RPM Motor
ITEM 10-3400
\$139.95**

• New, CENTURY electric motor. Manual thermal overload protection

SPECIFICATIONS

- Model 7-196325-21
- Power 3/4 HP
- Voltage 115/208-230 AC
- Phase 1
- Frequency 60/50 Hz
- Amperage 10.6/5.2-5.3 Amps
- Speed 1725/1425 RPM
- Rotation Reversible
- Service Factor 1.25
- Bearings Ball
- Enclosure ODP

- Thermal Overload Protection Manual
- Duty Continuous
- Frame K56C
- Base Mount Four slots on 4" to 5 3/4" x 3" centers
- Face Mount Four 3/8"-16 threaded holes on 5 7/8" B.C. w/ 4 1/2" pilot
- Shaft 5/8" dia. x 1 7/8" overall length w/ 3/16" wide x 1 1/2" long keyway
- Size 11 1/2" x 6 1/2" x 9"
- Shpg. 31 lbs.

**3/4 HP 1725
RPM Motor
ITEM 10-3470
\$69.95**

New, Century motor. Thermal overload protection with manual reset.

SPECIFICATIONS

- Model Number S56AA23C8
- Power 3/4 HP
- Voltage 115/230 AC
- Phase 1
- Frequency 60 Hz
- Amperage 10.4/5.2 Amps
- Speed 1725/1425 RPM
- Rotation Reversible
- Service Factor 1.00
- Bearings Ball
- Enclosure ODP

- Thermal Overload Protection Manual
- Duty Continuous
- Frame 56
- Base Mount Eight 1 1/4" x 5/16" elliptical slots on 1 7/8", 3", 4 1/8" x 5" centers
- Face Mount Four 3/8"-16 threaded holes in motor face on 5 7/8" B.C., 4 1/2" pilot
- Shaft 5/8" dia. x 2 3/8" overall length w/ flat
- Size 12 1/8" x 6 1/2" x 6 3/4"
- Shpg. 30 lbs.

**1 HP 1725
RPM Motor
ITEM 10-3402
\$149.95**

• New, CENTURY capacitor-start motor. Thermal overload protection with manual reset. Rigid Base and C-face mount.

SPECIFICATIONS

- Model C56AA79C28-03
- Power 1.0 HP
- Voltage 208-230/115 AC
- Phase 1
- Frequency 60/50 Hz
- Amperage 6.5-6.3/12.6 Amps
- Speed 1725/1425 RPM
- Rotation Reversible

- Service Factor 1.25
- Thermal Overload Protection Manual
- Enclosure ODP
- Duty Continuous
- Frame L56C
- Shaft 5/8" dia. x 2 3/4" w/ flat
- Size 10 1/4" x 7 1/2" x 8 3/4"
- Shpg. 37 lbs.

**1 HP 1800
RPM Motor
ITEM 10-3387
\$159.95**

• New, CENTURY model #C530 electric motor. Rigid base mount.

SPECIFICATIONS

- Power 1 HP
- Voltage 208-230/115 AC
- Phase 1
- Frequency 60 Hz
- Amperage 7.2-6.5/13.6 Amps
- Speed 1725 RPM
- Rotation Reversible

- Service Factor 1.25
- Bearings Ball
- Thermal Overload None
- Enclosure ODP
- Duty Continuous
- Frame L56C
- Size 10 1/4" x 6 1/2" x 8 5/8"
- Shpg. 35 lbs.

**2 HP 1725
RPM Motor
ITEM 10-3473
\$249.95**

• New, BALDOR RELIANCE model# 36F283-379 capacitor-start, capacitor-run motor. Thermal overload protection with manual reset. ON/OFF switch mounted on the electrical box.

SPECIFICATIONS

- Power 2 HP
- Voltage 115/230 Volts AC
- Phase 1
- Frequency 60 Hz
- Amperage 24/12 Amps
- Speed 1725 RPM
- Rotation CW
- Service Factor 1.15
- Bearings Ball

- Thermal Overload Protection Manual
- Enclosure Open
- Duty Continuous
- Frame 184
- Base Mount:
- Shaft 7/8" dia. x 2 1/4" w/ 3/16" keyway
- Size 14" x 10 1/2" x 11"
- Shpg. 72 lbs.