

5200 RPM 24 VDC Motor

ITEM 10-2492

\$3.99

• New, GLOBE motors model 397A1073. Permanent magnet design. Bronze sleeve bearings. Speed pickup sensor inside case (no details available).

SPECIFICATIONS

- Power .005 HP
- Voltage 24 DC
- Amperage 0.125 Amps
- Speed 5200 RPM
- Rotation Reversible
- Bearings Sleeve
- Duty Continuous
- Mount Two 6-32 holes 1" c/c
- Shaft 0.156" dia. x 0.25" w/flat
- Size 1.25" dia. x 2.25"
- Shpg. 1 lb.



1/2 HP 2500 RPM 180 Volt DC Electric Motor

ITEM 10-3194

\$49.95

• New, TURDAN model# A1K05J.

SPECIFICATIONS

- Power 1/2 HP
- Voltage 180 Volt DC
- Amperage 2.75 Amps
- Speed 2500 RPM
- Rotation Reversible
- Service Factor 1
- Bearings Ball
- Enclosure TENV
- Duty Continuous
- Frame C71
- Face Mount
- Shaft 5/8" dia. x 2" overall length keyed
- Size 8 3/4" x 6 1/2" x 6 1/2"
- Shpg. 23 lbs.



4000 RPM 12 Volt DC Fan Motor

ITEM 10-2032

\$12.99

• Replacement motor for automotive fan. Model 1632F.

SPECIFICATIONS

- Voltage 12 VDC
- Speed 4000 RPM
- Amperage 2.2 Amps @ no load
- Housing Vented
- Rotation CW
- Shaft 5/16" dia. x 1 1/8" w/flat
- Mount 3 holes on 6" B.C.
- Overall size 6 1/4" dia. x 4 1/4"
- Shpg. 5 lbs.



12 Volt DC Permanent Magnet Motor

ITEM 10-2548

\$14.99

• New, MAMCO Model CP-12-132 permanent magnet motor. Designed to fit into a 4.3" dia. opening with O-ring groove in edge of front mounting flange. Shaft is partially recessed in flange, extends 5/8" from face.

SPECIFICATIONS

- Voltage 12 DC
- Amperage 2.5 (no load)
- Speed 4400 RPM (no load)
- Torque 45 in.oz. at 3600 RPM 15 amps
- Rotation reversible
- Bearings bronze sleeve
- Enclosure TENV
- Duty continuous
- Shaft 5/16" dia. x 1" w/threaded end
- Size 4.33" dia. x 4 3/4"
- Shpg. 5 lbs.



12 VDC Blower Motor

ITEM 10-3471

\$24.95

• New, RED DOT CORP RD-5-5121-0 73R4252 single speed dual shaft permanent magnet motor.

SPECIFICATIONS

- Brand Red Dot Corp
- Model Number RD-5-5121-0 73R4252
- RPM 2000 at no load
- Voltage 12 Volts DC
- Rotation Reversible
- Dual Shafts 5/16" dia. x 3 3/8" w/ Flat
- Size 12" x 3" x 3"
- Shpg 4.6 lbs.



14000 RPM 6 Volt DC PM Motor

ITEM 10-3102

\$3.99

• New, permanent magnet motor. Shaft has 0.38" dia. 12 tooth gear on it.

SPECIFICATIONS

- Voltage 6 DC
- Amperage 0.3 amps (no load)
- Speed 14000 RPM
- Rotation Reversible
- Enclosure Open
- Duty Intermittant
- Mount Two tapped holes on face
- Shaft 0.09 dia. x 0.425
- Size 1 1/8" dia. x 2"
- Shpg. 1/2 lb.



6000 RPM, 12 VDC

ITEM 10-2631

\$7.99

• New, permanent magnet motor. Built for use in battery powered weed trimmers. Could also be used as small DC generator.

SPECIFICATIONS

- Voltage 12 DC
- Amperage 1 Amp (no load)
- Speed 6000 RPM
- Rotation reversible
- Bearings bronze bushings
- Enclosure TENV
- Duty intermittent
- Mnt. 2 studs rear 2 1/4" c/c
- Shaft 1/4" dia. x 1" w/flat
- Size 3.15" dia. x 1 3/4"
- Shpg. 3 lbs.



3200 RPM, 12 VDC Motor

ITEM 10-2606

\$2.99

• New, DAEWOO permanent magnet motor. Originally for automotive power seat drive. Accepts 3mm square flex drive cable into each end. Packard 12064750 terminal (5/16" push-on spades).

SPECIFICATIONS

- Voltage 12 DC
- Amperage 1.1 Amps
- Speed 3200 RPM
- Rotation reversible
- Enclosure TENV
- Duty intermittent
- Mount 2 screws each end
- Shaft female 3mm socket at each end
- Size 2" dia. x 4 5/8"
- Shpg. 2 lbs.



12 Volt DC Fan Motor

ITEM 10-3476

\$19.95

• New, BERGSTROM 2809-550-094R blower motor. Used in Kenworth and Peterbilt cab blowers.

SPECIFICATIONS

- Brand Bergstrom
- Model 2809-550-094R
- Part Number 203364
- Voltage 12 VOLT DC
- Rotation CW
- Wire Type 2 wire harness
- Mount Three 0.297" holes
- Shaft 5/16" dia. x 1 1/4" length w/ flat
- Size 6 1/4" x 6 1/4" x 6 1/4"
- Shpg. 5 lbs.



DC Motor Grab Bag



ITEM 10-2023

\$24.95

• 5 assorted new wound field direct current motors made for automotive fans. Most operate on 12 VDC, some were made to operate on 24 VDC but can run on 12 VDC. Photo shows five motors pulled at random and is intended to give a general representation only. Shpg. 20 lbs.

SPECIFICATIONS

- Voltage 12 DC
- Amps: 1.73, no load
- 90 ohm resistance
- 3600 RPM
- Rotation reversible
- Mount: 6 7/8" B.C.
- Shaft: 5/16" x 1 1/8" w/flat
- Motor Size 3" diam. x 5"
- Size w/mnt.: 7 3/4" dia. x 5"

3400 RPM 12 Volt DC Motor

ITEM 10-PM3727

\$12.95

• New, direct current Siemens fan motor. Originally made for automotive industry

SPECIFICATIONS

- Siemens Part #: PM3727X
- Voltage: 12VDC
- 3400 RPM @ no load
- 1 Amp @ no load
- Motor Type: flange mount, vented
- Rotation: CCW
- Shaft dia. x length: 6.8mm x 2 1/16"
- Mount: 3 bolt flange
- Overall size dia. 3" x 3 13/16"
- Shpg. 3 lbs.



1/4 HP 1500 RPM 24 VDC Motor

ITEM 10-3403

\$129.95

• New, 24 VDC 1500 RPM motor, model number 730203.

SPECIFICATIONS

- Power 1/4 HP
- Voltage 24 DC
- Amperage 13.5 Amps
- Speed 1500 RPM
- Rotation Reversible
- Thermal Overload Protection none
- Duty S2 60 minutes
- Face Mount Four M6-1.0 threaded holes in motor face on 3 3/8" B.C., 2 3/4" pilot
- Shaft 14mm dia. x 7/8" overall length w/ 5mm wide x 3/4" long keyway
- Size 7 1/2" x 5" x 4 1/2"
- Shpg. 14 lbs.



1/10 HP 4150 RPM 12 Volt DC Motor

ITEM 10-3390

\$24.95

• New, PROTECH model 1-030-015 permanent magnet motor. Heavy duty leads with connectors.

SPECIFICATIONS

- Voltage 12 DC
- Amperage 12 Amps
- Power 0.13 HP
- Torque 13 oz.in.
- Speed 4150 RPM
- Rotation Reversible
- Enclosure TENV
- Duty Intermittent
- Face Mount 3 tapped #10-32 holes on 2 9/16" dia. B.C. w/ 1.146" dia. pilot
- Shaft 3/8" dia. x 3" w/flat
- Size 4 5/8" x 3" x 3"
- Shpg. 5 lbs.

