



Motorized Impellers

• New. Backward curved motorized impeller. Use for cabinet cooling, air filtration systems. Air is discharged in 360° pattern around impellor. Narrow profile and vertical or horizontal mount to save space. Quiet operation with high airflow. Mounting flange four tapped holes on motor. Requires run capacitor, not included.



16-1475
Plastic



16-1478
Steel



16-1480
Steel

ITEM	Mfg.	Model	CFM	Voltage	Amps	RPM	Inlet	Capacitor Construction	Required	Size	Shpg.	Price
16-1475	Fans-Tech	FH133	115	230 VAC	0.14	3100	3 3/4"	Plastic	1 MFD 450 VAC	5 1/4" dia. x 3 3/4"	4 lbs.	\$9.99
16-1566	Fans-Tech	FH133L0000	120	230 VAC	0.14	3100	3 1 1/16"	Plastic	1 MFD 450 VAC	5 1/4" dia. x 3 13/16"	4 lbs.	\$9.99
16-1477	Fans-Tech	FH175	235	230 VAC	0.21	2800	5"	Plastic	1.5 MFD 450 VAC	7" dia. x 2 1/2"	4 lbs.	\$14.99
16-1468	Fans-Tech	FH175	235	115 VAC	0.4	2800	5"	Plastic	4MFD 250 VAC	7" dia. x 2 1/2"	4 lbs.	\$14.99
16-1478	EBM-Papst	R2E175	280	230 VAC	0.35	2300	5"	Steel	1.5 MFD 400 VAC	6 3/4" dia. x 2 1/4"	5 lbs.	\$14.99
16-1480	Fans-Tech	FH320	1175	230 VAC	0.75	1580	8 1/2"	Steel	4 MFD 450 VAC	12 1/2" dia. x 6"	14 lbs.	\$24.99

115 Volt AC Draft Inducer Blower

ITEM 16-1562
\$89.95



• New, JAKEL 119278-00 part # J238-15240 draft inducer blower. Shaded pole motor with cooling fan. Metal housing and blower wheel. Attaches to side of furnace. Hose barb for 3/16" ID pressure sense tube.

SPECIFICATIONS

- Voltage 115 AC
- Amperage 2.1
- Speed 3000 RPM
- Duty Continuous
- Size 8 1/2" x 6 1/4" x 8"
- Mount 5 hole flange w/ spun fiberglass gasket
- Inlet 6 1/2" dia.
- Outlet 1 5/8" x 2 5/8"
- Shpg. 6 lbs.

160 CFM 115 Volt AC Dual Blower

ITEM 16-1549
\$18.95



• New, AIR-DEC model 60992656 centrifugal double blower. Ideal for use on corn or wood stoves and other general purpose air movement. Metal housing and plastic blower wheels. Mounting tabs on bottom and front. Shaded pole motor.

SPECIFICATIONS

- Flow 215 CFM max.
- Voltage 115 AC
- Amperage 1.2
- Speed 3000 RPM
- Duty Continuous
- Blower Wheels 3" dia. x 3 3/4"
- Mount 6 hole base
- Inlets 3 1/4" dia.
- Outlets 4 3/4" x 1"
- Mounts Front 13 1/2" c/c, Base 2" x 3 5/8"
- Size 4 1/2" x 14" x 4"
- Shpg. 7 lbs.

13" 473 CFM 115 Volt AC Filter Fan

ITEM 16-1546-13-K **\$79.95**



• New, PENTAIR fresh air enclosure filter fan. High airflow and low noise for cooling electrical equipment or general air circulation. Gray plastic grill. Air is pulled through the plastic grill and filter. Plastic housing with metal blades. Click-fit design installs into enclosure wall. Snap over grill with foam filter. 70db rating. Terminal block electrical connection.

SPECIFICATIONS

- Pull Type Fan
- Model Number ST1316424
- Flow 473 CFM max.
- Voltage 115 AC
- Amperage 1.47 Amps
- Power 175 Watts
- Speed 2650 RPM
- IP Rating 54
- Size 12 3/4" x 12 3/4" x 6 3/4"
- Operating Temperature Range Min. 14° F to Max. 131° F
- Mount 8 holes on 5 15/16" to 11 7/8" x 5 15/16" to 11 7/8" centers
- Cutout Dimensions 11.5" x 11.5"
- Blade Dia. 9 7/8"
- Number of Blades 7
- Shpg. 11 lbs.



16-1439



16-1440



16-1367



16-1365



16-1366

• 120 Volt AC Axial Fans • ⚠

• Brand new, Thermocool, 5 blade axial fan. High airflow and low noise for cooling electrical equipment or general air circulation. Metal housing with plastic blades.

ITEM	CFM	Model	DB Rating	Watts	RPM	Mount	Bearings	Size	Shpg.	Price
16-1554	23	G8025HAS	27	12	2300	2.81" square	Sleeve	3.15" x 3.15" x 0.98"	1 lb.	\$10.50
16-1555	34	G9225HAS	34	12	2300	3.18" square	Sleeve	3.62" x 3.62" x 0.98"	1 lb.	\$10.25
16-1439	85	G12038MAS	44	25	2600	4.12" square	Sleeve	4.75" x 4.75" x 1.5"	2 lbs.	\$11.35
16-1440	122	G13538HAS	53	25	2600	4.43" square	Sleeve	5.31" x 5.31" x 1.5"	2 lbs.	\$12.35
16-1367	198	G15050HAST	59	38	2900	4.81" square	Sleeve	5.9" x 5.9" x 2"	2 lbs.	\$19.35
16-1365	198	G17050HASB	59	38	2900	4 holes on 6 3/8" b.c.	Ball	6.75" dia. x 2"	2 lbs.	\$18.40
16-1366	198	G17050	59	38	2900	4 holes on 6 3/8" b.c.	Ball	6.75" x 5.9" x 2"	2 lbs.	\$18.40