

Reversing Drum Switches

 Brand new, drum type reversing switches. Heavy duty copper contacts, painted metal housing. UL and CSA listed. Available for single or three phase operation and momentary or maintained operation. ÜŠÄ

		Horsepower Ratings 1 Phase Volts 3 Phase Volts						
ITEM	Action	115	<i>230</i>	230	460	Size	Shpg	Price
11-3390	Maintained	1.5	2	_	_	2.5" x 4" x 4.5"	2 lbs.	<i>\$80.50</i>
11-3390-M	Momentary	1.5	2	_	_	2-5" x 4" x 4.5"	2 lbs.	<i>\$89.35</i>
11-3391	Maintained	1.5	2	2	1	2.5" x 4" x 4.5"	2 lbs.	<i>\$100.60</i>
11-3391-M	Momentary	1.5	2	2	1	2.5" x 4" x 4.5"	2 lbs.	<i>\$110.45</i>
11-3392	Maintained	2	3	5	7.5	3.5" x 6.2" x 5.6"	4 lbs.	<i>\$226.70</i>



Heavy Duty Foot Switch **∧** w/Guard \$22.50

• Conduit Connection

Nema Enclosure

Type 2, 4, 13

• Shpg. 3 lbs.

Mounting Pattern

Triangular 3%" x 71/4"

1/2" NPT

• Brand new TMAZTZ heavy duty foot Switch. Features include momentary operation with SPDT switch, rugged cast aluminum construction and oversized guard opening.

• Similar to 11-3632 but with 2 pedals.

• Brand new, BUYERS PRODUCTS Part

SW710 reversing switch. Heavy-duty 50

Amp rotary switch controls forward and reverse motion of a 12-volt motor without

requiring a relay. Ideal for use with 12 VDC linear actuators, gearmotors and other permanent magnet motors. Commonly used on 12-volt truck and trailer tarp

systems. Three positions: momentary-ON,

OFF, momentary-ON. Terminal hardware

Each pedal has a N.O./N.C. plunger

switch. Size 81/4" x 9" x 6". Shpg 6 lbs.

SPECIFICATIONS

- Model TFS-502
- · Contact Rating 15A, 125/250 VAC
- · Actuation Force 7 lbs.
- Contacts SPDT
- Switch Action Momentary • Size 81/4" x 53/4" x 5"

Double Pedal

12 VDC Heavy

Duty Reversing

· Finish Powder-painted safety orange

Footswitch

ITEM 11-3633

Switch

ITEM 11-3295

\$18.65

included.

@ 12 VDC

reversing

SPECIFICATIONS

Contacts DPDT-CO

Switch Type Rotary

4 Button **Pendant Control**

ITEM 11-3708 \$29.95

New, MAFELEC pendant switch. Four independent, double pole normally open, momentary pushbutton switches. Rainproof plastic housing with rubber strain relief for cord (cord not included). Dual magnets on back for mounting

SPECIFICATIONS

- Four N.O. switches
- Size 7½" x 2½" x 2¼"
- Contacts rated 5 Amps @ 250 VAC
- Shpg. 1 lb.

SPST Momentary

Push Button

Switch

ITEM 11-3297 **\$9.60**

 Brand new, BUYERS SW901 panel mount momentary push button switch. Moisture repellent insulator.

SPECIFICATIONS

- · Contacts SPST N.O.
- Switch Type Pushbutton
- Termination Screw
- **Terminals**
- Action Momentary

· Switch Positions Two

- Face Size 7/16" diam.
- Mounting Stem 5/8"-32 thread x 3/4
- Mounting Depth 134"
- Shpg. 1/4 lb.

SPST Momentary **Pushbutton** Switch

ITEM 11-3293

mount momentary normally open push button switch. Weather and dust proof housing. Originally intended for vehicle

SPECIFICATIONS

- Action Momentary • Contact Ratings 50 Amps • Switch Positions ON-
 - @ 12 VDC
 - Switch Type Pushbutton
 - Screw Terminals

Action Momentary

- Face Size 15/16" diam.
- Mounting Depth 1¾

Two Button Pendant **Switches**

• Brand new, for Single Acting (power up, gravity down) hydraulc power units.

SPECIFICATIONS

- Pushbuttons (2) Normally
- Cord 18/3, 14 feet long
- Size 2½ x 2½ x 6 ITEM 11-2201

15' cord

\$37.20

ITEM 11-2201-20 20' cord \$37.20 ITEM 11-3709

\$39.05 15' cord



ITEM 11-3735 \$47.25

Switch



Brand new, dual pushbutton handheld remote. Use with power up/power down double acting hydraulic units. (Four wire control with input connecting to both output wires when "up" is pressed and input to only one output wire when "down" is pressed.) Magnetic back cover. • Wires 4 wires w/ ring

SPECIFICATIONS

- Pushbuttons 2 Normally
- terminals • Size 111/4" x 37/8" x 27/8"
- Cord 18/4, 15 feet long

• Shpg. 3 lbs.

ITEM 11-3735-20 • 20 ft. cord

Two Button Pendant Switch

ITEM 11-3244 \$29.95



 Brand new, dual pushbutton handheld remote. Use with power up/power down double acting hydraulic units. (Three wire control with input connecting to both output wires when "up" is pressed and input to only one output wire when "down" is presséd.)

SPECIFICATIONS

- · Pushbuttons 2 Normally
- Contact Rating 5 amp 250 VAC
- Cord 18/3, 10 feet long • Wires 3 wires w/ ring
- terminals • Size 57/8" x 21/2" x 21/8"
- . Shpg. 2 lbs.

12 VDC Rotary Disconnect Switch

ITEM 11-3294 **\$23.30**



15 sec. ON and 5 min. OFF


 Brand new, BUYERS Model SW700 heavy duty master disconnect switch.

SPECIFICATIONS

- Contacts SPST
- · Contact Ratings:
- Terminal Stud Size 3/8" Action Maintained
- 20 Amps @ 12 VDC cont. Mounting Panel 34"-16 125 Amps @ 12 VDC int. • Shpg. 1 lb.

153





- OFF-ON • Face Size 2" dia.
- Mounting 1/2" hole
- Mounting Depth 17/8"
- . Shpg. 2 lbs.







• Brand new, BUYERS BSW90030 panel

- Contacts SPST (normally Switch Positions Two
- Contact Ratings 35 Amps Mounting Stem 5/8"-32 thrd. x 21/32" long

 - Shpg. 1/4 lb.

