\$3.10

\$3.45

\$3.80

\$5.05

Toggle Switches **△**

• Brand new toggle switches. Includes legend plate. Screw terminals. Contact ratings 20 Amps at 125 VAC, 15 Amps at 250 VAC. Shpg. 1/4 lb.

ITEM 11-3217 **SPST Maintained**

ITEM 11-3218 SPDT-CO Maintained

ITEM 11-3456 SPDT-CO Momentary

ITEM 11-3219

DPST Maintained ITEM 11-3220

DPDT-CO Maintained ITEM 11-3259

DPDT-CO Momentary

ITEM 11-3279 \$5.50 DPDT-CO Momentary/Maintained

4PDT-CO Toggle Switch ∧ \$5.95 ITEM 11-3221

· Brand new, maintained toggle switch. Includes legend plate. Screw terminals. Contact ratings 15 Amps at 125 VAC, 10 Amps at 250 VAC. Shpg. ½ lb.

SPNC 16 Amp Paddle Switch ITEM 11-3115

• New, SPNC momentary paddle switch. 16 amps at 125 VAC, 10 amps at 250 VAC, ¾ HP at 125-250 VAC. ¼" spade terminals. **Shpg.** 1/10 **lb**.

4PDT 15 Amp Toggle Switch

ITEM 11-3724

• New, maintained toggle switch. 15 amps at 125 VAC. Mounts in ½" hole, 111/16" deep. Two switch positions. Push on terminals Shpg. 0.15 lb.

DPST 15 Amp Paddle Switch

ITEM 11-3098

\$1.49

• New, DPST maintained paddle switch. Orange paddle is %" wide by %" long. 10 amps at 250 VAC, 15 amps at 125 VAC, 4 HP at 125 VAC. Two hole mount 1%" c/c. 1%" spade terminals. Shpq. 1/10 lb.

SPST Illuminated Green Glow Toggle Switch

\$1.99 ITEM 11-3286-G

New, CALTERM duckbill lever SPST maintained action toggle switch. Contacts 20 Amps at 12 VDC. Switch positions 2 (on-off). 1/4" spade terminals. Mounting 1/2" hole. **Shpg.** 1/10 **lb.**

SPST Toggle Switch

\$3.99 ITEM 11-3452

 New, NAPA chrome maintained ON/OFF switch. Metal construction. Jam nut included. Contact ratings 35 Amps at 12 VDC. Screw terminals. Two switch positions. Mount ½" dia. opening. Shpg. ¼ lb.

DPDT-CO Toggle Switch

ITEM 11-3596 \$2.99 🗪

New, maintained toggle switch. Contact ratings 20 Amps at 125 VAC, 12 Amps at 277 VAC.
switch positions. Solder terminals. Shpg. ¼ lb.

SPST Toggle Switch

\$3.99 ITEM 11-3636

· New, CARLING illuminated rocker switch. Clear paddle. Red lamp illuminates in position 1, amber lamp illuminates in position 2. Contact ratings 15 Amps at 12 VDC. 1/4" spade terminals. Mount 1/2" dia. opening. Shpg. 1/10 lb.

SPST Toggle Switch ITEM 11-3287 \$1.49

 New, CALTERM 40100 black duckbill lever SPST maintained toggle switch. 20 Amps at 12 VDC. Switch positions 2 (on-off). 1/4" spade terminals. Mounting 1/2" hole. Shpg. 1/10 lb.

California

Residents

DPDT-CO Toggle Switch ITEM 11-3261 ▲ \$3.50

 Brand new, maintained toggle switch. Includes legend plate. Screw terminals. Contact ratings 10 Amps at 125 VAC, 6 Amps at 250 VAC. Shpg. 1/4 lb.

SPDT Toggle Switch ITEM 11-3634

• New, FEME model S1S-D maintained toggle switch. Solder terminals. Mounting 12mm, Mountin depth 11/6. Shpg. 1/6 lb.

SPDT Toggle Switch 11-3610 \$2.95

New, CARLING maintained toggle switch. Extra long 1" lever. Spade terminals. Mounts in ½" x 1" opening. Contacts rated 15 amps at 125 VAC, 10 amps at 250 VAC. Shpg. 1/8 lb.

4PST Toggle Switch ITEM 11-3523

\$3,99 New, maintained toggle switch. Screw terminals. Contacts rated 15 amps at 125 VAC, 10 amps at 250 VAC. Mounts in 1/2" hole, 11/4 deep. Two switch positions. Shpg. 1/4 lb.

DPST Toggle Switch \$2.29 🕏 ITEM 11-3611

 New, maintained toggle switch. Includes legend plate. Contact ratings 3 Amps at 125 VAC, Switch positions two. Mounts in ½" hole, %" deep. Shpg. 1/8 lb.

SPDT Toggle Switch **\$2.99** ITEM 11-3522

• New, maintained toggle switch. 1/4" Push-on terminals. Contact ratings 20 amps at 125 VAC, 3/4 HP. Shpq. 1/8 lb.

SPST Toggle Switch

ITEM 11-3694 New, CARLING, maintained toggle switch.

1/4" Spade terminals. Contacts rated 20 amps at 125 VAC, 10 amps at 250 VAC. Shpg. 0.05 lb.

SPDT Toggle Switch

ITEM 11-3726

• New, momentary toggle switch. Screw terminals. Two switch positions (on-on) Contact rated 15 amps at 115 VAC, Mounts in ½" hole, 11/8" deep. Shpq. 0.05 lb.

DPDT Toggle Switch

ITEM 11-3730

 New, momentary toggle switch. w/yellow plastic paddle. Three switch positions (onoff-on) 1/4" Push-on terminals. Contact rated 10 amps at 250 VAC, Mounts in ½" hole, 1" deep. Shpg. 0.1 lb.

SPST Illuminated **Toggle Switch**

New, illuminated lever toggle switch.

SPECIFICATIONS

- · Contacts SPST
- Contact Rating 20 Amps (on-off) @ 12 VDC
- Switch Type Toggle
- Termination 1/4" Spade

ITEM 11-3627 ITEM 11-3625

Blue Glow

- Action Maintained Switch Positions Two
- Mounting ½" hole
- Mounting Depth 1"

• Shpg. 1/10 lb.

Purple Glow

SPST Lighted LED Tip Toggle Switch \Lambda

 Brand new, maintained ON/OFF toggle switch. LED in tip of lever.

ITEM 11-3657-A Amber LED in tip \$4.10 \$4.10 ITEM 11-3657-B Blue LED in tip

ITEM 11-3657-G Green LED in tip ITEM 11-3657-R Red LED in tip

SPECIFICATIONS

- Contacts SPST
- Contact Ratings: 25 Amps @ 12 VDC
- Switch Type Toggle
- Termination 1/4" Spade
- Action Maintained
- Mounting Mounts in 1/2" dia. opening

\$4.10

- Mounting Depth 15/16"
- Shpg. 1/8 lb.

SPST 10 Amp Toggle Switch

w/ Recessed Pan ITEM 11-3298



 Brand new, BUYERS Model SW911 toggle switch recessed in a pan. Recessed pan prevents accidental activation and protects switch from impacts. 20 gauge plated steel pan. Mounts in 2" diameter hole, with 3 holes on 25%" diameter bolt circle.


SPECIFICATIONS

- Contacts SPST
- · Contact Ratings: 10 Amps @ 12 VDC 12 VDC max.
- Switch Type Toggle Spade Terminals
- Face Size 33/16" diameter

Action Maintained

- · Switch Positions Two Mounting Flange
- . Mounting Depth 2"
- Shpg. 1/4 lb.

Rubber Covers For Toggle Switch∧



SPECIFICATIONS

• Size 9/16" dia. x 1"

 Thread size M12 x 0.75 ITEM 11-3250

• Shpg. 1/10 lb. \$1.40 With loop

ITEM 11-3250-A Without loop

Spring-Loaded Switch Covers Your Choice A \$2.15 each

 Brand new. Spring-loaded switch covers for two-position, on-off switches to prevent accidental actuation. For switches with 1/2" dia. stems. Available in 9 colors (see item number suffix).

Shpg. 1/10 lb. each. ITEM 11-3260-BLACK

ITEM 11-3260-BLUE

ITEM 11-3260-CARBON ITEM 11-3260-CLEAR

ITEM 11-3260-GREEN ITEM 11-3260-PURPLE ITEM 11-3260-RED

Ceramic

ITEM 1-3509

New, ceramic (ferrite) ring magnet.

SPECIFICATIONS

- Inside diameter ¾
- Pull approx. 1 lb.
- Outside diameter 1½



