

▲ 10 Gallon 12 Volt DC Portable Tire Blaster Pump

\$189.00 ITEM 1-5014

 Brand new EAGLE Model IHCT10 portable tire blaster. Uses a blast of air to seat tire beads onto rims. 2" NPT ball valve and special adapter nozzle to control air flow into tire. Features include heavy gauge steel construction, shut-off valve, filling valve, pressure gauge, 3 foot hose, tire chuck and built-in cushioned carry handle. Quick coupler end for attachment to compressor airline for filling.

#### **SPECIFICATIONS**

# **Vacuum** ITEM 4-1831 \$18.95

 New MITSUBISHI. Model # G6T50371ZC. Original application was automotive cruise control. Ideal source of vacuum.

#### **SPECIFICATIONS**

- Vacuum 11 In. Hg vacuum Size 5½" x 23%" x 3¾" @ no flow

NN-NNA

Shpg. ¼ İb. ea.

ITEM 455-

• Brand new. Brass (except clamps). Give

full description on order (1/4" Tee = 455-LL).

(AA) Male hose end, 1/4" hose x 1/4" NPT...... \$1.55

(BB) Male hose end, %" hose x 1/4" NPT...... \$1.45

(CC) Female NPT, 1/4" hose x 1/4" NPT...... \$3.40

(EE) Hose mender, 1/4" hose x 1/4" hose ....... \$1.65

(FF) Hose mender, %" hose x %" hose ....... \$1.65

(GA) Reducer, 1/4" NPT x 1/6" NPT...... \$1.70

(HH) Bushing, 1/8" female x 1/4" male NPT...... \$0.90

(II) Bushing, 1/4" female x 3/6" male NPT...... \$1.40 

(PP) Clamp, for standard 1/4" ID hose............ \$0.60

(QQ) Clamp, for standard %" ID hose............ \$0.60

1/4" NPT x 1/4" cu. tubing ...... \$2.15

1/4" NPT x 5/16" cu. tubing ...... \$2.40

1/4" NPT x 3/8" cu. tubing ...... \$2.05

(AAA) Male hose end, 1/8" hose x 1/8" NPT...... \$1.10

(BBB) Female solid NPT, ¼" hose x ¼" NPT... \$2.00 (CCC) Female solid NPT, ¾" hose x ¼" NPT.... \$2.30

(RR) Compression Coupling

(SS) Compression coupling

(TT) Compression coupling

Port Barb for 0.2 ID tubing

- Volts 12 VDC
- Amps 0.35 Amps
- side
- . Mounting 3 holes each
- Shpg. 6 lbs.

## Unloader Valve A ITEM 4-1499 \$46.50

Compressor

 Brand new. Use on compressors driven by continuous power input (gas engines, hydraulic, etc.). Once tank reaches full pressure incoming air from compressor is vented to atmosphere. 1/4" NPT tank connection, 1/4" tubing connection for air line, 1/8" NPT for idle control or head unloader. Toggle lever to override. Size 3" x 31/2" x 11/2". **Shpg. 1 lb.** 

### ¼"NPT Air 🛦 Safety Valve



 Brand new, CONRADER SRV-187 brass air compressor safety relief valve. Factory set, non-adjustable. Pull ring allows manual pressure relief.

#### SPECIFICATIONS FOR ALL

Connection ¼" NPT
Size ¾6" dia. x 1½"
Shpg. ¼ lb.

	Relief	Air	
ITEM	Setting	Flow	Price
4-1927-125	125 PSI	62 CFM	\$4.15
4-1927-150	150 PSI	73 CFM	<i>\$4.15</i>
4-1927-170	170 PSI	82 CFM	\$4.15
4-1927-200	200 PSI	96 CFM	\$4.15

#### 115 Volt AC Air Pump ITEM 4-1951 \$39.95

• New, HAILEA model ACO-009E air pump. Use for large or multiple aquariums. Finned aluminum housing. Linear piston design for long life, low noise and vibration. Oilfree air.

#### **SPECIFICATIONS**

Voltage 115 AC

UU-VV

RR-SS-TT

**Air Fittings** 

- Power Consumption 160 watts
- Flow 5 CFM (145 Liters/ Min.) free flow
- Pressure 5 PSI (0.035 Mpa)
- Noise Level <60 db</li>
- Duty Continuous
- Inlet Port 0.571 OD barb for 13mm tubing
- Outlet Port M12x1.5 metric pipe Inlet Port 0.466 OD barb
- for 10mm tubing Mount Rubber cushion

ÜSÄ

- feet • Size 11¼" 5" x 65%"
- Shpg. 13 lbs.

#### **Quick Change** Air Hose Couplers

- Brand new. Install at one end of hoses to air equipment.
- · Compressor need not be shut off. Swivel action helps prevent hose kinking. Change from one air tool to another in seconds.

#### **Complete Unit** *ITEM 438* \$7.10



· Complete unit (coupler and adapter). Couplers 1/4" female NPT. Adapter 1/4" male NPT. Complete unit  $\frac{3}{4}$  x  $2\frac{1}{2}$ . Shpg. 1 lb.

Male Adapter Only **ITEM 439** \$1.20



• 1/4" male NPT adapter only. Shpq. 1/4 lb. Female Adapter Only **ITEM 440** 

\$1.25 ¼" female NPT adapter only. Shpg. ¼ lb.

- Pressure 150 PSI max. • Tank capacity 10 gallon
- Shpg. 39 lbs. Size 35" x 12½" x 15.8"

## In-tank Check Valves

• Brand new brass construction air check valve. Threads directly into tank port. Allow one way airflow from compressor to tank while preventing air from leaking backward from tank thru compressor. Auxillary port for connection to unloader valve on pressure

#### SPECIFICATIONS FOR ALL A

• 450 PSI max. • Cracking pressure 4 PSI • Unloader port 1/8" NPT • Temp. 400° F

	Tank	Inlet			
ITEM	Port	Port	Size	Shpg.	Price
4-1925-50	1/2" NPT	1/2" NPT	1" hex x 213/16"	1 lb.	<i>\$10.45</i>
4-1925-75	3/4" NPT	3/4" NPT	13/16" hex x 315/16"	1 lb.	<i>\$12.40</i>
4-1925-100	1" NPT	1" NPT	11/2" hex x 315/16"	1½ lbs.	<i>\$22.15</i>
4-1926	1/2" NPT	½" male flare	1" hex x 213/16"	1 lb.	<i>\$7.50</i>

# Air Control Valves

4-1542 & 4-1544

4-1543

· Brand new AIR-MITE. Use for operating single or double acting air cylinders. Anodized aluminum body. Ports 1/4" NPT. Rated 150 PSI. **Shpg. 2 lbs.** 

#### ITEM 4-1542

\$96.00

• Model V-4203. Two position, lever operated. Manual return. Size 5½″ x 2″ x 1¾″.

#### \$129.00 ITEM 4-1544

• Model V-4204-3P. Three position, lever operated. Spring return to center. Size 5½" x 2" x 1%".

#### ITEM 4-1543

\$99.00

 Model V-4208. Two position, foot pedal. Spring return. Size 7" x 2\%" x 1\%".



• Brand new AIR-MITE Model V-4210-3P. Use for operating single or double acting air cylinders. Anodized aluminum body. All ports blocked in spring centered position.


#### **SPECIFICATIONS**

- Treadle style foot pedal Spring centered
- Ports 1/4" NPT • PSI 150 Size 7" x 2%" x 15%"
- Three position · Shpg. 2 lbs.

## 14 NPS x 14 NPS Air Hex Fitting Nipple ITEM 4-1952



- ¼ NPS 30° cone seat x ¼ NPS 30° cone seat
- Shpg. 0.1 lbs.



(FFF) Male hose end, 0.17" hose x 1/4" NPT.... \$3.35 (GGG)45° elbow Male hose end,