

Humphrey Multi-Mount Air Cylinders

• New, HUMPHREY. Multi-mount style air cylinders. Aluminum construction, rated to 100 PSI working pressure. 10-32 ports.

Bore - Rod Dimensions

$\frac{1}{4}" = 0.118"$ $\frac{3}{8}" = 0.197"$ $\frac{5}{8}" = 0.236"$

Single Acting
Push Only



ITEM	Bore	Stroke	R. Lgth.	Shpg.	Price
4-10621	$\frac{1}{4}"$	$\frac{1}{4}"$	2.14"	$\frac{1}{2}$ lb.	\$5.95
4-10622	$\frac{3}{8}"$	$\frac{1}{4}"$	2.337"	$\frac{3}{4}$ lb.	\$5.95
4-10633	$\frac{3}{8}"$	$\frac{1}{2}"$	2.587"	$\frac{3}{4}$ lb.	\$5.95
4-10640	$\frac{5}{8}"$	$\frac{1}{4}"$	2.533"	$\frac{1}{2}$ lb.	\$6.95
4-10647	$\frac{5}{8}"$	$\frac{1}{2}"$	2.783"	$\frac{3}{4}$ lb.	\$6.95

Double Acting

ITEM	Bore	Stroke	R. Lgth.	Shpg.	Price
4-10618	$\frac{1}{4}"$	$\frac{1}{2}"$	2.193"	$\frac{1}{2}$ lb.	\$5.95
4-10613	$\frac{1}{4}"$	$\frac{3}{4}"$	2.443"	$\frac{1}{2}$ lb.	\$5.95
4-10631	$\frac{3}{8}"$	$\frac{3}{4}"$	2.64"	$\frac{1}{2}$ lb.	\$5.95
4-10637	$\frac{5}{8}"$	$\frac{3}{4}"$	2.837"	1 lb.	\$7.99

Double Acting
Double Rod



ITEM	Bore	Stroke	R. Lgth.	Shpg.	Price
4-10627	$\frac{3}{8}"$	$\frac{1}{2}"$	3.4375"	$\frac{1}{4}$ lb.	\$16.95
4-10630	$\frac{3}{8}"$	$\frac{3}{4}"$	3.902"	$\frac{1}{2}$ lb.	\$8.95
4-10649	$\frac{5}{8}"$	$\frac{1}{2}"$	3.677"	$\frac{3}{4}$ lb.	\$9.95
4-10636	$\frac{5}{8}"$	$\frac{3}{4}"$	4.177"	$\frac{3}{4}$ lb.	\$9.95

12 mm x 2 3/4" DA Air Cylinder



ITEM 4-1630

\$5.95

• New, FESTO Model DO-12-74-PP-SA air cylinder. Stainless steel tubing with aluminum end-caps. 10-32 ports with adapters to $\frac{1}{16}"$ hosebarbs. Rod end threaded 4 mm, 0.70" pitch. Base end-cap tapped 4 mm, 0.70" pitch. Cushions at both ends of stroke.

SPECIFICATIONS

- Double Acting
- Bore 12 mm (0.472")
- Stroke 2 3/4"
- Rod dia. 4 mm (0.156")
- Press. 8 Bar (116 PSI) max
- Ports $\frac{1}{16}"$ hosebarbs
- Retracted lgth. 6 3/4" end-to-end
- Shpg. 1 lb.

3/4" Bore Air Cylinder



ITEM 4-1761-A

\$4.95

• Used BIMBA stainless steel. Extend port in base, retract port in rod end. P/N 53E743. Stroke $\frac{3}{4}"$, retracted lgth. 5" (rod end to base end).

SPECIFICATIONS

- Double acting
- Bore $\frac{3}{4}"$
- PSI max. 250
- Rod diam. $\frac{1}{4}"$
- Ports $\frac{1}{8}"$ NPT
- Threaded rod end $\frac{1}{4}"$ -28 x $\frac{1}{2}"$ long
- Nose mount threaded $\frac{5}{8}"$ -18
- Flat base 0.81" O.D.
- Shpg. 1 lb.

Double Acting Pneumatic Cylinders

• New. BUYERS double acting pneumatic cylinder. Has a cushion valve on each end. H Models have hinge mount accessory kit. Ideal for remote tailgate latches.

SPECIFICATIONS

• Double Acting

- Gland Retainer Tie-Rod
- Pressure 200 PSI

- Ports $\frac{1}{4}"$ NPT
- Rod End Clevis w/ Jam Nut

- Base End Clevis
- Pin Holes $\frac{1}{2}"$

ITEM	Bore	Stroke	Rod Dia.	R. Lgth.	Shpg.	Price
4-1968-6	2.5"	6"	0.75"	14.5"	8.5 lbs.	\$91.40
4-1968-8	2.5"	8"	0.75"	16.5"	8.5 lbs.	\$91.80
4-1968-8-H	2.5"	8"	0.75"	16.5"	9.5 lbs.	\$103.25
4-1969-6	3.25"	6"	1"	16.25"	11 lbs.	\$112.35
4-1969-8	3.25"	8"	1"	18.25"	13 lbs.	\$132.45
4-1969-8-H	3.25"	8"	1"	18.25"	14 lbs.	\$150.05



4-1968-6



4-1968-8-H

1/4" NPT Mini Air Regulator w/Gauge

ITEM 4-9094

\$5.95

• New, CAMPBELL HAUSFELD part number RE206901AV. Inline air pressure regulator with gauge.

SPECIFICATIONS

- Inlet Pressure 200 PSI max.
- Outlet Pressure Range 0-135 PSI
- Ports $\frac{1}{4}"$ NPT
- Gauge Port $\frac{1}{8}"$ NPT
- Size 3 5/8" x 1 1/2" x 2 3/4"
- Shpg. $\frac{1}{2}$ lb.



Air Filter Pair

ITEM 4-1930

\$4.95

• New, pair of plastic housing air filters for air compressors. Uses paper element.

SPECIFICATIONS

- $\frac{1}{2}"$ NPT connection
- $\frac{1}{2}"$ inlet tube
- 4" dia x 2"
- Shpg 1 lb.



2" x 8" Air Cylinder



ITEM 4-1971

\$89.95

• New, BIMBA, TRD, double acting air cylinder. Tie-rod construction. Foot mounted. Cylinder has a integrated cushion valve on each end.

SPECIFICATIONS

- Model CYL-9929418
- Double Acting
- Bore/Stroke 2" x 8"
- Rod $\frac{5}{8}"$ dia.
- Pressure 250 PSI max
- Ports $\frac{3}{8}"$ NPT Ports
- Rod $\frac{7}{16}$ -20 UNF thread
- Mounting Pattern 10 7/8" x 3 1/4"
- Overall Retracted Length 13 3/4"
- Shpg 6 lbs.

5" x 12" x 1" Air Cylinder



ITEM 4-9355

\$199.95

• Unused old inventory. Tie-rod, double acting pneumatic cylinder.

SPECIFICATIONS

- Double Acting
- Bore x Stroke 5" x 12"
- Pressure 250 PSI max.
- Rod Dia. 1"
- Ports $\frac{1}{2}"$ NPT
- Retracted Length 21.75"
- Clevis Ends
- Pin Holes 0.75"
- Shpg. 5 lbs.

11.9 CFM 3 HP Single Stage Air Compressor

ITEM 4-1974

\$179.95

• New, B2800B 3 HP two cylinder single stage air compressor. Oil level sight glass.

SPECIFICATIONS

- Cylinders 2
- Stages Single
- Flow 11.9 CFM
- Pressure 131 PSI max.
- Power Req'd. 3 HP max.
- Speed 1570 RPM max.
- Rotation CCW
- Flywheel 11" A belt
- Port $\frac{1}{2}"$ NPT
- 1st Stage Bore/Stroke 2.36"/1.97"
- Mount Four 0.34" holes on 5 1/4" x 6 1/4" centers
- Size 10" x 11" x 13"
- Shpg. 25 lbs.



7.5 CFM, Single Stage Air Compressor

ITEM 4-1916

\$149.95

• New, V-twin cylinder single stage air compressor. Cast iron block and cylinder with aluminum head. Oil level sight glass.

SPECIFICATIONS

- One stage, two cylinders
- Flow: 7.5 CFM open flow
- 4.28 CFM at 110 PSI
- Pressure 115 PSI max.
- Power req'd. 2 HP max.
- Speed 980 RPM max.
- Rotation CCW
- Flywheel 10 1/2" A belt
- Port $\frac{1}{2}"$ OD tube
- 1st stage bore/stroke 55mm x 45mm
- Mount 6 7/8" x 3 5/8"
- Size 13" x 10 1/2" x 10 1/2"
- Shpg. 37 lbs.



7.1 CFM, Single Stage Air Compressor

ITEM 4-1972

\$149.95

• New, B2800 2 HP two cylinder single stage air compressor. Oil level sight glass.

SPECIFICATIONS

- Cylinders 2
- Stages Single
- Flow 7.1 CFM
- Pressure 90 PSI max.
- Power Req'd. 2 HP max.
- Speed 1000 RPM max.
- Rotation CCW
- Flywheel 11" dia. A belt
- Port $\frac{1}{2}"$ NPT
- 1st Stage Bore/Stroke 2.36"/1.97"
- Mount Four 0.34" dia. holes on 5 1/4" x 6 1/4" centers
- Size 10" x 11" x 12 1/2"
- Shpg. 23 lbs.

