



Metal Housing Pressure Switches

\$29.00 each



• Brand new, LEFOO automatic pressure switch for compressed air systems. Automatically turns electric motor ON or OFF at set values. Adjustable differential. Unloader port 1/4" OD copper tubing which allows compressor to start without back pressure load. Sturdy metal housing. Single port.

SPECIFICATIONS FOR BOTH

- Contact rating
 - Min. ON (cut-in) 40 PSI
 - 2 HP, 24 amps at 120 VAC
 - Differential 25-60 PSI
 - 3 HP, 20 amps at 240 VAC
 - Size 3 3/4" x 3 1/2" x 4 1/4"
 - Shpg. 3 lbs.
- Port 1/4" NPT

ITEM	Factory Setting		Max. OFF (cut-out)
	ON (cut-in)	OFF (cut-out)	
4-1820-H1	145 PSI	175 PSI	250 PSI
4-1820-L1	105 PSI	135 PSI	200 PSI

Heavy Duty Automatic Pressure Switches



• Brand new, SUNNY automatic pressure switch for compressed air systems. Automatically turns electric motor ON or OFF at set values. Adjustable differential. Unloader port 1/4" OD copper tubing which allows compressor to start without back pressure load. Sturdy plastic housing. Manual off switch.

SPECIFICATIONS

- Contact ratings
 - Port(s) 1/4" NPT
 - 25 amps at 120/240 VAC
 - Size 3 3/4" x 3" x 3 3/8"
 - 25 amps at 32/120/230 VDC
 - Shpg. 1 1/2 lbs.

ITEM	Port(s)	Factory Setting		Price
		ON (Cut-In)	OFF (Cut-Out)	
4-1823-L1	1	95 PSI	125 PSI	\$14.50
4-1823-H1	1	140 PSI	175 PSI	\$14.50
4-1823-L4	4	95 PSI	125 PSI	\$14.50
4-1823-H4	4	140 PSI	175 PSI	\$14.50

0-4 BAR Pressure Switch

ITEM 11-3475-A

\$19.95



• New. industrial pressure switch. Able to process air, oil and water. Commonly used on rail-ways, boilers, water treatment, fire fighting systems, and compressors.

SPECIFICATIONS

- Brand WAAREE
- Model CNI-3
- Range 0-4 BAR (0-58 PSI)
- Max. Pressure 25 BAR (362.5 PSI)
- Differential Pressure 0.1 to 0.3 BAR (1.45 to 4.35 PSI)
- Max. Temperature 150° C (302° F)
- Mounting Direct/Panel
- Switch 1 SPDT Snap action micro switch
- Contact Rating 15 Amps 250 Volts AC, 0.4 Amps 110 Volts DC
- Electrical Connection P.G. 13.5 mm
- Process Connection Size 3/8" BSP male standard
- Size 2 3/8" x 1 1/2" x 2 1/2"
- Shpg 3 lbs.

ITEM 11-3475-B

SPECIFICATIONS

- Range 0-6 BAR (0-87 PSI)
- Size 4 1/2" x 5" x 1 3/4"
- Differential Pressure 0.25 to 1.5 BAR (3.6 to 21.7 PSI)
- Shpg 3 lbs.

\$19.95

Automatic Pressure Switches

\$14.50 each

• Brand new, LEFOO automatic pressure switch for compressed air systems. Automatically turns electric motor ON or OFF at set values. Adjustable differential. Unloader port 1/4" OD copper tubing which allows compressor to start without back pressure load. Sturdy plastic housing. Manual OFF switch.

SPECIFICATIONS

- Contact ratings
 - 120 VAC: 1 1/2 HP at 20 amps
 - 240 VAC: 2 HP at 12 amps
 - 240 VAC 3 Ph.: 3 HP at 9.6 amps
- Size 3 3/4" x 3 3/8" x 3 1/4"
- 32 VDC: 1/4 HP at 8.6 amps
- 120 VDC: 1/4 HP at 3.1 amps
- 240 VDC: 1/4 HP at 1.6 amps
- Shpg. 1 1/2 lbs.



ITEM	Factory Setting		Min. On (Cut-In)	Max. OFF (Cut-Out)	Differential	Ports
	ON (Cut-In)	OFF (Cut-Out)				
4-1819-L1	95 PSI	125 PSI	35 PSI	150 PSI	30-40 PSI	1/4" NPT (x1)
4-1819-L4	95 PSI	125 PSI	35 PSI	150 PSI	30-40 PSI	1/4" NPT (x4)
4-1819-H1	140 PSI	175 PSI	50 PSI	175 PSI	35-55 PSI	1/4" NPT (x1)
4-1819-H4	140 PSI	175 PSI	50 PSI	175 PSI	35-55 PSI	1/4" NPT (x4)



ITEM 11-3044-E



ITEM 11-2576

Automatic Pressure Switches

• New automatic pressure switches. For compressed air of water systems. Automatically switch electric motor ON or OFF at pre-set values.

ITEM	Pressure (PSI)				Port	Size	Shpg	Price
	HP	Voltage	ON	OFF				
11-3044-E	1	115/230	20	40	1/4" Hosebarb	4" x 2 3/4" x 3 1/2"	2 lbs.	\$11.95
11-2576	1 1/2	115	20	40	1/4" NPT	3 1/2" x 2 1/4" x 3"	1 1/2 lbs.	\$12.99

Portable Air Carry Tanks



• Brand New IRON HORSE portable air carry tanks. Ideal for filling tires, blowing off equipment and other inflation needs when a compressor isn't handy. Features include heavy gauge steel construction, shut-off valve, filling valve, pressure gauge, 3 foot hose, tire chuck and built-in carry handle. Pressure 150 PSI max.

5 Gal. Tank
ITEM 4-1890-5
\$55.15

SPECIFICATIONS

- Capacity 5 gallon
- Size 17 1/2" x 9 3/4" x 11 1/2"
- Shpg. 20 lbs.



10 Gal. Tank
ITEM 4-1890-10
\$86.65

SPECIFICATIONS

- Capacity 10 gallon
- Size 22 1/2" x 12" x 14"
- Shpg. 34 lbs.



2-Way N.C. Air Control Valve

ITEM 20-1674
\$29.99

• New, SAF HOLLAND model XB-11745 fifth wheel release valve. Pull knob, spring return. For kingpin or slider lock release. Ports labeled on valve body as #1 Delivery Port, to the fifth wheel slide assembly, and #2 Supply Line, from the truck.

SPECIFICATIONS

- 2-Way N.C.
- Max. Pressure 200 PSI
- Ports 1/2" NPTF
- Pull Type, Spring Return
- Size 3 1/2" x 1 3/4" x 1 3/8"
- Shpg 0.55 lb.



120 Volt AC 2 Way Solenoid Valve

ITEM 20-1603
\$8.95

• New, GOULD ALLIED CONTROL model 306x 14 two way normally closed solenoid valve. For use in low pressure water systems.

SPECIFICATIONS

- Configuration 2 way N.C.
- Voltage 120 VAC
- Power 9 W
- Duty Intermittent
- Maximum Opening Pressure Difference 12 PSI
- Ports 1/4" NPTF
- Size 1 5/8" x 1 1/2" x 2 7/8"
- Shpg. 1 1/2 lbs.



115 VAC Solenoid Valve

ITEM 4-1922

\$8.95

• New PARKER model 15-200470-001B solenoid valve. Normally closed, furnished with brass right angle hose barb adapters (1/4" ID on inlet and 1/8" ID on outlet). Stainless steel body.

SPECIFICATIONS

- Voltage 115 VAC
- Power consumption 6 Watts
- Pressure Rating 10 PSI
- Orifice 1/8"
- Ports 1/8" NPT
- Size 2" x 1 3/8" x 2 1/4"
- Shpg. 1 lb.



1/8" NPT Bronze Air Muffler

ITEM 4-11261

• New, HUMPHREY model HKM-10 brass air muffler.

SPECIFICATIONS

- Thread 1/8" NPT male
- Hex Size 7/16"
- Size 1/2" dia. x 3/4" long
- Shpg. 1/16 lb.



99¢