

2.50-4 Wheel Assembly

ITEM 1-5932

\$5.95

• New, rubber tire with tube on steel wheel. Offset hub.

SPECIFICATIONS

- Size 2.50-4
- O.D. 8 1/2"
- Bore 5/8" dia.
- Thru Bore Length 1 1/16"
- Tread Width 2 3/16"
- Tube Type
- Load Range 297 lbs. Pressure 30 PSI max.
- Ply Rating 2
- Shpg. 4 lbs.



11 x 4.00-5 Wheel Assembly

ITEM 1-6173

\$29.95

• New, CST 50076282 pneumatic tire mounted on steel rim. Not for Highway Service.

SPECIFICATIONS

- Size 11 x 4.00-5
- Outside Diameter 11" dia.
- Cross Section 3 3/4" Wide
- Tread Smooth
- Bore 1/2" dia.
- Bore Thru-Length 4 1/2"
- Hub Type Centered
- Bearing Ball Bearing
- Tire Tubeless
- Load Rating 330 lbs.
- Pressure 46 PSI max.
- Ply Rating 4
- Shpg. 7 lbs.



ST175/80D13 Trailer Wheel Assembly

ITEM 1-6207

\$29.95

• New, KENDA LOADSTAR K550 high speed trailer tire for highway use.

SPECIFICATIONS

- Brand Kenda
- Model Number Loadstar K550
- Size ST175/80D13
- Outside Diameter 23 1/2"
- Cross Section 6 1/2" Wide
- Tread Rib
- Tread Width 4 1/2"
- Back space 3"
- Tire Tubeless
- Mount: 4 hole on 4" B.C. 2 1/2" dia. pilot
- Load Rating 1100 lbs. @ 35 PSI
- Pressure 35 PSI max.
- Ply Rating 4
- DOT Approved for Highway Use
- Shpg. 34 lbs.



Trailer Bearing Kits

• Brand new, DURA-ROLL replacement trailer bearing kit. Use with boat, camping, utility and snowmobile trailers. 1 kit per wheel required. Bearings must be packed with grease before installation. Kit contents available at www.surpluscenter.com. Fully tested and exceeds VESC regulations. Installation instructions included.



Typical Axle					
ITEM	Bearing	Bore	Rating	Shpg.	Price
	Inner	Outer	(lbs.)		
1-3535	1"	1"	2000	1 lb.	\$14.85
1-3536	3/4"	3/4"	2000	1 lb.	\$11.90
1-3537	1 1/4"	1 1/4"	2000	1 1/2 lbs.	\$14.35
1-3538	1 3/8"	1 1/16"	3500	1 lb.	\$15.00
1-3539	1 1/16"	1 1/16"	2000	1 lb.	\$14.50

18 x 6.50-8 Wheel Assembly

ITEM 1-5725

\$32.99

• New, WANDA pneumatic tire mounted on steel rim. NOT for Highway Service.

SPECIFICATIONS

- Size 18 x 6.50-8
- Outside Diameter 18"
- Cross Section 6 1/2" Wide
- Tread Knobby
- Tread Width 5 1/2"
- Bore 1"
- Bore Thru-Length 3"
- Hub Type Centered
- Tire Tubeless
- Load Rating 330 lbs. @ 10 PSI
- Ply Rating 2
- Shpg. 16 lbs.



4.10/3.50-4 Wheel Assembly

ITEM 1-4932

\$5.95

• New, pneumatic tire mounted on steel rim.

SPECIFICATIONS

- Size 4.00/3.50-4
- Ball bearing
- Outside dia. 10 1/4"
- Tube type
- Cross section 3 1/4"
- Load rating 300 lbs.
- Tread Knobby
- Pressure 30 PSI max.
- Hub 5/8" bore x 2 3/8" wide
- Ply rating 2
- Hub type offset
- Shpg. 5 lbs.



4.10/3.50-4 Wheel Assembly

ITEM 1-4889

\$2.99

• New, pneumatic tire mounted on plastic rim. Tires may be dusty and have some grime on them from warehouse storage.

SPECIFICATIONS

- Size 4.00/3.50-4
- Outside Diameter 10 1/4"
- Cross section 3 1/4"
- Tread Knobby
- Hub 5/8" bore x 2 7/16" wide
- Hub Type Offset
- Bearing Plastic bushing
- Tire Tube type
- Load Rating 300 lbs.
- Pressure 30 PSI max.
- Ply Rating 2
- Shpg. 5 lbs.



Hi-Speed Wheel Hubs



• Brand new. Use with a 1" diameter spindle to mount high speed wheels on small trailers. Includes grease cap, tapered roller bearings and seal. **Shpg. 7 lbs.**

ITEM	Bolts	Bolt Circle	Type	Price
1-1133	4	4"	Lug Bolt	\$43.95
1-1134	5	4 1/2"	Lug Bolt	\$46.70
1-4884	4	4"	Stud	\$45.05
1-4885	5	4 1/2"	Stud	\$48.00

1" Trailer Spindle

ITEM 1-1128

• Brand new steel trailer spindle with castle nut. 1" diam. x 8 1/2" long. **Shpg. 4 lbs.**



13 x 5.00-6 Pair Snowblower Wheels

ITEM 1-5833

\$36.95

• New pair of CARLISLE model X-TRAC tires mounted on black painted steel wheels. Built for snow blowers. Directional lug tread mounted with 1/4" diameter cross-hole to outside. Not for highway service.

SPECIFICATIONS

- Size 13 x 5.00-6
- O.D. 12"
- Tread Directional lug
- Tread width 4 1/2"
- Bore 3/4" diam.
- Bore Thru-Length 4 1/2"
- Max. Pressure 20 PSI
- Offset None
- Crosshole Diameter 1/4"
- Load Range 290 lbs. (per tire)
- Hub Smooth w/crosshole
- Inner hub to crosshole length 4 1/4"
- Tubeless
- Ply Rating 2 Ply
- Shpg. 19 lbs.



4.80-12 Wheel Assembly Pair

ITEM 1-6206-2

\$69.95

• New, LOADSTAR ST32306 high speed trailer tire for highway use. Sold in pairs.

SPECIFICATIONS

- Brand Kenda
- Model Number Loadstar ST32306
- Size 4.80-12
- Outside Diameter 20"
- Cross Section 5" Wide
- Tread Sawtooth
- Tread Width 3 1/4"
- Back space 2 1/2"
- Mount: 4 hole on 4" B.C. 2 3/4" dia. pilot
- Tire Tubeless
- Load Rating 990 lbs. @ 90 PSI
- Pressure 90 PSI max.
- Ply Rating 6
- DOT Approved for Highway Use
- Shpg. 44 lbs.



4.80/4.00-8 Wheelbarrow Wheel

ITEM 1-5684

\$65.60

• New, LOADSTAR wheelbarrow tire on steel wheel with ball bearings. NHS

SPECIFICATIONS

- Size 4.80/4.00-8
- Outside Diameter 16"
- Tread Sawtooth
- Tread Width 3 1/4"
- Cross section 4"
- Bore 5/8"
- Bore Thru-Length 6"
- Hub Type Centered
- Bearing Ball
- Tire Tubeless
- Load Rating 590 lbs.
- Pressure 30 PSI max.
- Ply Rating 4
- Shpg. 12 lbs.



8" x 5.5" Steel Wheel Rim w/Bearings

ITEM 1-5079

\$5.99

• New take-offs, black steel rim with dual ball bearings for 8" tires.

SPECIFICATIONS

- Wheel Rim Size 8" x 5.5"
- O.D. 8 7/8"
- Width 6 5/16"
- Bearings Ball
- Bore 3/4"
- Hub thru length 3 1/16"
- Hub type Offset
- Shpg. 8 lbs.

