
5"x 11/2" Swivel Stem Caster

w/ Swivel & Wheel Lock

ITEM 1-3311 \$19.99



SPECIFICATIONS

- Wheel size 5" x 1½"
- · Load capacity 325 lbs. • Mounting height 61/4"
- · Stem friction grip stem mount 1" dia. x 21/2"
- · Shpg. 6 lbs.

5" x 11/4" Swivel Plain Stem Caster

ITEM 1-4538 **\$4.95**

New, MEDCASTER

model# HC05RPP125TLCL02 plain stem caster with sheet metal threadguards and central total brake. Intended for use with hospital beds. Braking mechanism is operated by rotating 11mm (0.433") hex.


- · Load Capacity 260 lbs.
- Mounting Height 6⁷/₈"
- Brake Wheel and Swivel
- Wheel Size 5"x 11/4"
 Load Canacity 260 lhs Wheel Tread Gray TPR
 - Caster Wheel Core Material Polypropylene
- Caster Wheel Bearing Ball Shpg. 5 lbs.

5" x 11/8" Swivel Stem Caster ITEM 1-1591 \$6.95

• New. Ball bearing swivel stem caster with 5" diam. x 11/8" wide cushion rubber wheel. 7/16" diam. x 11/2" stem with retention ring. 150 lb. capacity. Shpg. 4 lbs.

5"x 15/16" Swivel Stem Caster w/ Wheel Lock

ITEM 1-3307 \$5.99



SPECIFICATIONS

- Wheel size 5" x 15/16"
- · Load capacity 125 lbs.
- Mounting height 53/4" • Stem threaded 1/2"-13 x 11/2
- Shpg. 11/2 lbs.

Grip Ring Caster Sockets











1-3668

1-5361

1-4898

• Brand new, use to mount grip ring casters with 7/16" dia. stem into steel tubing. Shpg. 1/10 lb.

ITEM	Fits into	Length	Price
	1" OD 16 gauge tubing	1½″	<i>\$0.60</i>
1-3668	3/4" OD 16 gauge tubing	1½″	<i>\$2.55</i>
1-5361	%16" OD 16 gauge tubing	13⁄8″	\$.39
1-4898	Steel Corner Bracket	15⁄8″	<i>\$.59</i>

5"x 15/16" Swivel Stem Caster ITEM 1-4751 \$3.95

 New, FAULTLESS model# 30807 threaded stem caster. Ball bearing in swivel head.

SPECIFICATIONS

- . Wheel Diameter 5"
- Wheel Width ¹⁵/₁₆"
- . Load Capacity 125 lbs.
- Mounting Height 5¾"
- Wheel Tread Gray TPR
- Mount ½"-13 x 1½" long threaded stem
- Caster Wheel Core Polypropylene
- · Caster Wheel Bearing Plain
- Shpg. 21/2 lbs.

5" x 15/16" Swivel Stem Caster w/ Brake

ITEM 1-4234 \$3.95



 New, FAULTLESS swivel threaded stem caster with brake. Zinc plated steel yoke. Solid polypropylene wheel.

SPECIFICATIONS

- Wheel Size 5" dia. x 15/16" Mounting height 513/16"
- · Load Capacity 150 lbs.
- Stem Threaded
- Mount: ½"-13 x 1½"
- Shpg. 1½ lbs.


4" x 21/2" Swivel Stem Caster w/ Brake ITEM 1-4635 \$2.95

New, threaded stem swivel caster.

SPECIFICATIONS

- Wheel Diameter 4" dia. Wheel Width 2½" Wide
- · Load Capacity 100 lbs.
- Mounting Height 4½"
- Brake Wheel lock
- Mount 1/2"-13 threaded
- stem, 1" long
- · Wheel Tread Material **Black Plastic**
- Caster Wheel Core Material Plastic
- · Caster Wheel Bearing Plain
- Shpg. 2 lbs.

4" x 1" Grip Ring Caster ITEM 1-3766



SPECIFICATIONS

- Wheel size 4" dia. x 1"
- · Load capacity 150 lbs.
- Mounting height 45%"
- · Stem grip ring
- 0.845" dia. x 2"

• Mount 3/8"-16 x 3/4" long

Wheel Tread Material

Red Polyurethane

Material Polyolefin

· Caster Wheel Core

threaded stem

. Shpg. 3 lbs.

4" x 15/16" Swivel Stem Caster ITEM 1-6123



SPECIFICATIONS


- Wheel Diameter 4'
- Wheel Width 15-16"
- . Load Capacity 150 lbs.
- Mounting Height 4¾" Brake None
- Caster Wheel Bearing Ball
 Shpg. 0.8 lbs.

Swivel Caster ITEM 1-2404 \$5.99

3"x 114" Stem

· New. Swivel stem caster with 3" diam. x 11/4" wide solid polypropylene wheel. 1"-12 diam. x 51%" threaded stem. Working height 41/4" (floor to base of stem). Load capacity 100 lbs. Shpg. 5 lbs.

3"x 13/16" Rigid Stem Caster ITEM 1-3394 \$1.99



SPECIFICATIONS

- Mounting height 3½"
- Wheel size 3" x ¹³/₁₆" · Load capacity 90 lbs.
- Stem grip ring 7/16" dia. x 2"
- Shpg. 1 lb.

3"x 1/2" Swivel Stem Caster w/ Brake ITEM 1-5146

 New, TENTE swivel threaded stem caster with wheel brake.

SPECIFICATIONS

- Brake Wheel
- Wheel Diameter 3" (2.95") Wheel Tread Material Black Flastic Tire • Wheel Width 1/2" tread, 2" · Caster Wheel Core
- overall . Load Capacity 110 lbs.
- Mounting Height 3"

- Material Polyamide · Caster Wheel Bearing

3"x 7/16" Swivel Stem Caster w/ Brake ITEM 1-4758 \$2.99

 New, SHEPHERD threaded stem caster with total brake.

SPECIFICATIONS

- Wheel Diameter 3" • Wheel Width 7/16" tread,
- 25/16" overall
- Mounting Height 3¾"
- threaded stem
- · Load Capacity 165 lbs.
- Mount ½"-13 x 1" long
- · Brake Wheel and Swivel
- · Wheel Tread Material Gray Urethane
- · Caster Wheel Core Material Polyolefin · Caster Wheel Bearing
- Plain · Shpg. 1.5 lbs.

1.5" Dual Wheel Swivel Caster Set ITEM 1-4718

.**99**¢ • New, set of 4 nylon hooded swivel casters with dual plastic wheels and grip ring stem. Two casters have wheel rotation locks.

Independent wheel rotation in each caster.

SPECIFICATIONS

- (2 per caster)
- Load Capacity 50 lbs. ea. ring stem (200 lbs. per set)
- Mount 7/16" dia. x 1" grip
 - Shpg. ½ lb.





