POWER TEAM

10.000 PSI Air Driven **Hydraulic** Pump 🛦 💄



ITEM 9-8000 **\$662.9**0

 Brand new, POWER TEAM PA6 Model F air driven hydraulic pump designed to operate single acting cylinders. Compact, lightweight and portable for powering all types of hydraulic equipment. Internal relief valve.

POWER TEAM

<u>SPECIFICATIONS</u>

- Air Consumption 20 CFM
- Flow:
- 78 cu. in./min at 500 PSI 29 cu. in./min at 5000 PS 10 cu. in./min at 10000 PSI
- Operation Hand/Foot
- Air Requirement 40-100 PSI Reservoir Size 105 cubic inches
- Hydraulic Pressure 10000 PSI Sound Level 85 dBA at 10000 PSI
 - Air Inlet Port 1/4" NPT
 - Hyd. Oulet Port 3/8" NPT

 - Size 9½" x 5" x 7¾"
 - Shpg. 18 lbs.
 - Reservoir Useable 295 cu. in
 - Outlet Port 3/8" NPT

SPECIFICATIONS

• Power ½ Hp

Voltage 115 VAC

· Amperage 10 amps

Pressure 10000 PSI

Operation Electric

. Sound Level 81 dBA at 10,000 PSI Reservoir Size 2 gallon

10,000 PSI, ½ HP

ÜSÄ

• Brand new, POWER TEAM PE172 115

volt AC hydraulic pump designed to op-

erate single acting cylinders. Two speed

delivery flow for fast cycle times. Remote

ON/OFF pendant control with ten foot cord.

Two position valve to either advance cyl-

inder and hold pressure with power off or

advance cylinder and release pressure with

power off. Valve also used to release pres-

• Flow:

sure when in the hold pressure position.

115 VAC

Hvdraulic Pump A

ITEM 9-8003

\$3232.05

• Size 113/8" x 91/4" x 181/2"

290 cu. in./min at 0 PSI

190 cu. in./min at 100 PSI

20 cu. in./min at 5000 PSI

16 cu. in./min at 10000 PSI

Shpq. 40 lbs.

10,000 PSI, ¼"Hose ∧





• Brand new, POWER TEAM hose for use with Power Team 10,000 PSI hydraulic accessories. Two ply rated hose reinforced with two braids of high tensile steel wire. Rubber covering is oil and weather resistant. MSHA approved. Plastic hose guards on each end with male pipe fittings.

• Pressure: **SPECIFICATIONS**

- Hose I.D. 1/4"
- End fittings 3/8" NPT
- operating 10,000 PSI burst 20,000 PSI

\$128.50 ITEM 9-8010-6 • Length 6 ft. Shpg. 2 lbs.

ITEM 9-8010-10

Length 10 ft. Shpg. 4 lbs.

With Half Coupler

ITEM 9-8009

 Coupler half 9798 male. Length 6 ft. Shpg. 2 lbs.

By Prince Manufacturing

Wolverine Hydraulic Hand Pump Heads and Reservoirs

Brand new, WOLVERINE by PRINCE hydraulic hand pump heads and reservoirs.

• Hand pump head is sold separately from the hydraulic reservoir for greater variety of combinations.

9-8436 9-8437

Hand Pump Heads

- Hand pump head bolts to the top of reservoir (sold separately at right).
- Single acting version has large release valve knob to give added control for metering loads down.
- Double acting version has 4 way, 3 position directional control valve.
- Hand pump head and reservoir sold separately.

SPECIFICATIONS

- Pressure 3500 PSI Shpg. 10 lbs.
- Size 27%16" x 21/2" x 91/4" including handle • Outlet port 3/6" NPT adapter installed in #4 BSPP port

	Cylinder	cuin./cycle	
ITEM	Operation	Flow	Price
9-8436-15	SA	1.5	<i>\$155.25</i>
9-8436-21	SA	2.1	<i>\$172.80</i>
9-8437-15	DA	1.5	<i>\$168.10</i>
9-8437-21	DA	2.1	\$172.80

Hand Pump Reservoirs









• Use with Wolverine hand pumps. Pump head (sold separately at left) bolts directly to the top of reservoir. Brass breather cap installed in top of reservoir. Steel construction, side mounting holes.

• Hand pump head and reservoir sold separately.

Capacity in Gallons							
ITEM				Shpg.	Price		
9-8438-60	0.25	0.225	5.96" x 3.94" x 5.04"	4 lbs.	<i>\$47.95</i>		
9-8438-180	0.8	0.72	5.984" x 3.94" x 9.75"	5 lbs.	<i>\$57.40</i>		
9-8438-300	1.3	1.17	6.89" x 6.89" x 6.32"	7 lbs.	<i>\$67.50</i>		

Prince Hydraulic Hand Pump

ITEM 9-014

 Brand new PRINCE. Operates hydraulic presses, dumps, plows, snow blades, hydraulic tables, frame straightners, etc.

 Quick change. Choose from three pressure and volume rates with 3 position fulcrum. Magnetic plug in reservoir traps ferrous metal particles to keep from circulating. Mount pump in various positions with 2 position handle. Model PM-HP-10-B.

SPECIFICATIONS

- Vol/press 1.25 cu in, 1500 PSI*, 0.95 cu 14 ¾" handle in, 2000 PSI*, 0.60 cu in, 3000 PSI*
- 1 gal reservoir
- IN check valve
- Release valve

- Press port 3/8" NPT
- 60-65 lbs applied force on handle
- 16 ½" x 10 ¼" x 7 ½"
- Shpq 34 lbs
- * At applied force of 60-65 lbs. on handle. Pressure to 6000 PSI can be developed with more force.

Brand Hand Pumps A

• Brand new, BRAND. Double action hand pump displaces oil on both forward and return motion for rapid cylinder travel. Choice of integral tank (ITEM 9-4144) or port for use with external tank (ITEM 9-3509).

SPECIFICATIONS

Port SAE 6

• 0.6 cu. in./complete stroke • Adj. relief valvel Lever release 3000 PSI

ÜSÄ



		Tank	Size		
ITEM	Model	Capacity	(not including handle)	Shpg.	Price
9-4144	HP61DA80	80 cu. In.	7″ x 4½″ 13½″	16 lbs.	<i>\$272.50</i>
9-3509	HP61DATI	None *	7" x 41/2" x 51/2"	13 lbs.	\$277.20

^{*} ¼" NPT port for use with external reservoir (not included)