

3" x 6.125" x 1.5"**ITEM 9-2191-R****SPECIFICATIONS**

- Unused old inventory
- Double Acting
- Bore x Stroke 3" x 6 1/8"
- Pressure 2500 PSI max.
- Rod Diam. 1 1/2"

- Ports SAE 8
- Retracted Length 21 3/4"
- Tang Ends
- Pin Holes 1"
- Shpg. 45 lbs.

\$76.50**3" x 10" x 1.25"****ITEM 9-16375****SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 3" x 10"
- Pressure 3000 PSI max.
- Rod Dia. 1.25"

- Ports SAE 8
- Retracted Length 20.25"
- Flat Ends
- Shpg. 25 lbs.

\$69.95**3" x 16" x 1.5"****ITEM 9-12924****SPECIFICATIONS**

- Unused old inventory
- Double Acting
- Bore x Stroke 3" x 16"
- Pressure 2500 PSI
- Rod Dia. 1.5"
- Ports SAE 8

- Retracted Length 36"
- Swivel Eye Ends
- Rod End: Width 1.71"
- Base End: Width 1.76"
- Swivel Eye Width 1.375"
- Pin Holes 1 1/2"
- Shpg. 66 lbs.

\$149.95**3" x 7.5" x 1.25"****ITEM 9-16165****SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 3" x 7.5"
- Pressure 2700 PSI max.
- Rod Dia. 1.25"
- Ports SAE 6

- Retracted Length 15"
- Cross-Tube Ends
- Rod End: Width 1.75"
- Base End: Width 4.25"
- Pin Holes 1"
- Shpg. 22 lbs.

\$99.95**3" x 12" x 1.5"****ITEM 9-16571****SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 3" x 12"
- Pressure 2500 PSI max.
- Rod Dia. 1.5"

- Ports 1/2" NPT
- Retracted Length 22.25"
- Clevis Ends
- Pin Holes 1"
- Shpg. 31 lbs.

\$109.95**3" x 7.75" x 1.5"****ITEM 9-9756****SPECIFICATIONS**

- Unused, old inventory
- Double acting
- Bore/Stroke 3" x 7 3/4"
- Pressure 2500 PSI
- Rod dia. 1 1/2"
- Ports SAE 8

- Retracted lgth. 24 3/4"
- Rod End Thread-on Tang
- Max Thickness 2"
- Base End Clevis
- Pin Holes 1 1/4"
- Shpg. 34 lbs.

\$144.95**3" x 14" x 2"****ITEM 9-20765****SPECIFICATIONS**

- Unused old inventory
- Double Acting
- Bore x Stroke 3" x 14"
- Pressure 3000 PSI max.
- Rod Dia. 2"

- Ports SAE 6
- Retracted Length 25.75"
- Clevis Ends
- Pin Holes 1.375"
- Shpg. 46 lbs.

\$149.95**3" x 8" x 1.25"****ITEM 9-16163****SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 3" x 8"
- Pressure 2500 PSI max.
- Rod Dia. 1.25"

- Ports 1/2" NPT
- Retracted Length 20.25"
- Clevis Ends
- Pin Holes 1"
- Shpg. 22 lbs.

\$119.95**3" x 15" x 1.5"****ITEM 9-7339****SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 3" x 15"
- Pressure 3200 PSI max.
- Rod Dia. 1.5"
- Port SAE 8
- Retracted Length 61"

- Crosstube Ends
- Rod End Outside Width 2.69"
- Base End Outside Width 5"
- Pin Holes 1.25"
- Shpg. 60 lbs.

\$109.99**3" x 8.75" x 1.5"****ITEM 9-20764****SPECIFICATIONS**

- Unused old inventory
- Double Acting
- Bore x Stroke 3" x 8.75"
- Pressure 2500 PSI max.
- Rod Dia. 1.5"
- Ports JIC 6
- Retracted Length 8.25"
- Rod End: Tang
- Width 2.102"

- Pin Hole 1.5"
- Base End: Male Trunnion
- Pin Outside/Inside Width 7.25" / 4.75"
- Pin-Center-To-Rod Pin Center 8.25"
- Pin Center To Base End 8"
- Pin Diameter 1.5"
- Shpg. 35 lbs.

\$129.95**3" x 15" x 1.5"****ITEM 9-7340****SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 3" x 15"
- Pressure 3200 PSI max.
- Rod Dia. 1.5"
- Port SAE 8
- Retracted Length 61"

- Crosstube Ends
- Rod End Outside Width 2.69"
- Base End Outside Width 5"
- Pin Holes 1.25"
- Shpg. 60 lbs.

\$109.99**3" x 15" x 1.5"****ITEM 9-7341****SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 3" x 15"
- Pressure 3200 PSI max.
- Rod Dia. 1.5"
- Port SAE 8
- Retracted Length 61"

- Crosstube Ends
- Rod End Outside Width 2.69"
- Base End Outside Width 5"
- Pin Holes 1.25"
- Shpg. 60 lbs.

\$109.99**3" x 9" x 1.5"****ITEM 9-20768****SPECIFICATIONS**

- Unused old inventory
- Double Acting
- Bore x Stroke 3" x 9"
- Pressure 3000 PSI max.
- Rod Dia. 1.5"

- Ports SAE 8
- Retracted Length 22"
- Clevis Ends
- Pin Holes 1"
- Shpg. 34 lbs.

\$99.95**3" x 20" x 1.5"****ITEM 9-16136****SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 3" x 20"
- Pressure 3000 PSI max.
- Rod Dia. 1 1/2"
- Ports SAE 8

- Retracted Length 28.125"
- Rod End: Threaded
- Thread size-Pitch 1 1/4"-12"
- Base End: Clevis
- Pin Hole 1"
- Shpg. 43 lbs.

\$89.95**SPECIFICATIONS**

- Unused, old inventory
- Double Acting
- Bore x Stroke 3" x 16"
- Rod Ends Tapped
- Thread size-Pitch 1 1/8"-12

- Thread Depth 3"
- Pressure 2500 PSI max.
- Rod Dia. 1 3/4"
- Ports SAE 6, See Above
- Overall Length 92 1/2"
- Shpg. 190 lbs.

*Truck freight only***3" x 16" x 1.75"****ITEM 9-10315**

- Two independent 3" x 16" x 1.75" welded cylinders joined in the middle. Four SUN model CACA-LHN adjustable, counterbalance valves.

SPECIFICATIONS

- Unused, old inventory
- Double Acting
- Bore x Stroke 3" x 16"
- Rod Ends Tapped
- Thread size-Pitch 1 1/8"-12

- Thread Depth 3"
- Pressure 2500 PSI max.
- Rod Dia. 1 3/4"
- Ports SAE 6, See Above
- Retracted Length 92 1/2"
- Shpg. 190 lbs.

*Truck freight only***3" x 16" x 1.75"****ITEM 9-10009**

- Tandem welded cylinder. Two independent cylinders joined in the middle. Four counterbalance valves. Each cylinder has two bleeder valves.

SPECIFICATIONS

- Unused, old inventory
- Double Acting
- Bore x Stroke 3" x 16"
- Pressure 3000 PSI max.

- Rod dia. 1 3/4"
- Ports SAE 6
- Overall lgth. 62"
- Rod tapped 1 1/8"-12 x 3"
- Shpg. 107 lbs.

Truck freight only