

13200 BTU **12 VDC** Cab Heater With 2 Speed Fan

12500 BTU **12 VDC** Cab Heater

With 3 Speed Fan



#### ITEM 28-1826

Brand new, MARADYNE Model H-400012 cab heater. Heater uses engine coolant to heat your cab. Mounts easily to floor of cab. 2 speed fan with speed control switch built into the housing. Four, rotatable, adjustable opening louvers. Glass-filled nylon housing, aluminum tube and fin heating core.

# **SPECIFICATIONS**

- . Heating Output 13200 BTU/HŘ
- Air Flow 200 CFM
- · Blower Motor Voltage 12 VDC
- Size 7¾" x 7¼" x 9¾"

**SPECIFICATIONS** 

One, shut-off valve %

NPTM x 5/8" hosebarb

One, 3/8" NPTM x 5/8"

Hourmeter

**SPECIFICATIONS** 

Non-resettable

ITEM 1-5081

\$25.00

hose barb

12 Volt

Digital

- Blower Motor Amperage
- 6 amps • Hose Fittings 5/8" diam. x 115/16" hose barb
- Mount Three 5/16"-18 x 1" studs

Cab Heater

ITEM 28-1827

Installation Kit

**S32.20 ∆ \$32.20** 

bushing
• Four, 5%" hose clamps
• Shpg. ½ lb.

• Two. 1/2" NPTM x 3/8" NPTF

• Shpg. 10 lbs.

## ITEM 28-1824

· Brand new, MARADYNE cab heater. Heater uses engine coolant to heat your cab. Mounts easily to wall or floor of cab. 3 speed fan. Directional airflow doors. Steel housing, aluminum tube and fin heating core. Comes with 3 speed fan switch.

# **SPECIFICATIONS**

- Heating Output 12500 BTU/HŘ
- Air Flow 200 CFM
- Blower Motor Voltage 12 VDC
- Blower Motor Amperage 2.9 amps
- Hose Fittings 5%" diam. x 1½" hose barb
- Mount Three 5/16"-18 x 1" studs
- Size 7<sup>7</sup>/<sub>16</sub>" x 7<sup>3</sup>/<sub>8</sub>" x 7<sup>1</sup>/<sub>16</sub>" **Shpg. 11 lbs**.

# **Magnetic Engine** Block Heaters

• Brand new, KAT'S MAGNUM HAN-DI-HEAT magnetic heaters. General application usage includes hydraulic reservoirs, thawing frozen locks, pipes, gutters and live stock feeders. ÜŠÄ



ITEM 11-3396

 Ideal for small engine blocks. Thermostatically controlled.

#### **SPECIFICATIONS**

- Voltage 120 VAC
- Power 200 W
- . Cord Length 43

· Heated surface dimension 3¾" x 2¼

- Size 61/2" x 21/4" x 2"
- Shpg. 1 lb.

**300 Watt** ITEM 11-3397 \$141.00

· Ideal for car and truck engine blocks. **SPECIFICATIONS** 

- Voltage 120 VAC
- Power 300 W
- Cord Length 42"
- Heated surface dimension 41/8" x 5
- Size 7" x 5" x 2"
- Shpg. 11/2 lbs.

# ATC Fuse Holder 10 pack 14 Gauge ∧

## ITEM 11-3697

· New, blue rubber fuse holder without cap. Uses ATC blade style fuses. Simply splice into circuit. Set of 10 holders. Does not include fuses.

#### **SPECIFICATIONS**

- Wire #14 AWG,
- Length 12"
- Fuse Type ATC blade
- Shpq ½ lb.

## Flat Document Holders A

Brand new. Molded plastic construction with two latches for lid and rubber seal to keep manuals, service records or other documents clean

and dry. Four holes for mounting.

Holds 81/2" x 11" documents

#### ITEM 1-3970 **SPECIFICATIONS**

- ServiceMate SM9000-8
- Document Size 8.5" x 11" x 1"
- Label area 6.25" x 2.75"
- Size 14.5" x 11" x 2.135"
- Mounting pattern 5 875" x 7
  - Shpg. 3 lbs.

#### Holds 6"x 8" documents

### ITEM 1-3972

• Size 11.2" x 8.25" x 1.95

- **SPECIFICATIONS**
- ServiceMate SM9000-16
  Mounting pattern
  Document Size 6" x 8" x 1"
  4.25" x 6" (T pattern)
- Label area 5" x 2.75"
  - · Shpg. 3 lbs.

# Round Document Holder A

ITEM 1-3971

• Brand new, SERVICEMATE SM9000-14, holds rolled up 81/2" x 11" documents. Molded plastic construction with twist lock lid and rubber seal to keep manuals, service records or other documents clean and dry.

**SPECIFICATIONS** 

• Label area 5.25" x 1.75"

 Document Size 8.5" x 11" x 1"

• Size 3.7" dia. x 12.5"

Face

• Shpg. 1/4 lb.

## **12 VDC** ÜSÄ **Electronic** Fuel Pumps A

 Brand new, FACET solid state electronic fuel pumps. For carbureted gas, diesel and blended fuel engines.

Not intended for any aircraft use. • Ports 1/8" NPT female **SPECIFICATIONS** 

## • Voltage 12 Volts DC

- Size 3" x 31/4" x 23/8"
- Amps 1.6
- · Shpg. 2 lbs.

		Range Flow		
ITEM	Model	Pressure	(GPH)	Price
28-1870	40104	1.5-4 PSI	25	<b>\$68.00</b>
28-1894 *	40102	1.5-4 PSI	25	<i>\$73.10</i>
28-1895	40106	4-7 PSI	32	<i>\$68.00</i>
28-1896		9-11.5 PSI		<i>\$85.10</i>

Same as 28-1870 but includes brass adapters to 5/16" ID hose and mounting hardware.

# 12 Volt Hourmeters

• Brand new. Shows running time of equipment. 12 volt DČ (will operate on 10-80 VDC). Non-resettable. Shpq 1/4 lb.









				- IIEM 1-1238	11EM 1-2506	11EM 1-2507	
		ÜSÄ			Panel Opening And		
e	Price	ITEM	Front Face	Mount	Rear Clearance Require	d Price	
⁄4″ x 2″	<i>\$18.75</i>	1-1238	2¾″ 0.D.	Rear Clamp	2" dia. x 13/4"	\$29.90	
7⁄8″ x 2″	<i>\$20.05</i>	1-2506	27/8" O.D.	3 holes in flange 2½" B.C.	2" dia. x 13/4"	<i>\$31.60</i>	
¾″ x 2″	<i>\$20.50</i>	1-2507	21/8" x 11/4"	2 holes in flange 13/4" c/c	1" x 1½" x 25%"	<i>\$29.90</i>	





ITEM	Decibels		Price
12-976		41/4" x 23/4" x 2"	<i>\$18.75</i>
12-977	102 dB	45/16" x 27/8" x 2"	<i>\$20.05</i>
12-978	107 dB	4¾16″ x 3¾8″ x 2″	<i>\$20.50</i>

· Brand new. Shows running time of

equipment. Digital design, no moving

parts. Spade terminals. Includes metal

clamp mounting bracket to hold meter in place in a panel. Chrome bezel.

12-24 VDC Back-Up Alarms

• Brand new, BUYERS back-up alarms.

Plastic housing, epoxy sealed from moisture,

dust and vibration. Self grounding. Back up

alarm should be louder than background

noise of all jobsites vehicle is used at. Meets

OSHA, Bureau of Mines, GSA and all state

• Voltage 12-24 VDC. Mount two 1/4" holes

regulations. Conforms to J994 criteria.

Operates on 12/24 volts DC diameter hole

Panel mount in 2"

• Shpq. 1/4 lb.