

DATA SHEET

Premium Efficiency Motor: **NT34-36-56CB**

60 Hz

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Document Generated: 5-Sep-2023

Document ID:

Customer:

MOTOR INFORMATION

HP	3/4
RPM	3600
Phase	1
Frequency	60 Hz
Voltage	115/230
Frame Size	56C
Enclosure	TEFC
Degree of Protection	IP43
Service Factor	1.15
Poles	2
Full Load Speed	3450
Insulation Class	F
Temp Rise	80°C
NEMA Code Letter	M
Duty Cycle	S1 / Continuous
Slip	4.17%
Max Ambient Temperature	40°C
Max Elevation	1000 m.a.s.l (3300 f.a.s.l)
Mounting	F1
Rotation	Bi-Directional
Mounting Type	C-Face with Removable Base
Standard	NEMA MG-1
Approvals	CSA, CE
Overload	None

EFFICIENCY/POWER FACTOR

LOAD	EFF	P. F.
100%	69.4 %	76.7
75%	66.4 %	69.7
50%	59.9 %	59.2

TORQUE

FULL LOAD	LRT	BDT
1.12 lb.ft.	290 %	295 %

AMPERAGE INFORMATION

	115V	230V
Full Load Amps	9.2	4.6
Locked Rotor Amps	69.0	34.5
No Load Current	5.65	2.825
Usable at 208V	4.9A	

BEARING INFORMATION

DE Bearing	6203 2RS
ODE Bearing	6203 2RS

CAPACITOR INFORMATION

Start Capacitor	(1)400uF/165V
Run Capacitor	--

ADDITIONAL DATA

F2 Suitable	No
Shaft Material	1045 Carbon Steel
Connection Diagram	115/230V - 6 Lead
Approximate Weight	27 lbs.


MOTOR DRAWING

Premium Efficiency Motor: **NT34-36-56CB**

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



DIMENSION - INCHES

MOUNTING					A	B	C	D	G	L	P	AB	J
E	2F1	2F2	H	BA									
2.44	3	5	0.34	2.75	6.54	6.54	11.9	3.5	0.12	8.2	7.3	5.2	1.65

SHAFT & KEY				
R	ES	S	U	NW
0.517	1.41	0.188	0.625	1.88

TERMINAL BOX				
XB	XC	XD	XE	AA
1.65	3.7	3.2	2.15	3-0.88/2-1.109

FLANGE				
AK	AJ	BF	BB	BC
4.5	5.875	3/8-16	0.16	-0.19

NAMEPLATE / WIRING

Premium Efficiency Motor: **NT34-36-56CB**

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Document Generated: 5-Sep-2023

Document ID:

Customer:

SAMPLE NAMEPLATE DATA

WORLDWIDE Electric Corp		SINGLE PHASE INDUCTION MOTOR		C SP US 256950		CE	
MODEL	FRAME 56C	LOW VOLTAGE		HIGH VOLTAGE		MADE IN CHINA	
Hz 60	ENCL. TEFC	BLUE (T1)	LINE1	BLUE (T1)	LINE1		
HP	PH 1	ORANGE (T3)		ORANGE (T3)	INS		
RPM	DUTY CONT	RED (T8)	RED (T8)				
VOLTS 115/230	CODE	WHITE (T2)	LINE2	WHITE (T2)			
AMPS	INS. F IP43	YELLOW (T4)		YELLOW (T4)	LINE2		
	DES.	BLACK (T5)	BLACK (T5)				
S. F. 1.15	LB/WT	ACCEPTABLE FOR FIELD WIRING					
SFA.	MAX. AMB. 40°C	ROTATION CCW-OPE TO REVERSE EITHER VOLTAGE					
DE/ODE BRG.	Date Code X X / X X X X	INTERCHANGE BLACK (T5) AND RED (T8) LEADS					
SERIAL NO. X X X X X X X X X X		THERMALLY PROTECTED : NONE					
WorldWide Electric Corporation							

Model	NT34-36-56CB	Frame	56C
Hz	60 Hz	Encl	TEFC
HP	3/4	PH	1
RPM	3450	DUTY	CONT
Voltage	115/230	Code	M
Amps	9.2/4.6	Ins Cl	F
S.F.	1.15	IP	IP43
SFA.	10.0/5.0	DES.	N
DE Brng	6203 2RS	WT:	27 lbs.
ODE Brng	6203 2RS		