



HANDLE KIT (ONE PER SPOOL)

HIGH PRESSURE CARRY-OVER PLUG

PRODUCT NOTES:

1. TWO SPOOL VALVE ASSY; SPOOL 1 IS 4-WAY 4-POSITION FLOAT W/ SPRING CENTER & DETENT, SPOOL 2 IS 4-WAY 3-POSITION SPRING CENTER ACTION. (THE FLOAT SPOOL IS TO HAVE METAL END CAP AND HANDLE HOUSING.) (POWER BEYOND AND CLOSED CENTER CONVERTIBLE)
2. MAX OPERATING PRESSURE: 3500 PSI
RELIEF PRESSURE SETTING: 2500 PSI @ 6 GPM FLOW (ADJUSTMENT RANGE: 2000-3500 PSI)
MAX TANK PRESSURE: 500 PSI
NOMINAL FLOW RATING: 8 GPM
MAX OPERATING TEMPERATURE: 180F.
3. PORT SIZE (INLET/OUTLET, WORK PORTS, POWER BEYOND):
#8 SAE/ORB (3/4-16UNF-2B)
4. TOP-INLET PORT, TOP OUTLET PORT AND POWER BEYOND PORT ARE TO BE SEALED WITH STEEL PLUGS.
5. NO PAINT
6. VALVE SHIPPED IN OPEN CENTER CONFIGURATION (HIGH PRESSURE CARRY-OVER PLUG IS TO BE SHIPPED UNINSTALLED).
7. HANDLE KITS ARE TO BE SHIPPED UNATTACHED.
8. FILTRATION RECOMMENDATIONS: ISO 4406 19/17/14
9. NOTE: TORQUE ON CAPSCREWS HOLDING ON GFN HANDLE HOUSINGS AND GFN END CAPS TO BE 10-12 IN-LBS.